

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

MATED WITH
PASSEND ZU
HA 16

COPYRIGHT - By -

ALL RIGHTS RESERVED.

PROJEKT NR.:

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D6	ECR-17-009069	09FEB2018	SG	MKO

SCREW TERMINATION 4 M3x10.5

CRIMP TERMINATION 5 M3x10.5

SPRING CLAMP TERMINATION 6 M3x10.5

Contact arrangement / view from termination side

Contact arrangement / view from termination side

Contact arrangement / view from termination side

Contact arrangement / view from termination side

NOTES:

1 SUITABLE CRIMP CONTACTS: SERIES HE/HA
OUTER DIMENSIONS OF INSULATION: MAX. $\phi 3,2$ MMSUITABLE HOOD SIZE 5; 7; 9; 11: SERIES HA; HD
SUITABLE INSERTION AND EXTRACTION TOOL:
SCREWDRIVER 0,5x3 DIN 5264Strip lenght: Screw conection 10mm
Spring clamp conection 10mm Crimp conection 7.5mmSTANDARDS:
DIN EN 61984; DIN EN 60664-1PACKAGING:
5 SETS IN A CARTON, PRE-MOUNTEDSPECIAL PACKAGING: Krauss-Maffei
PACKAGING UNIT: 300 PIECESSPECIAL PACKAGING: Krauss-Maffei
PACKAGING UNIT: 150 PIECESSPECIAL PACKAGING: AIS
PACKAGING UNIT: 250 PIECESSPECIAL PACKAGING: WIELAND
PACKAGING UNIT: 100 PIECES

SEE TE CONNECTIVITY QUALITYMANAGEMENT PROCEDURE NO. 1.12

Panel cut-out for contact insert

when used without housing

Assembling instruction

DISTANCE FOR SAFETY
CONTACT MARKING MAX. 24 mm

1-3	1-2	1-0	0-4	0-7	0-6	0-5	2-9	1-9	7-9	7-8	1-8	2-8	1-7	7-2	7-1	2-3	1-1	DESCRIPTION / BENENNUNG	MATERIAL	COLOR / FARBE	ITEM NO. POS.	REMARKS / BEMERKUNGEN	
																		Pin insert screw	PBT	light beige	8	with stainless steel-fixing screw	
																		Pin insert screw	PBT	light beige	7	with stainless steel-fixing screw	
																		Pin insert screw	PBT	light beige	6	with AU contact	
																		Cover	PBT	light beige	5		
																		Cover	PBT	light beige	4		
																		Cover	PBT	light beige	3		
																		pin insert spring clamp	PBT	light beige	2		
																		pin insert crimp/screw	PBT	light beige	1		
HA-16-Sti.S-B1-16-WIE	HA-16-Sti.S-B1-16-AIS	HA-16-Sti.S-B17-32-KM	HA-16-Sti.S-B1-16-KM	HA-16-Sti.S-VA-B1-16	HA-16-Sti.S-VA-B17-32	HA-16-Sti.S-AU-B1-16	HA-16-Sti.S-C-B-49-64	HA-16-Sti.S-B-49-64	HA-16-Sti.S-C-B-49-64	HA-16-Sti.S-C-B-33-48	HA-16-Sti.S-B-33-48	HA-16-Sti.S-C-B-33-48	HA-16-Sti.S-B-17-32	HA-16-Sti.S-C-B-17-32	HA-16-Sti.S-C-B-17-32	HA-16-Sti.S-C-B-1-16	HA-16-Sti.S-B-1-16	HA-16-Sti.S-B-1-16	THIS DRAWING IS A CONTROLLED DOCUMENT.	DWN Schneider 09.02.2000			
																		DIMENSIONS: mm	CHK Schweiger 09.02.2000				
																		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC 1 PLC 2 PLC 3 PLC 4 PLC ANGLES FINISH	APVD Schweiger				
																		MATERIAL	PRODUCT SPEC 108-74007				
																			APPLICATION SPEC 114-77009				
																			WEIGHT				
																			CUSTOMER DRAWING				
																				SCALE 1:1			
																					SHEET 1 OF 1		
																						REV D6	

1471-9 (1/15)

1103416

A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heavy Duty Power Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[647757-1](#) [6643411-1](#) [6646058-2](#) [6646137-1](#) [6646138-1](#) [6646479-1](#) [6646608-1](#) [6646786-1](#) [6646940-1](#) [6651091-1](#) [6651525-1](#) [6651529-1](#)
[6651788-1](#) [696475-1](#) [702-32-01109](#) [703-25-02205](#) [73000005059](#) [73000005642](#) [73080255059](#) [73080965046](#) [765-15-0080A](#) [765-16-0080B](#)
[765-18-0080D](#) [829992-1](#) [902-77-02113](#) [PS00/A0620/6300](#) [PS25/A0420/63](#) [129-1J](#) [1409400](#) [AN0024023](#) [E6374G1](#) [e6389g2](#) [157-43GW8](#)
[MS3117-14AC](#) [1643543-1](#) [1650540-1](#) [1651811-2](#) [1766260-1](#) [1766282-1](#) [1766966-1](#) [1791340000](#) [NLDFT-3-BL-L-S120-M40A](#) [NLDFT-N-](#)
[W-L-C240-M40B](#) [NLS-2-R-C240-M40B](#) [NLS-N-W-C240-M40B](#) [NPS-3-BL-T6](#) [1986615-1](#) [2-1589900-8](#) [2199314-1](#) [KA8102](#)