

4

3

2

1

THIS DRAWING IS UNPUBLISHED.
VERTRAULICHE UNVERÖFFENTLICHTE ZEICHNUNGRELEASED FOR PUBLICATION
FREI FUER VERÖFFENTLICHUNG
ALL RIGHTS RESERVED.
ALLE RECHTE VORBEHALTENMATED WITH:
PASSEND ZU:
BG 3REVISIONS
ÄNDERUNGEN

© COPYRIGHT - By -

DESCRIPTION
BESCHREIBUNG

DATE

DWN

APVD

P

LTR

A10

ECR-17-009069

09FEB2018

SG

MKO

1;5;6 Screw version Thermo

M3x10

8

44

52

1 Crimp version

M3x10

8

21.2

34

27

33

44

52

4 spring clamp version

M3x10

8

44

52

assembly directions

Sti

Bu

x19.5

x distance for a safe - contact max: 21mm

Printing 1-6 Thermo

4- 5- 6-

1+ 2+ 3+

Contact arrangement

view from termination side

Printing 1-6 Screw

4 5 6

1 2 3

NOTES:

1 SUITABLE CRIMP CONTACTS: SERIES HE/HA
OUTER DIMENSIONS OF INSULATION: MAX. Ø3,2 MM2 SUITABLE HOOD SIZE 3: SERIES HB; HD; HIP; EMV
SUITABLE INSERTION AND EXTRACTION TOOL:
SCREWDRIVER 0,5x3 DIN 52643 Strip length: Screw connection 10mm
Spring clamp connection 10mm Crimp connection 7.5mm4 STANDARDS:
DIN EN 61984; DIN EN 60664-1△ PACKAGING:
5 SETS IN A CARTON, PRE-MOUNTED△ SPECIAL PACKAGING: Krauss-Maffei
PACKAGING UNIT: 150 PIECES

OBSOLETE	OBSOLETE	SUPERSEDED BY T2040063201-000	OBSOLETE	OBSOLETE	DESCRIPTION	MATERIAL	COLOR	ITEM NO. POS.	NOTES SURFACE
4	4	4	4	4	fixing screw	steel	nickel plated	blue	8 M3x10
		6			contact spring clamp	brass	silver plated		7
					contact socket screw termination	brass	gold plated		6
					contact socket screw termination	brass	silver plated		5
		1			cover spring clamp version		light grey		4
			1		cover crimp version		light grey		3
1	1			1	cover screw version		light grey		2
1	1	1	1	1	socket insert		light grey		1
0-3	0-2	7-1	2-3	1-7	1-1				
△	△	△	△	△	△				
HE.6.Bu.S.KM	HE.6.Bu.S-AU	HE.6.Bu.SC	HE.6.Bu.C	HE.6.Bu.S-T	HE.6.Bu.S				

THIS DRAWING IS A CONTROLLED DOCUMENT. DIESE ZEICHNUNG IST EIN KONTROLLIERTES DOKUMENT.		DWN	12.02.1999	 TE Connectivity
DIMENSIONS: MASSENGHEITEN: mm		CHK	18.02.1999	
TOLERANCES UNLESS OTHERWISE SPECIFIED: ALLGEMEINTOLERANZEN		APVD	-	NAME
 0 PLC ± 0.15 1 PLC ± 0.15 2 PLC ± 0.15 3 PLC ± 0.15 4 PLC ± 0.15 ANGLES / WINKEL ± 0.15 FINISH/OBERFLAECHE/FARBE		PRODUCT SPEC PRODUKTSPEZ.		Female insert HE.6.BU.C/S
MATERIAL		APPLICATION SPEC VERARBEITUNGSSPEZ.		SIZE
		WEIGHT GEWICHT		A3
		CUSTOMER DRAWING/KUNDENZEICHNUNG		CAGE CODE
		SCALE MASSTAB 1:1		00779
		SHEET BLATT		DRAWING NO ZEICHNUNGS-NR.
		1 von 1		C=1103635
		REV		A10

M3

37

27

Panel cut-out for contact insert

when used without housing

20

36

44

52

1470-19 (1/15)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heavy Duty Power Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[647757-1](#) [6643411-1](#) [6646058-2](#) [6646137-1](#) [6646138-1](#) [6646479-1](#) [6646608-1](#) [6646786-1](#) [6646940-1](#) [6651091-1](#) [6651525-1](#) [6651529-1](#)
[6651788-1](#) [696475-1](#) [702-32-01109](#) [703-25-02205](#) [73000005059](#) [73000005642](#) [73080255059](#) [73080965046](#) [765-15-0080A](#) [765-16-0080B](#)
[765-18-0080D](#) [829992-1](#) [902-77-02113](#) [PS00/A0620/6300](#) [PS25/A0420/63](#) [129-1J](#) [1409400](#) [AN0024023](#) [E6374G1](#) [e6389g2](#) [157-43GW8](#)
[MS3117-14AC](#) [1643543-1](#) [1650540-1](#) [1651811-2](#) [1766260-1](#) [1766282-1](#) [1766966-1](#) [1791340000](#) [NLDFT-3-BL-L-S120-M40A](#) [NLDFT-N-](#)
[W-L-C240-M40B](#) [NLS-2-R-C240-M40B](#) [NLS-N-W-C240-M40B](#) [NPS-3-BL-T6](#) [1986615-1](#) [2-1589900-8](#) [2199314-1](#) [KA8102](#)