

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

REVISIONS

© COPYRIGHT - TE Connectivity Ltd.

ALL RIGHTS RESERVED.

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL DRAWN	22OCT2019	RV	MB

Specifications

Timing Data					
Timing Action	Delay on Operate or Delay on Release				
Time Delay, Fixed - M83726/28, /29 and Commercial 28C, 29C	Select from 0.1 to 600 sec for Commercial Models Select from 0.1 to 500 sec for Mil-Spec Models				
Time Delay, Adjustable - M83726/30, /31 and Commercial 30C, 31C	Select one decade between 0.1 to 1.0 and 60 to 600 seconds				
Timing Accuracy (note 1)	±10% of Nominal Value				
Recycle Time (note 2)	50 ms, max., to next cycle.				
Power Interrupts	Accuracy is not affected by power interruptions up to 1 ms spaced at least 10ms apart.				
Input Data					
Input Voltage	28 Vdc nominal, range 20 - 32 Vdc				
Duty Rating	Continuous				
Input Current	110 mAdc Max @ 25°C				
Control Voltage (applies only to Delay on Release type)	20 - 32 Vdc				
Control Current	15 mAdc Max (applies only to delay on release types)				
Input Voltage Polarity Protection	The timer will be inoperative during, and undamaged by, reversal of the polarity of the input voltage.				
Output Data					
Contact Form	2 Form C (DPDT)				
Contact Material	Silver Cadmium Oxide, Gold plated				
Contact Rating in Amps (Continuous Duty)					
Type of Load	Life (Min.) Cycles	28 Vdc	115 Vac 400Hz	115/200 Vac - 3 phase 400 Hz.	60 Hz.*
Resistive	100 x 10 ³	10	10	10	2.5
Inductive	20 x 10 ³	8	8	8	2.5
Motor	100 x 10 ³	4	4	4	2.0
Lamp	100 x 10 ³	2	2	2	1.0
* 60 Hz. loads are rated at 10 x 10 ³ cycles.					
Overload Current	40 Adc; 60A, 400 Hz.				
Rupture Current	50 Adc; 80A, 400 Hz.				
Max. Contact Drop at 10A	Initial 0.150V; After Life 0.175V				
Electrical Data					
Electrostatic Discharge Withstand Voltage	16,000V				
Transients (note 3):					
Positive Transients	+80V				
Self-generated Transients	±50V, Max.				
Spike Susceptibility	±600V, 10 µs, Max.				
Insulation Resistance (note 4)	1,000 megohms at 500Vdc, between each pin and case				
Dielectric Strength (note 4)	1,000Vrms at 60 Hz at sea level, between case and all pins connected together				
Environmental Data					
Ambient Temperature Range, Operating	-55°C to +125°C				
Altitude	80,000 feet maximum				
Shock Resistance	100 G's, 6 ms.				
Vibration Resistance, Sinusoidal	Z & Y Enclosure: 30 G's, 33-3000Hz.; X & W Enclosure: 20 G's, 33-3000Hz.				
Mechanical Data					
Approximate Weight	2.5 oz. (71g) Max.				

NOTES

- The accuracy requirement applies to any combination of operating temperature and voltage. Add ±10ms for timing less than one second.
- Recycle time to assure that the next timing cycle will be completed. Units can be recycled during timing and after time-out:
Delay on operate models - Power must be OFF the input at least 10 ms. Delay on release models - Power must be ON the control terminal at least 10 ms.
- Transient specifications are based on a maximum duty cycle of 1/50.
- All wired terminals must be connected together during this test. Dielectric withstanding voltage and insulation resistance are measured between all mutually insulated wired terminals and between all these terminals and case.
- Inductive loads must be diode suppressed.

Product Facts

- Qualified to:
MIL-PRF-83726/28
MIL-PRF-83726/29
MIL-PRF-83726/30
MIL-PRF-83726/31
- Fixed delay on operate, fixed delay on release, adjustable delay on operate & adjustable delay on release
- Meets or exceeds electrostatic discharge MIL-STD-1686 Class Non-Sensitive
- Welded hermetically sealed enclosure occupies about 1 in³ (16.4 cm³)
- 10A, 2 form C (DPDT) output contacts

TD2 series time delay relays are available for delay on operate or delay on release operation. Either can be supplied as fixed or resistor adjustable types. Both military and commercial versions are offered.

These products consist of solid state timing circuits controlling our FCA-210 series relays, providing 2 Form C (DPDT) output contacts rated 10 amps. The internal timing circuit uses an R/C controlled oscillator with a program-

mable digital pulse counter, gating a semiconductor switch to operate the relay. Timing is independent of whether the controlling voltage is a ramp or step function.

For the adjustable models the user specifies a one decade range in seconds, within which the required delay will be set. This range is programmed internally at the time of manufacture. The required delay is obtained by calculating the oscillator timing resistor as

follows and connecting it externally to terminals 1D - 3D as below.

$$R_{EXT} = [(T_1 / T_0) - 1] 100K \text{ Ohms}$$

T₀ = Minimum time of selected decade in seconds.


T₁ = Required time delay.

EXAMPLE

Selected Range = 3-30 sec

Required Time = 15 sec


$$R_{EXT} = [(15/3) - 1] 100K = 400K$$



Timing Action and Terminal Wiring


Delay On Operate:

The time delay starts on the application of input voltage to X1-X2. The timing circuit energizes the end of the time delay period.




Delay On Release:


The input voltage is continuous to X1-X2. When the control voltage is applied to C1-X2 the timing circuit and the relay are both energized. The time delay starts when the control voltage is shut off.




Fixed Model




Fixed Model



Adjustable Model



Adjustable Model






Terminal designations shown in the diagrams above are for reference only. They do not appear on the relay header.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	RV	22OCT2019	 TE Connectivity	NAME			C-TD2-SERIES TIME DELAY RELAY													
DIMENSIONS: INCHES		CHK	RV	22OCT2019		PRODUCT SPEC			-													
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	MB	22OCT2019		APPLICATION SPEC			-													
<table border="1"> <tr><td>0 PLC</td><td>± -</td></tr> <tr><td>1 PLC</td><td>± -</td></tr> <tr><td>2 PLC</td><td>± -</td></tr> <tr><td>3 PLC</td><td>± -</td></tr> <tr><td>4 PLC</td><td>± -</td></tr> <tr><td>ANGLES</td><td>± -</td></tr> </table>		0 PLC	± -	1 PLC		± -	2 PLC	± -	3 PLC	± -	4 PLC	± -	ANGLES	± -	WEIGHT			-			RESTRICTED TO	
0 PLC	± -																					
1 PLC	± -																					
2 PLC	± -																					
3 PLC	± -																					
4 PLC	± -																					
ANGLES	± -																					
MATERIAL		FINISH			-			SIZE	CAGE CODE	DRAWING NO	-											
-		-			-			A3	-	C-TD2-SERIES	-											
CUSTOMER DRAWING		SCALE			NTS			SHEET		1 OF 2		REV	A									

P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	SEE SHEET 1	-	-	-

Outline Dimensions

The standard terminal types and enclosures are illustrated below with dimensions expressed as inches ± 0.010 and (millimeters ±0.25).



Part Numbering System Mil-Spec Types

Typical Mil-Spec Part Number	TD2	28-	5002	S
Series:	TD2 = Time delay relay with 2 pole, 10A output			
Mil-Spec Model:	28 = M83726/28 (Fixed, Delay on Operate) 29 = M83726/29 (Fixed, Delay on Release) 30 = M83726/30 (Adjustable, Delay on Operate) 31 = M83726/31 (Adjustable, Delay on Release)			

Time Delay Range (Within 0.1 to 500 seconds):
 For /28 and /29 types (fixed types), the delay is expressed in milliseconds in a four-digit code. The first three digits are significant. The fourth is the number of zeros following the first three.
 Example: 5002 is 50 seconds.
 For /30 and /31 types (adjustable types), the delay decade range is expressed in milliseconds in a four-digit code representing the upper limit of the range. The first three digits are significant. The fourth is the number of zeros following the first three.
 Example: 1001 is 1 second, so the range is 0.1 to 1 second.

Terminals:

S= Solder Hook

Note: Mil-spec models have "Y" type enclosure.

Commercial Types

Typical Commercial Part Number	TD2	28C-	1001	S	Y
Series:	TD2 = Time delay relay with 2 pole, 10A output				
Commercial Model:	28C = Fixed, Delay on Operate (COTS version of M83726/28) 29C = Fixed, Delay on Release (COTS version of M83726/29) 30C = Adjustable, Delay on Operate (COTS version of M83726/30) 31C = Adjustable, Delay on Release (COTS version of M83726/31)				

Time Delay Range (Within 0.1 to 600 seconds):
 For fixed types, the delay is expressed in milliseconds in a four-digit code. The first three digits are significant. The fourth is the number of zeros following the first three.
 Example: 5002 is 50 seconds.
 For adjustable types, the delay decade range is expressed in milliseconds in a four-digit code representing the upper limit of the range. The first three digits are significant. The fourth is the number of zeros following the first three.
 Example: 1001 is 1 second, so the range is 0.1 to 1 second.

Terminals:



S= Solder Hook

Enclosure

W = Mounting Studs
 X = Horizontal Flange Mount
 Y = Raised Vertical Flange Mount
 Z = No Mount

Enclosures

All Enclosures have cupro-nickel cans bright acid tin/lead plated after assembly to terminal headers.



*Metric threads available. To specify use "M" in place of "W"

ALL DIMENSIONS ARE IN INCHES(MM)

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	RV	22OCT2019	TE Connectivity		
DIMENSIONS: INCHES		CHK	RV	22OCT2019			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	MB	22OCT2019	SIZE A3		
0 PLC ± -		PRODUCT SPEC		CAGE CODE -			
1 PLC ± -		APPLICATION SPEC					DRAWING NO C-TD2-SERIES
2 PLC ± -		WEIGHT		RESTRICTED TO -			
3 PLC ± -		CUSTOMER DRAWING					SCALE NTS
4 PLC ± -		FINISH		SHEET 2 OF 2			
ANGLES ± -		MATERIAL					REV A
-		-					

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[D38999/24FJ4AN](#) [570416-000](#) [CLTEQ-M81CE-SSRELAY-4-20V](#) [4-1195131-0](#) [650069-000](#) [SMD100-2](#) [358838-000](#) [CB-1022B-78](#)
[RM707012](#) [RP410012](#) [MMS42](#) [1-640426-8](#) [2EDL4CM](#) [DTS20W19-11PD-3028-LC](#) [RM202615](#) [NC6-P104-06](#) [MSPS103B](#) [DTS26F21-](#)
[41HE-LC](#) [DTS26F21-41AE](#) [DTS26F21-41PE-LC](#) [DTS26F21-11SE-3028-LC](#) [30DCB6](#) [1932144-1](#) [293545-4](#) [LVR125S](#) [MS27466T25F4PB](#)
[CKB-38-78010](#) [TR04AI-TINELLOCKRING](#) [1206SFF150F/63-2](#) [D38999/20JB35HA](#) [TE1500A2R2J](#) [D38999/20WC8BB](#) [DTS24F19-11SC-](#)
[3028-LC](#) [D38999/24WG11HA](#) [D38999/24WG11HN](#) [MS27467T21F11H](#) [DJT16E21-11HA](#) [MS27467T21F35J](#) [MS27467T21F11J](#)
[MS27467T21F16H-LC](#) [MS27467T21F35H](#) [MS27467T21F41H-LC](#) [1206SFH150F/24-2](#) [RP330024](#) [DJT16E21-11PA-LC](#) [DJT16E21-11HA-](#)
[LC](#) [DJT16E21-11AA](#) [MS27467T21B11JA](#) [DJT16E21-11JA](#) [MS27467T21B11JA-LC](#)