


P	LTR	DESCRIPTION	DATE	DWN	APVD
	1	INITIAL CREATED	23SEP2019	CL	RS



THIS PRINT IS
PRELIMINARY
 UNQUALIFIED PRODUCT
 CONTACT PRODUCT ENGINEERING
 BEFORE USING THIS PRINT

NOTES:

- MATERIAL AND PROCESSING MUST MEET REQUIREMENTS OF TEC-138-702
- CONNECTOR SMA INTERFACE FOLLOW IEC60169-15
- PRODUCT RATING:
 TEMPERATURE: -40°C TO +85°C
 CHARACTERISTIC IMPEDANCE: 50 OHMS Normal
 FREQUENCY RANGE: DC TO 18GHz
 DURABILITY: NO LESS THAN 500TIMES
 BEND RADIUS: 54MM MIN (STATIC)
 108MM MIN(REPEATED)
- CABLE ASSEMBLY TO BE 100% SI TESTED
 VSWR: 1.3:1 MAX @ DC~18GHz
 INSERT LOSS: REFER TO TABLE
 MECHANICAL PHASE STABILITY: $\pm 5^\circ$
 MECHANICAL AMPLITUDE STABILITY: $\pm 0.1\text{dB}$
- CONNECTOR NEED COVER WITH CAP, PACKAGE FOLLOW TEC-107-115

1-2016655-5	1500±15	1.98dB@6GHz	3.96dB@18GHz
1-2016655-0	1000±15	1.42dB@6GHz	2.94dB@18GHz
2016655-6	600±10	0.97dB@6GHz	1.94dB@18GHz
PART NUMBER	LENGTH	INSERTION LOSS(MAX)	

UNIT	Q'TY	DESCRIPTION	ITEM
PC	1	LABEL	4
MR	AR	HEAT SHRINK TUBE	3
MR	AR	COAX CABLE, SOLID SPCCS 0.94MM, PTFE TAPE INSULATION, SPC TAPE OUTER CONDUCTOR 3.15MM, FEP JACKET, 50OHM, BLUE	2
PC	2	PC SMA, MALE, STRAIGHT	1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 20AUG2019 Cedar Liu	STE TE Connectivity	
DIMENSIONS: mm		CHK 28AUG2019 Roger Song		
TOLERANCES UNLESS OTHERWISE SPECIFIED.		APVD - Roger Song	NAME RF CA, SMA M TO SMA M, WITHOUT ARMOR 18GHz	
0 PLC ± 1 PLC ±0.1 2 PLC ±0.01 3 PLC ±0.001 4 PLC ±0.0001 ANGLES ±		PRODUCT SPEC -	SIZE A3	
MATERIAL TBD		APPLICATION SPEC -	CAGE CODE 00779	DRAWING NO C-2016655
FINISH - finish_spec_2		WEIGHT -	RESTRICTED TO	
		CUSTOMER DRAWING	SCALE 1:3	SHEET 1 OF 1
				REV 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Cable Assemblies](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[73-6352-10](#) [73-6353-3](#) [R285001001](#) [R288940004](#) [145111-05-12.00](#) [1661-C-24](#) [1801171170914KE](#) [24P104C24J1-012](#) [24P104C24P1-006](#)
[24P104C24P1-018](#) [24P204C24J1-003](#) [172-2150-EX](#) [1800920920914PJ](#) [FCB-3030-ALT](#) [21117-046](#) [21117-050](#) [PCX-24-50](#) [24P103C24P2-](#)
[003](#) [25P203C25P2-003](#) [R284008001](#) [R285001021](#) [R285426000](#) [R288940003](#) [4814-BB-24](#) [5260-72](#) [JT2N1-CL1-1F](#) [DLP-COAX1](#) [4814-K-](#)
[48](#) [115101-09-06.00](#) [CCNTN2-MM-LL335-26](#) [73-6351-25](#) [73-6352-3](#) [73-6353-25](#) [1800920920610PJ](#) [GD0BQ0BQ024.0](#) [1-3636-600-5210](#)
[TL8A-11SMA-11SMA-01500-51](#) [R284C0351060](#) [R288940009](#) [R284C0351028](#) [R288940002](#) [9702-1SL-1](#) [PT82NSMA](#) [73-6353-10](#)
[R285020301W](#) [PCX-18-50](#) [Minibend-9](#) [Minibend-4](#) [BNC TO SMA Cable](#) [MIKROE-274](#)