



RECOMMENDED PC BOARD MOUNTING DIMENSIONS FOR .063 [1.60] THICK PC BOARD AND .012 [0.305] STENCIL THICK

- TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- RETENTION FEATURES ON SOLDER TAILS, LOCATED AT MANUFACTURERS OPTION
- 0.00254 - 0.00504 [0.000100 - .000200] MATTE TIN-LEAD, ALL OVER 0.00127 [0.000050] NICKEL
- HOUSING: LCP, COLOR: BLACK
POSTS: COPPER ALLOY.
- 0.00254 - 0.00504 [0.000100 - .000200] MATTE TIN, ALL OVER 0.00127 [0.000050] NICKEL
- OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

6	101.19 [3.984]	99.06 [3.900]	39	40	9-146294-0
6	98.65 [3.884]	96.52 [3.800]	38	39	8-146294-9
6	96.11 [3.784]	93.98 [3.700]	37	38	8-146294-8
6	93.57 [3.684]	91.44 [3.600]	36	37	8-146294-7
6	91.03 [3.584]	88.90 [3.500]	35	36	8-146294-6
6	88.49 [3.484]	86.36 [3.400]	34	35	8-146294-5
6	85.95 [3.384]	83.82 [3.300]	33	34	8-146294-4
6	83.41 [3.284]	81.28 [3.200]	32	33	8-146294-3
6	80.87 [3.184]	78.74 [3.100]	31	32	8-146294-2
6	78.33 [3.084]	76.20 [3.000]	30	31	8-146294-1
6	75.79 [2.984]	73.66 [2.900]	29	30	8-146294-0
6	73.25 [2.884]	71.12 [2.800]	28	29	7-146294-9
6	70.71 [2.784]	68.58 [2.700]	27	28	7-146294-8
6	68.17 [2.684]	66.04 [2.600]	26	27	7-146294-7
6	65.63 [2.584]	63.5 [2.500]	25	26	7-146294-6
6	63.09 [2.484]	60.96 [2.400]	24	25	7-146294-5
6	60.55 [2.384]	58.42 [2.300]	23	24	7-146294-4
6	58.01 [2.284]	55.88 [2.200]	22	23	7-146294-3
6	55.47 [2.184]	53.34 [2.100]	21	22	7-146294-2
6	52.93 [2.084]	50.80 [2.000]	20	21	7-146294-1
6	50.39 [1.984]	48.26 [1.900]	19	20	7-146294-0
6	47.85 [1.884]	45.72 [1.800]	18	19	6-146294-9
6	45.31 [1.784]	43.18 [1.700]	17	18	6-146294-8
6	42.77 [1.684]	40.64 [1.600]	16	17	6-146294-7
6	40.23 [1.584]	38.10 [1.500]	15	16	6-146294-6
6	37.69 [1.484]	35.56 [1.400]	14	15	6-146294-5
6	35.15 [1.384]	33.02 [1.300]	13	14	6-146294-4
6	32.61 [1.284]	30.48 [1.200]	12	13	6-146294-3
6	30.07 [1.184]	27.94 [1.100]	11	12	6-146294-2
6	27.53 [1.084]	25.40 [1.000]	10	11	6-146294-1
6	24.99 [0.984]	22.86 [0.900]	9	10	6-146294-0
6	22.45 [0.884]	20.32 [0.800]	8	9	5-146294-9
6	19.91 [0.784]	17.78 [0.700]	7	8	5-146294-8
6	17.37 [0.684]	15.24 [0.600]	6	7	5-146294-7
6	14.83 [0.584]	12.70 [0.500]	5	6	5-146294-6
6	12.29 [0.484]	10.16 [0.400]	4	5	5-146294-5
6	9.75 [0.384]	7.62 [0.300]	3	4	5-146294-4
6	7.21 [0.284]	5.08 [0.200]	2	3	5-146294-3
6					
PLATING	C	B	A	NO. OF POSITIONS	PART NUMBER

4	101.19 [3.984]	99.06 [3.900]	39	40	4-146294-0
4	98.65 [3.884]	96.52 [3.800]	38	39	3-146294-9
4	96.11 [3.784]	93.98 [3.700]	37	38	3-146294-8
4	93.57 [3.684]	91.44 [3.600]	36	37	3-146294-7
4	91.03 [3.584]	88.90 [3.500]	35	36	3-146294-6
4	88.49 [3.484]	86.36 [3.400]	34	35	3-146294-5
4	85.95 [3.384]	83.82 [3.300]	33	34	3-146294-4
4	83.41 [3.284]	81.28 [3.200]	32	33	3-146294-3
4	80.87 [3.184]	78.74 [3.100]	31	32	3-146294-2
4	78.33 [3.084]	76.20 [3.000]	30	31	3-146294-1
4	75.79 [2.984]	73.66 [2.900]	29	30	3-146294-0
4	73.25 [2.884]	71.12 [2.800]	28	29	2-146294-9
4	70.71 [2.784]	68.58 [2.700]	27	28	2-146294-8
4	68.17 [2.684]	66.04 [2.600]	26	27	2-146294-7
4	65.63 [2.584]	63.5 [2.500]	25	26	2-146294-6
4	63.09 [2.484]	60.96 [2.400]	24	25	2-146294-5
4	60.55 [2.384]	58.42 [2.300]	23	24	2-146294-4
4	58.01 [2.284]	55.88 [2.200]	22	23	2-146294-3
4	55.47 [2.184]	53.34 [2.100]	21	22	2-146294-2
4	52.93 [2.084]	50.80 [2.000]	20	21	2-146294-1
4	50.39 [1.984]	48.26 [1.900]	19	20	2-146294-0
4	47.85 [1.884]	45.72 [1.800]	18	19	1-146294-9
4	45.31 [1.784]	43.18 [1.700]	17	18	1-146294-8
4	42.77 [1.684]	40.64 [1.600]	16	17	1-146294-7
4	40.23 [1.584]	38.10 [1.500]	15	16	1-146294-6
4	37.69 [1.484]	35.56 [1.400]	14	15	1-146294-5
4	35.15 [1.384]	33.02 [1.300]	13	14	1-146294-4
4	32.61 [1.284]	30.48 [1.200]	12	13	1-146294-3
4	30.07 [1.184]	27.94 [1.100]	11	12	1-146294-2
4	27.53 [1.084]	25.40 [1.000]	10	11	1-146294-1
4	24.99 [0.984]	22.86 [0.900]	9	10	1-146294-0
4	22.45 [0.884]	20.32 [0.800]	8	9	146294-9
4	19.91 [0.784]	17.78 [0.700]	7	8	146294-8
4	17.37 [0.684]	15.24 [0.600]	6	7	146294-7
4	14.83 [0.584]	12.70 [0.500]	5	6	146294-6
4	12.29 [0.484]	10.16 [0.400]	4	5	146294-5
4	9.75 [0.384]	7.62 [0.300]	3	4	146294-4
4	7.21 [0.284]	5.08 [0.200]	2	3	146294-3
PLATING	C	B	A	NO. OF POSITIONS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DRW: T. HOFFMAN	06DEC95	TE Connectivity	
CHK: G. DUBNICZKI	01FEB96	NAME: HEADER ASSEMBLY, MOD II, BREAKAWAY, SINGLE ROW, HIGH TEMPERATURE, VERTICAL WITH RETENTION FEATURE, W/.025 SQ. POSTS, .100 C/L	
APVO: G. DUBNICZKI	01FEB96	SIZE: A1	CAGE CODE: 00779
PRODUCT SPEC: ---	APPLICATION SPEC: ---	WEIGHT: ---	RESTRICTED TO: ---
MATERIAL: ---	FINISH: SEE TABLE	CUSTOMER DRAWING	SCALE: 4:1 SHEET: 1 OF 1 REV: K

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009508121](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#) [67095-007LF](#) [68002-116](#) [68016-236H](#) [68648-049](#)