

**CHARACTERISTICS OF SILICONE FUSION TAPE**

The following values are typical performance data and are not intended to be used as design data.

PROPERTY	TEST METHOD	PERFORMANCE
Operating Temperature Range:		
Continuous		-60°C to 200°C
Intermittent		-65°C to 260°C
Specific Gravity	ASTM D792	1.2
Hardness, Durometer, Shore A	ASTM D2148	
Room-cured - 24 Hours		50
Cured at 300°F - 24 Hours		70
Cured at 480°F - 24 Hours		75
Tensile Strength, psi, minimum	ASTM D119	700
Elongation, %, minimum	ASTM D119	300
Tear Strength, ppi, minimum	ASTM D624, Die B	
Bond Strength, pounds, minimum	MIL CID-A-A-59163	2 (1" width)
Adhesion, inches unwind, maximum	ASTM D2148	3
Cold Brittle Point, °C, maximum	ASTM D746	-65
Water Absorption, % max., by weight	MIL CID-A-A-59163	3
Dielectric Strength, volts/mil, minimum	MIL CID-A-A-59163	
Thickness 0.020 Inch		400
Thickness 0.030 Inch		400
Thickness 0.040 Inch		300
Thickness 0.050 Inch		275
Thickness 0.060 Inch		250
Thickness 0.080 Inch		200
Dielectric Constant, 1 KHz	ASTM D150	2.95
Dissipation Factor, 1 KHz	ASTM D150	<0.0004
Volume Resistivity, ohms/cm, minimum	MIL CID-A-A-59163	3x10 <sup>14</sup>

We hope this is of some benefit. If you have additional questions or comments, please contact the Tyco Electronics Product Information Center at 800-522-6752.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Adhesive Tapes](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[PF24.0W](#) [4718](#) [4516-1/4x36](#) [56-YELLOW-34"X72YD](#) [00-021200-13972-7](#) [021200-64630](#) [60 TAPE \(1"\)](#) [62-GRAY-12"X36YD](#) [62-GRAY-1"X36YD](#) [69-1"X36YD](#) [764-1"x36yd-Red](#) [764-1"x36yd-White](#) [PG ASSY](#) [926-1/4X18YD](#) [967454-1](#) [1194-14"X36YD](#) [1181 19MM X 16,5 METERS](#) [1182-7.7X10](#) [1245-34"X18YD](#) [1267](#) [130C-1X15FT](#) [130-1x10FT](#) [1345-3/8x18yrd](#) [1380-2"X8"](#) [E39-RS1-CA](#) [1900-48mm](#) [22-1/2X36YD](#) [2229-P-2-1/2x3-3/4](#) [88-SUPER-34X44FT](#) [890103N001](#) [2670](#) [SJ3527N-Black-1.5"x50yd](#) [EVK-TA-TM047NBH01](#) [AD-UCUSB-DCAUD-SPL](#) [20-1"X60YDS](#) [2020-18mmx55m](#) [H150](#) [3900-Blue](#) [3939-24mmx55m](#) [396-1"x36yd](#) [4016-34"x36yd](#) [4462W-12"x72yd](#) [44-TAN-14"X90YD](#) [4504-34x18](#) [471-Trans-1"x36yd-Bulk](#) [5414 34X36](#) [C-22](#) [35-Gray-1/2](#) [371-Tan-48mmx50m](#) [4008-12"X36YD](#)