



- 1 MATERIAL:
PIN CONTACTS - PHOSPHOR BRONZE.
PLUG SHELL - STEEL.
PLUG HOUSING & TERMINATING COVERS - UL V-0 RATED THERMOPLASTIC, COLOR: BLACK.
- 2 FINISH:
PIN CONTACTS - EITHER 0.76µm [.000030] MIN GOLD PLATE OR GOLD FLASH OVER PALLADIUM NICKEL PLATE, 0.76µm [.000030] MIN TOTAL IN LOCALIZED PLATE AREA, 1.52µm [.000060] MIN TIN-LEAD IN TERMINATION AREA, ALL OVER 1.27µm [.000050] MIN NICKEL.
PLUG SHELL - 0.25µm [.000010] MIN TIN-NICKEL OVER 3.81µm [.000150] MIN NICKEL OVER 2.54µm [.000100] MIN COPPER.
- 3. RECOMMENDED WIRE: 28 AWG OR 30 AWG, SOLID OR 7 STRAND, PVC INSULATION WITH A 0.74-0.91 [.029-.036] INSULATION DIAMETER.
- 4 FINISH:
PIN CONTACTS - PLATED WITH EITHER 0.76µm [.000030] MIN GOLD PLATE OR GOLD FLASH OVER PALLADIUM NICKEL PLATE, 0.76µm [.000030] MIN TOTAL IN LOCALIZED PLATE AREA, 3.00µm [.000118] MIN TIN IN TERMINATION AREA, ALL OVER 1.27µm [.000050] MIN NICKEL.
PLUG SHELL - 0.25µm [.000010] MIN TIN-NICKEL OVER 3.81µm [.000150] MIN NICKEL OVER 2.54µm [.000100] MIN COPPER.

SUPERSEDED BY 5749111-8	4	9.47 [.373]	71.86 [2.829]	66.60 [2.622]	62.23 [2.450]	49	100	1-749111-4
SUPERSEDED BY 5749111-4	4	7.44 [.293]	40.11 [1.579]	34.85 [1.372]	30.48 [1.200]	24	50	1-749111-3
SUPERSEDED BY 5749111-3	4	7.44 [.293]	33.76 [1.329]	28.50 [1.122]	24.13 [.950]	19	40	1-749111-2
OBSOLETE	2	7.44 [.293]	31.22 [1.229]	25.96 [1.022]	21.59 [.850]	17	36	1-749111-1
SUPERSEDED BY 1-5749111-0	2	7.44 [.293]	24.87 [.979]	19.61 [.772]	15.24 [.600]	12	26	1-749111-0
SUPERSEDED BY 5749111-9	2	9.47 [.373]	84.56 [3.329]	79.30 [3.122]	74.93 [2.950]	59	120	749111-9
	2	9.47 [.373]	71.86 [2.829]	66.60 [2.622]	62.23 [2.450]	49	100	749111-8
SUPERSEDED BY 5749111-7	2	9.47 [.373]	59.16 [2.329]	53.90 [2.122]	49.53 [1.950]	39	80	749111-7
	2	7.44 [.293]	51.54 [2.029]	46.28 [1.822]	41.91 [1.650]	33	68	749111-6
OBSOLETE	2	7.44 [.293]	46.46 [1.829]	41.20 [1.622]	36.83 [1.450]	29	60	749111-5
SUPERSEDED BY 5749111-4	2	7.44 [.293]	40.11 [1.579]	34.85 [1.372]	30.48 [1.200]	24	50	749111-4
OBSOLETE	2	7.44 [.293]	33.76 [1.329]	28.50 [1.122]	24.13 [.950]	19	40	749111-3
OBSOLETE	2	7.44 [.293]	26.14 [1.029]	20.88 [.822]	16.51 [.650]	13	28	749111-2
	2	7.44 [.293]	21.06 [.829]	15.80 [.622]	11.43 [.450]	9	20	749111-1
FINISH		E	D	C	B	A	NO. OF POSN	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN: M.A. McCAFFREY 11-17-88		CHK: M.E. SHIRK 11-17-88	
DIMENSIONS: mm[INCHES]		TO DIMENSIONS UNLESS OTHERWISE SPECIFIED:	
0 PLC	±	PRODUCT SPEC	108-1228
2 PLC	±	APPLICATION SPEC	114-40029
3 PLC	± 0.38 [015]	WEIGHT	-
4 PLC	±	CUSTOMER DRAWING	
ANGLES	±	SCALE	5:1
MATERIAL	SEE TABLE	SHEET	1 OF 1
		REV	Z1

STE TE Connectivity

PLUG ASSEMBLY, AMPLIMITE .050 Series

SIZE: A1 CAGE CODE: 00779 DRAWING NO: 749111

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [I/O Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[571763P](#) [58098-0628](#) [D20419-211](#) [D38999/20FJ24PA L/C](#) [D38999/20FJ29SB L/C](#) [D38999/24FG11SN L/C](#) [72.250.1628.2](#) [72.250.2428.2](#)
[74720-0505](#) [76.350.0729.0](#) [76871-1403](#) [FCN-244F080-G/1](#) [FCN-260A9920](#) [FCN-268D024-G/2F#10X-R10](#) [PCS-E50FA](#) [PCS-XE26LKA](#)
[PCS-XE26MA+](#) [PCS-XES68MS+](#) [G38A71314B](#) [DX40-50P\(55\)](#) [1571250010](#) [157-22500-3](#) [MS3471L14-19P L/C](#) [1888020-8](#) [91-569786-](#)
[35H](#) [91-569786-35M](#) [91-644626-35P](#) [SM3100F14S-58S](#) [172501-4002](#) [172501-6002](#) [FCN-260C008-A/L0](#) [FCN-260C024-AL0](#) [FCN-](#)
[261Z008](#) [FCN-268D008-G/1K](#) [2000314-1](#) [200331-1](#) [2007498-2](#) [PCR-E28LMDAG1+](#) [PCR-E36FC+](#) [PCS-E28FS+](#) [PCS-XE26SLFD+](#) [PCS-](#)
[XE26SLFDT+](#) [G38A71214B](#) [HDRA-E68W1LFDTC-SL+](#) [HDR-E14MSG1+](#) [R88A-CNK81S](#) [CRT1-ATT02](#) [54182-0605](#) [U90B2054081210](#)
[UE86K842720321](#)