

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
J	-	P	LTR	DESCRIPTION	DATE	DWN	APVD
		D4		OBSOLETE -5	ECR-11-013812	08JUL11	TS KB

Technical drawing showing front, side, and cross-sectional views of the 28-position cap housing assembly. Dimensions include: 19.2REF, 16.2±0.5, 3REF, 5±0.3, 16.9±0.5, 14.7, 11.8, 5.2±0.3, 1.85±0.3, 4.5±0.3, 2.5±0.45(PITCH), 2.1±0.3, 23.2REF, 2.5±0.45×7=17.5±0.45, 6±0.45, 2.5±0.45×5=12.5±0.45, 2.5±0.45(PITCH), 51REF, 45, 42.6±0.5, 16.7, 6REF, 2-ø2.4, and 0.64.

プリント基板取付穴寸法
 (MOUNTING DIMENSIONS FOR P.C.BOARD)
 (公差: ±0.1)
 (TOLERANCE: ±0.1)

2-ø3.5, 5.2, 4.5, 2.5(PITCH), 2.5×7=17.5, 6, 2.5(PITCH), 2.5×5=12.5, 28-ø1, 2.6

注、公差は累積しない事
 (NON ACCUMULATE PITCH TOLERANCE)

△ TO BE MEASURED WITHIN 2mm FROM [-Z-]
 2. APPLICABLE P.C.BOARD THICKNESS; 1.6mm
 3. THE MATING COUNTERPART PART NUMBER; 174045,174046
 4. RECOMMENDED MOUNTING SCREW; 3mmDIA, 6mmLENGTH
 TAPPING SCREW SPECIFIED IN JIS B1115,B1122.
 (TIGHTENING TORQUE;0.8N-M MAX.)

△ [-Z-]面より2mmの範囲で測定
 2. 適用プリント基板厚; 1.6mm
 3. 嵌合相手ハウジング型番; 174045,174046
 4. 推奨取付ネジ; JIS B1115,B1122 タッピンネジ、ナベ2種
 呼び径3、長さ6mm (締付けトルク0.8N-M以下)

断面 A-A (SECT.A-A)
 Dimensions: 1.1, 9.5, 7±0.3, 3.2REF, 3.7±0.5

OBSOLETE	SELECTIVE-TIN	PRE-TIN	BLACK	2-174979-2
OBSOLETE		PRE-TIN	BLUE	174979-5
		PRE-TIN	GREEN	174979-4
		PRE-TIN	BLACK	174979-2
	SELECTIVE-TIN (MATTE)	SELECTIVE-TIN (BRIGHT)	BLACK	174979-1
	SOLDERING SIDE 半田付け部	CONTACT SIDE 接触部側	COLOR 色	PART NUMBER 製品型番
	CONTACT FINISH コンタクト仕上			

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: 単位: 桁 mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差	DWN M.SUGAWARA 05JUL2006	TE Connectivity	
	0 PLC ±	CHK T.SHINOHARA 05JUL2006	28POSITION CAP HOUSING ASSEMBLY 040 SERIES MULTI-LOCK I/O CONNECTOR VERTICAL TYPE	
	1 PLC ±	APVD K.BETSUI 05JUL2006	NAME 名称	
	2 PLC ±	PRODUCT SPEC 製品規格	SIZE	CAGE CODE
	3 PLC ±	APPLICATION SPEC 取付適用規格	A2	00779
	4 PLC ±	ANGLES ±	DRAWING NO 番号	C=174979
			WEIGHT	9g
			CUSTOMER DRAWING	SCALE 尺度 2:1
				SHEET 1 of 1
				REV D4

MATERIAL
HOUSING: PBT
CONTACT: BRASS

TOLERANCES UNLESS OTHERWISE SPECIFIED:
 一般公差
 10± : ±0.2
 30± > 10 : ±0.25
 100± > 30 : ±0.3
 ANGLE : ±3°

1471-9 (3/11)

174979

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Automotive Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[003-018-000](#) [60403001](#) [60993906-B](#) [M902-2131](#) [M902-2161](#) [72.330.1035.1](#) [73.353.4028.0](#) [F119300-B](#) [F166900](#) [F258300-B](#) [F358300-B](#)
[F407400](#) [F444110](#) [F487000](#) [F509500B-B](#) [827153-1](#) [8N1515-32-24P](#) [9-1326729-8](#) [925474-1](#) [928905-1](#) [964562-4](#) [968782-1](#) [GT17SA-8DS-](#)
[HU](#) [98891-1012](#) [98947-1016](#) [12004147](#) [12004475-L](#) [12010290](#) [12010309-B](#) [12015454](#) [12020219-B](#) [12020308](#) [12041318-B](#) [12052225-L](#)
[12052466](#) [12059125](#) [12064869](#) [12004327-B](#) [12010503-B](#) [12015308](#) [12015384](#) [12015909](#) [1-21030-1](#) [12041254](#) [12041318](#) [12047946-B](#)
[12047957](#) [12047957-L](#) [12059473](#) [12066261](#)