

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

MAR .1992.

© COPYRIGHT 1992 By -

ALL RIGHTS RESERVED.

LOC  
JDIST  
/

REVISIONS

変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
	G3	REVISED PER ECR-11-024209	30NOV11	H.U	N.Y

D

CIRCUIT NO.  
DATE CODE (HOT MARKING)  
D/C  
D-3500  
AMP

1 2 3 4 5 6 7 8 9 10

52.8

27.18

3.8<sup>+0.6</sup>/<sub>-0.4</sub> (0.82)  
5.08 ±0.4  
7.62 ±0.4  
9.6  
3.34 ±0.4

A B

45.72 ±0.05 (3.54)  
5.08 ±0.05  
1.1 ±0.1 穴 20箇所  
Ø1.1 ±0.1 20 PLC  
5.08 ±0.05  
7.62 ±0.05  
21.28  
6.5  
Ø3 ±0.1 2 PLC  
3 ±0.1 穴 2箇所  
ROUND Ø4 MIN 2 PLC  
ランド径最小4mm 2箇所  
ヘッドハウジング外形  
リセプタクルハウジング外形  
REFERENCE P.C. BOARD HOLE (NOT ACCUMULATE TOLERANCE)  
P.C. BOARD THICKNESS: 1.6 ±0.1  
基板厚: 1.6 ±0.1

C

45.72 ±0.3  
5.08 ±0.3  
18.17  
1.5  
6 ±0.4  
5.08 ±0.3  
5.08 ±0.4  
45.72 ±0.4  
リテンションレグ  
RETENTION LEG  
CONTACT TAIL

1 材料; 熱可塑性ポリエステル樹脂(ガラス入り)  
色; 黒  
2 製品規格; 108-5349  
3 製品認定報告書; 501-5013  
△4 接触部仕上; ニッケル下地0.38 μMIN.金めっき  
△5 接触部仕上; ニッケル下地0.76 μMIN.金めっき  
△6 接触部仕上; ニッケル下地2.0 μMIN.すずめっき  
△7 レグおよび脚部仕上; ニッケル下地半田めっき  
△8 6箇所マーキング、白  
△9 レグおよび脚部仕上; ニッケル下地すずめっき

1 MATERIAL; GLASS FIELD THERMO PLASTIC, POLYESTER.  
COLOR; BLACK  
2 PRODUCT SPEC; 108-5349  
3 QUALIFICATION TEST REPORT; 501-5013  
△4 FINISH (CONTACT AREA); 0.38u MIN. GOLD PLT. OVER NICKEL.  
△5 FINISH (CONTACT AREA); 0.76u MIN. GOLD PLT. OVER NICKEL.  
△6 FINISH (CONTACT); 2.0u MIN. TIN PLT. OVER NICKEL.  
△7 FINISH (RETENTION LEG AND CONTACT TAIL);  
TIN-LEAD PLT. OVER NICKEL.  
△8 6 PLACES MARKING, WHITE  
△9 FINISH (RETENTION LEG AND CONTACT TAIL); TIN PLT. OVER NICKEL.  
△10 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

B

A

KEY LESS

FINISH	型番	マーキング
△9 △4	3-175365-2	△8
△9 △6	175365-5	
△9 △5	175365-3	
△9 △4	175365-2	

3-175365-2 のみ  
ONLY 3-175365-2

GENERAL TOLERANCE  
一般公差

10 ≥ : ±0.2  
30 ≥ > 10: ±0.25  
100 ≥ > 30: ±0.3  
ANGLES: ±3°

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
単位: 耗  
mm

MATERIAL  
材料SEE NOTE  
注記参照TOLERANCES UNLESS  
OTHERWISE SPECIFIED:  
一般公差

0 PLC	±
1 PLC	±
2 PLC	±
3 PLC	±
4 PLC	±
ANGLES	±

FINISH  
仕上

DWN 18MAR1992

T.YONEBAYASHI

CHK 07APR1992

S.MANABE

APVD 07APR1992

S.MANABE

PRODUCT SPEC

製品規格

APPLICATION SPEC

取付適用規格

WEIGHT

CUSTOMER DRAWING

TE Connectivity

NAME  
名称DYNAMIC D-3500  
20 POS HDR ASSY

SIZE

CAGE CODE

DRAWING NO

番号

RESTRICTED TO

A3 00779 C-175365

SCALE  
尺度 2:1SHEET  
1 of 1REV  
G3

1470-19 (3/11)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009508121](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#) [67095-007LF](#) [68002-116](#) [68016-236H](#) [68648-049](#)