

DIMENSIONING AND TOLERANCING PER ASME Y14.5M (ISO STANDARDS). THIS DRAWING IS A CONTROLLED DOCUMENT.

TOOL NUMBER	WIRE SIZE mm <sup>2</sup> [AWG]	INSULATION DIAMETER mm [in.]	INSUL. ADJ.	FLIP LOCATOR	STRIP LENGTH mm [in.]	CRIMP HEIGHT mm [in.]	CONTACT PART NUMBERS <sup>1</sup>		CONTACT DESCRIPTION	APPLIC. SPECIF.		
							LOOSE PIECE	STRIP FORM				
91584-1 91584-3	0.50-1.25 [20-16]	2.10-3.00 [.083-.118]	NO	NO	3.5-4.0 [.138-.157]	1.25-1.37 [.049-.054]	170189-[ ]	170289-[ ]	170177-[ ]	170286-[ ]	MIC Contacts	114-5004 114-5018
	0.75-1.42 [18-16]	2.16-2.85 [.085-.112]					170222-[ ]	170221-[ ]	187 Series FASTON Receptacle	114-5068		
	2.00-2.30 [14]	2.60-3.40 [.102-.134]					170189-[ ]	170286-[ ]	MIC Contacts	114-5004 114-5018		
91586-1 91586-3	0.50-0.85 [20-18]	2.1-3.0 [.082-.118]	YES	NO	3.5-4.5 [.138-.177]	1.25-1.35 [.049-.053]	172778-[ ]	172777-[ ]	MIC MK II Tab Contacts	114-5072		
	0.50x2 [20x2]										2.60-3.43 [.102-.135]	
	1.25-2.27 [16-14]											
91587-1 91587-3	0.30-0.56 [22-20]	1.50-2.20 [.059-.087]	NO	NO	4.0-5.0 [.157-.197]	1.06-1.19 [.042-.047]	170458-[ ]	170307-[ ]	MIC Contacts	114-5004 114-5018		
	0.75-0.89 [18]	2.20-2.60 [.087-.102]					170459-[ ]	170308-[ ]	MIC MK II Tab Contacts	114-5072		
91589-1 91589-3	0.50-1.25 [20-18]	2.1-3.0 [.083-.118]	NO	NO	3.5-4.0 [.138-.157]	1.25-1.37 [.049-.054]	170189-[ ]	170177-[ ]	MIC Contacts	114-5004 114-5018		
	1.25-2.30 [16-14]	2.6-3.4 [.102-.134]					170222-[ ]	170221-[ ]			170289-[ ]	170286-[ ]
91592-1 91592-3	0.30-0.35 [22]	1.5-2.0 [.060-.079]	NO	NO	3.5-5.5 [.138-.216]	1.05-1.28 [.041-.050]	172776-[ ]	172775-[ ]	MIC MK II Receptacle Contacts	114-5071		
	0.50-0.89 [20-18]	2.0-2.6 [.079-.102]									1.20-1.37 [.047-.054]	
1804014-1	0.50-0.85 [20-18]	2.10-3.00 [.083-.118]	YES	NO	3.5-5.5 [.138-.216]	1.25-1.45 [.049-.057]	172774-[ ]	172773-[ ]	MIC MK II Receptacle Contacts	114-5071		
	0.50x2 [20x2]											
	1.25-2.00 [16-14]	2.60-3.40 [.102-.134]										
	0.50+0.85 [20+18]											

<sup>1</sup> LIST OF APPLIED CONTACT PART NUMBERS MAY NOT BE COMPLETE AND IS SUBJECT TO CHANGE. FOR CURRENT INFORMATION ON TERMINAL PART NUMBERS, CONTACT THE TOOLING ASSISTANCE CENTER : 1-800-722-1111.

<sup>3</sup> -1 IS A COMPLETE CERTICRIMP II TOOL ASSEMBLY. -3 IS A CERTICRIMP II HEAD SUB ASSEMBLY.

4. THE HAND TOOL INSTRUCTION SHEET, ALSO KNOWN AS AN "IS", FOR MOST CERTI-CRIMP II TOOLS USE IS 408-8547. IF THE TOOL HAS A FLIP LOCATOR USE IS 408-10414.

2. AMP, CERTI-CRIMP, FASTON and MIC are trademarks.

## CERTI-CRIMP II DATA SHEET

DWG: M. YOUNGER 21FEB2012		MATERIAL: -		HEAT TREAT: -	
CHK: B.A. WOLFE 22FEB2012		APVD: B.A. WOLFE 22FEB2012		TE Connectivity	
NAME: B.A. WOLFE		DRAWING NO: 1583008			
DIMENSIONS: mm 		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± -		SCALE: - SIZE: A1 SHEET: 1 of 1 REV: A3	
ANGLE: - SURFACE TEXTURE:		REVISION RECORD: A3 REVISED - NEW FORMAT 2-2012 MY BAW		CERTI-CRIMP II TOOL DATA SHEET MULTI-INTERLOCK (MIC) CONNECTORS	

LOC: A  
 DIST: 00

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Crimpers / Crimping Tools](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[010-0096](#) [M225201-06](#) [M225202-37](#) [6-1579015-5](#) [CT150-2-D02](#) [622-6441LF](#) [M322](#) [6-304052-1](#) [63456-0054](#) [63484-3701](#) [63800-8355](#)  
[63819-1875](#) [63819-2875](#) [63819-4475](#) [63823-3475](#) [63827-5375](#) [64001-0975](#) [64001-4175](#) [64005-0175](#) [662903-2](#) [690602-6](#) [7-1579001-9](#) [7-](#)  
[23471-1](#) [762637-1](#) [808714-1](#) [811242-5](#) [999-50-020083](#) [1-21002-3](#) [1-21002-7](#) [12085270](#) [1-21002-6](#) [1-21113-6](#) [1-22548-4](#) [125442-1](#)  
[DCE.91.073.BVC](#) [DCE.91.090.3MVM](#) [DCE.91.130.5MVU](#) [DCE.91.202.BVCM](#) [1338300-1](#) [1-354003-0](#) [1338301-1](#) [DF62/RE-MD](#) [142321](#)  
[1456088-1](#) [1490794-1](#) [1-45804-6](#) [1490357-2](#) [1490357-3](#) [AX100749](#) [1-59619-7](#)