

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

REVISIONS

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

P	LTR	DESCRIPTION	DATE	DWN	APVD
P		REVISED PER ECO-11-005150	21MAR2011	RK	HMR
P1		REDRAWN IN CREO	02NOV2015	SCK	JP

Technical drawing of a Junior Power Timer Receptacle. The drawing includes a front view (top), a side view (bottom), and two detail views (right). Dimensions are provided in millimeters with tolerances. Callouts 1 through 42 identify specific features and dimensions.

Key dimensions and callouts:

- Overall length: 21 ± 0.5 (1)
- Distance from left edge to center of spring: $4.1 - 0.2$ (8)
- Distance from left edge to center of spring: $2.8 - 0.3$ (9)
- Distance from left edge to center of spring: 5 (3)
- Distance from left edge to center of spring: 5.7 (4)
- Distance from left edge to center of spring: 7.3 (2)
- Distance from left edge to center of spring: 0.32 ± 0.05 (5)
- Distance from left edge to center of spring: 1.2 (7)
- Distance from left edge to center of spring: 0.6 (6)
- Distance from left edge to center of spring: 2.5 (20)
- Distance from left edge to center of spring: 2.8 (21)
- Distance from left edge to center of spring: 5.4 (40)
- Distance from left edge to center of spring: 4.6 (42)
- Distance from left edge to center of spring: $3.08 - 0.1$ (30)
- Distance from left edge to center of spring: 2 (31)
- Distance from left edge to center of spring: 4.8 (34)
- Distance from left edge to center of spring: 4.5 (33)
- Distance from left edge to center of spring: 0.7 (32)
- Distance from left edge to center of spring: 0.32 (22)
- Distance from left edge to center of spring: 0.32 (41)

Labels: STAINLESS STEEL SPRING, Y, 10:1, C-C, D-D.

Y
10:1

1

SELECTIVE GOLD PLATING $0.4 \mu\text{m}$ min. DORUGE SELECTIVE $0.4 \mu\text{m}$ min	CuSn4	185026-3
TIN PLATING 0.8 TO $3.3 \mu\text{m}$ ETAMAGE 0.8 A $3.3 \mu\text{m}$	CuSn4	185026-1
FINISH	MATERIAL	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

MATERIAL

SEE TABLE

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	\pm	
1 PLC	\pm	± 0.3
2 PLC	\pm	
3 PLC	\pm	
4 PLC	\pm	
ANGLES	\pm	$\pm 5^\circ$

FINISH

SEE TABLE

DWN 18JAN1999

J.LALANGE

CHK 20JAN1999

J.LALANGE

APVD 20JAN1999

J.J.REV11

PRODUCT SPEC

108-15118

APPLICATION SPEC

114-15076

WEIGHT

0.4 g

CUSTOMER DRAWING

18JAN1999

20JAN1999

20JAN1999

20JAN1999

20JAN1999

20JAN1999

20JAN1999

20JAN1999

20JAN1999

20JAN1999

20JAN1999

20JAN1999

20JAN1999

NAME
JUNIOR POWER TIMER RECEPTACLE

SIZE

A3

CAGE CODE

00779

DRAWING NO

C=185026

RESTRICTED TO

-

SCALE

5:1

SHEET

1 OF 1

REV

P1

TE Connectivity

1470-19 (3/13)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Automotive Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[003-018-000](#) [60403001](#) [60993906-B](#) [M902-2131](#) [M902-2161](#) [72.330.1035.1](#) [73.353.4028.0](#) [F119300-B](#) [F166900](#) [F258300-B](#) [F358300-B](#)
[F407400](#) [F444110](#) [F487000](#) [F509500B-B](#) [827153-1](#) [8N1515-32-24P](#) [9-1326729-8](#) [925474-1](#) [928905-1](#) [964562-4](#) [968782-1](#) [GT17SA-8DS-](#)
[HU](#) [98891-1012](#) [98947-1016](#) [12004147](#) [12004475-L](#) [12010290](#) [12010309-B](#) [12015454](#) [12020219-B](#) [12020308](#) [12041318-B](#) [12052225-L](#)
[12052466](#) [12059125](#) [12064869](#) [12004327-B](#) [12010503-B](#) [12015308](#) [12015384](#) [12015909](#) [1-21030-1](#) [12041254](#) [12041318](#) [12047946-B](#)
[12047957](#) [12047957-L](#) [12059473](#) [12066261](#)