



SUGGESTED PRINTED CIRCUIT BOARD LAYOUT (COMPONENT SIDE)

4805 (3/11)

REVISIONS

DESCRIPTION B ECO-15-007496 11MAY2015 LL SH

⚠ MATERIAL:

HOUSING - HIGH TEMPERATURE THERMOPLASTIC, COLOR: BLACK, UL94V-0

TERMINALS - 0.36[.014] THICK PHOS BRONZE PLATED WITH $3.81\mu_{m}$ [.000150] MINIMUM THICK MATTE TIN IN SOLDER AREA. 1.27 μ m[.000050] MINIMUM GOLD IN LOCALIZED PLATE AREA. ENTIRE TERMINAL PLATED WITH $1.27\,\mu\mathrm{m}$ [.000050] MINIMUM THICK NICKEL. SHIELD - 0.196[.0077] THICK COPPER ZINC ALLOY PREPLATED WITH 1.27 mm[.000050] MINIMUM SATIN NICKEL WITH 2.03 μ m[.000080] MINIMUM TIN POST DIPPED ON PCB GROUND TABS.

2. JACK CAVITY CONFORMS TO FCC RULES AND REGULATIIONS PART 68, SUBPART F.

SUGGESTED PANEL OPENING DIMENSIONS.

SUGGESTED CLEARANCE BETWEEN TOP OF CONNECTOR AND TOP PANEL OPENING.

MANUFACTURING DATE CODE: LOCATED APPROX. AS SHOWN. FIRST 2 DIGITS = LAST 2 DIGITS OF YEAR. NEXT 2 DIGITS = MANUFACTURING WORK WEEK, LAST DIGIT = DAY OF WEEK WITH SUNDAY = 1.

CONTACT AREA LUBRICATED WITH BELLCORE APPROVED LUBRICANT. TECHNICAL REFERENCE GR-1217-CORE ISSUE 1, NOVEMBER 1995.

3.56 [.140]	6	1932219-2	
2.54 [.100]	6	1932219-1	
DIMENSION A	PANEL GROUNDS	PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT.		D.ZHU	20NOV2008			
		CHK M.LI	20NOV2008			Connectivity
DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD S.YAO	20NOV2008	NAME	INVERTED MODULAR JACK	ACCEMBLY
	0 PLC ± - 11 PLC ± -	PRODUCT SPEC			1 X 1, SHIELDED, PANE	•
	2 PLC ± 0.25[.010] 3 PLC ± -	APPLICATION SPEC			_	
	4 PLC ± – ANGLES ± –	_		SIZE	CAGE CODE DRAWING NO	RESTRICT
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	-	A1	00779 C- 1932219	_
		CUSTOMER DRAWING SCALE 4:1 SHEET 1 OF 1 REV				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

8949-H88/06BLKA/SN 74441-0010/BKN MP1010RX-1000 MP44RX-1000 PHJ-4P4C-1-V-4 PHP-6P6C-5 GAX-3-66 GAX-8-62 GDCX-PA-66-50 GDCX-PN-64 GDCX-PN-66 GDCX-PN-66-50 GDLX-A-66 GDLX-N-66 GDLX-S-66 GDLX-S-88K GDTX-S-88-50 GDX-PA-1010 GLX-N-1010M-BLK GLX-S-88M-BLK GMX-N-1010 GMX-S-1010 GMX-S-66 GMX-SMT4-N-88 GPX-2-64 GSGX-N-2-88 GSX-N-4-88 GSX-NS2-88-3.05 GSX-NS2-88-3.05-50 GSX-NS-88-3.05-50 PT-108A-8C-UL PT-J951-8C PTS-J531-8CS-50UL 1-1775629-2 A-2014-0-4 GWLX-S-88-GR GWLX-S9-88-YG DC-1021-8-WH-6 1300530003 1324640-4 RJ11FTVC2G RJ11FTVC2N RJFTVX2SA1G 132764-001 1413235 MP88X-1000 MPS88RX-5000 E5288-S000K3-L E5908-15A242-L 155302-001