



CABLE ENTRY DIAMETER MINIMUM		REVISIONS			
		REV	DESCRIPTION	DATE	APPROVED
HOUSING	.143	A1	REVISED PER ECO-11-005294	13APR11	HMR

NOTES:

- DESIGNED FOR USE WITH .141 DIA (RG 402/U) SEMI-RIGID CABLE.
- PICTORAL VIEW IS AFTER CRIMPING.
- MIN. STRAIGHT CABLE LENGTH .389
- IT IS SUGGESTED TO BEND CABLE PRIOR TO CRIMPING.

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions MIL-STD-348	Temperature Rating <u>-65° to +105°C</u>
Frequency Range (GHz) DC to <u>18</u>	Recommended Mating	Vibration MIL-STD-202, Method 204, Condition D
Volt Rating (VRMS MAX) @ Sea Level <u>500</u>	Torque <u>7-10</u>	Shock MIL-STD-202, Method 213, Condition I
VSWR <u>1.035+0.005f(GHz)</u>	Center Contact Captivation	Thermal Shock MIL-STD-202, Method 102, Condition C
Insertion Loss (dB MAX) <u>.03x√f(GHz)</u>	Axial (Lbs) <u>6</u>	Moisture Resistance MIL-STD-202, Method 106
RF Leakage (dB MIN) (Interface Only, Fully Mated) <u>-(100-f(GHz))</u>	Cable Retention	Corrosion - MIL-STD-202, Method 101, Condition B
Corona, 70,000 Ft (VRMS MIN) <u>375</u>	Axial Force (Lbs) <u>60</u>	
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1500</u>	Torque (In/Oz) <u>55</u>	
Contact Resistance (Milliohms MAX)		
Center Contact <u>2.0</u>		
Outer Contact <u>2.0</u>		
Cable to Housing <u>0.5</u>		
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>1000</u>		
IR.(Megohms MIN) <u>5000</u>		

	DIM "A"	DIM "B"				
BEFORE CRIMPING	.502 REF (12.8mm)	.385 REF (9.8mm)				
AFTER CRIMPING	.400 MAX (10.2mm)	.272 REF (6.9mm)				
COUPLING NUT HOUSING BUSHING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303		PASSIVATE PER QQ-P-35			
GASKET	SILICONE RUBBER PER ZZ-R-765		N/A			
COMPONENT	MATERIAL		FINISH			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON	DRAWN BY <u>D.CAM</u> DATE <u>10/12/82</u>					
FRAC. DEC. ANGLES	CHECKED BY <u>RMF</u> DATE <u>10/22/82</u>					
± 1/64 ±.005 ± °	APPD BY <u>RMF</u> DATE <u>10/27/82</u>					
	USE ASS'Y PROCEDURE		TITLE <u>OSM STRAIGHT CABLE PLUG - COMPRESSION CRIMP ATTACHMENT</u>			
	NO. AP. <u>408-04690 (20-198)</u>		SIZE <u>B</u>	CODE IDENT NO. <u>26805</u>	1050740-1	REV <u>A1</u>
			SCALE <u>6:1</u>			SHEET 1 OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors / Coaxial Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[8915-1511-000](#) [89674-0827](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39030/3-01N](#) [6500-7071-046](#) [6769](#) [CX050L2AQ](#) [7002-1541-010](#) [7002-1542-011](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-015](#) [7210-1511-019](#) [73137-5015](#) [73216-2241](#) [73404-2300](#) [7405-1521-005](#) [7405-1521-802](#) [8527](#) [8547](#) [FS11V](#) [877931](#) [8808-1511-001](#) [9049-9513-000](#) [9074-9513-000](#) [9101-9573-002](#) [910A205F](#) [9130-9573-002](#) [PL11SC-026](#) [PL375-33](#) [PL40-5](#) [PL74C-221](#) [PL75MC-217](#) [PL803-7](#) [1200690078](#) [1-201144-1](#) [R107003010W](#) [R110A172100](#)