



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₂	SEE ECN 80-0084	VM 2/22/80	BZ 2/28/80
01 ₃	REDRAWN ON CAD, ECN 92-0010	<i>OKR</i> 07/09/92	<i>M.M.</i> 07/14/92
01 ₄	REVISED PER ECN 99-0094	DM 7/16/99	<i>S. Mady</i>

DESIGNED FOR USE WITH .141 DIA S.R. CABLE CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.144
CONTACT	.037

ELECTRICAL	MECHANICAL	ENVIRONMENTAL	HOUSING	DIELECTRIC	CENTER CONTACT	COMPONENT	MATERIAL	FINISH
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions MIL-STD-348A, Fig. 310.2	Temperature Rating <u>-65°C to +125°C</u>	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PTFE FLUOROCARBON PER ASTM-D-1457	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± °	GOLD PLATE PER MIL-G-45204	N/A
Frequency Range (GHz) DC to <u>18</u>	Recommended Mating Torque <u>N/A</u>	Vibration MIL-STD-202, Method 204, Condition D				DRAWN BY <u>BWC</u> DATE <u>6/5/67</u>		
Volt Rating (VRMS MAX) @ Sea Level <u>500</u>	Mating Characteristics: Insertion (MAX Lbs) <u>3</u>	Shock MIL-STD-202, Method 213, Condition I				CHECKED BY <u>ED</u> DATE <u>8/19/67</u>		
VSWR <u>1.05 + .005 f(GHz)</u>	Withdrawal (MIN Oz) <u>1</u>	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp 115°C				APPD BY <u>D.NANIA</u> DATE <u>8/31/67</u>		
Insertion Loss (dB MAX) <u>.03 √f(GHz)</u>	Force to Engage and Disengage (In-Lbs MAX) <u>2</u>	Moisture Resistance MIL-STD-202, Method 106				AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599		
RF Leakage (dB MIN) <u>-[90-{f(GHz)}]</u>	Center Contact Captivation Axial (Lbs) <u>N/A</u>	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray				TITLE OSM 4-HOLE FLANGE MOUNT CABLE JACK DIRECT SOLDER ATTACHMENT		
Corona, 70,000 Ft (VRMS MIN) <u>375</u>	Radial (In-Oz) <u>N/A</u>					USE ASS'Y PROCEDURE 408-04767 (20-009) NO. AP. _____	SIZE <u>B</u> CODE IDENT NO. <u>26805</u>	2006-7941-00
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1,500</u>	Cable Retention Axial Force (Lbs) <u>60 Min</u>						SCALE <u>4:1</u>	REV <u>01₄</u>
Contact Resistance (Milliohms MAX) Center Contact <u>2.0</u>	Torque (In-Oz) <u>55 Min</u>							SHEET 1 OF 1
Outer Contact <u>2.0</u>	Weight (Grams) <u>TBD</u>							
Cable to Housing <u>0.5</u>								
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>1,000</u>								
LR.(Megohms MIN) <u>5,000</u>								

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors / Coaxial Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[8915-1511-000](#) [89674-0827](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39030/3-01N](#) [6500-7071-046](#) [6769](#) [CX050L2AQ](#) [7002-1541-010](#) [7002-1542-011](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7105-1521-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-015](#) [7210-1511-019](#) [73137-5015](#) [73216-2241](#) [73404-2300](#) [7405-1521-005](#) [7405-1521-802](#) [8527](#) [8547](#) [FS11V](#) [877931](#) [9049-9513-000](#) [9074-9513-000](#) [9101-9573-002](#) [910A205F](#) [9130-9573-002](#) [PL11SC-026](#) [PL375-33](#) [PL40-5](#) [PL74C-221](#) [PL75MC-217](#) [PL803-7](#) [1200690078](#) [1-201144-1](#) [R107003010W](#) [R110A172100](#)