

Molded Parts Specification Control Drawing

NOTES

- 1. All dimensions are in $\frac{\text{inches}}{[\text{millimeters}]}$
- 2. Dimensions appearing in table are as follows:
 - a As Supplied
 - b After Unrestricted Recovery
- Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by .06 max.





202D2XX-X-48

Boot, Straight With Lip

Part Number :

Description :

TABLE OF DIMENSIONS											
PART NUMBER	н		J			P	R	s	Т	нw	JW
	Min	Max	Min	Min -5,-6,-8 -12,-100	Max	±10%	Ref	Ref	Ref	±20%	±20%
	a	ь	-3,-4,-25 -130 C	-12,-100 0	b	b	b	b	b	ь	b
202D211-X-48	.88	.45	.88	.55	.25	3.00	<u>.46</u>	. <u>12</u>	.04	.06	. <u>045</u>
	[22,4]	[11,4]	[22,4]	[14,0]	[6,4]	[76,2]	[11,7]	[3,0]	[1,0]	[1,52]	[1,14]
202D221-X-48	1.01	.59	1.01	.63	<u>.29</u>	3.00	.48	. <u>12</u>	.04	.06	. <u>045</u>
	[25,7]	[15,0]	[25,7]	[16,0]	[7,4]	[76,2]	[12,2]	[3,0]	[1,0]	[1,52]	[1,14]
202D232-X-48	1.16	.74	1.16	.72	. <u>33</u>	3.00	.48	. <u>12</u>	.04	.07	. <u>045</u>
	[29,5]	[18.8]	[29,5]	[18,3]	[8,4]	[76,2]	[12,2]	[3,0]	[1,0]	[1,78]	[1,14]
202D242-X-48	1.34	.90	1.34	.84	<u>.38</u>	3.00	.48	. <u>12</u>	.04	<u>.07</u>	. <u>045</u>
	[34,0]	[22,9]	[34,0]	[21,3]	[9,7]	[76,2]	[12,2]	[3,0]	[1,0]	[1,78]	[1,14]
202D253-X-48	1.47	1.16	1.47	<u>.91</u>	<u>.41</u>	3.00	<u>.55</u>	<u>.12</u>	. <u>065</u>	<u>.08</u>	. <u>045</u>
	[37,3]	[29,5]	[37,3]	[23,1]	[10,4]	[76,2]	[14,0]	[3,0]	[1,65]	[2,0]	[1,14]

tyco/Electronics

TYCO ELECTRONICS 307 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025 Revision: B
Date: 6/21/02

Part Number :

202D2XX-X-48

Description : Boot, Straight With Lip


Molded Parts Specification Control Drawing

Part Number : 202D2XX-X-48

Description : Boot, Straight With Lip

COMPATABILITY	CHART					
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION	
-3	Polyolefin, Semi-rigid	RT-301	/42; /86	S-1017; S-1048	Adhesive	
-4	Polyolefin, Flexible	RT-1304	/42; /86	S-1017;S-1048	Adhesive	
-5	Neoprene	RT-501	/42	S-1017		
-6	Silicone	RT-602	N/A			
-8	Polyolefin, Space	RT-1308	N/A			
-12	*VITON, Flexible	RT-1312	N/A			
-25	Elastomer, Fluid Resistant	RT-1325	/42,/86	S-1017; S-1048	Adhesive	
-130	Polyolefin, Flexible	RW-2008	/42; /86	S-1017; S-1048	Adhesive	
-100	Polyolefin, Semi-flexible ZEROHAL ^M	RT-1323	/86	S-1048	Adhesive	

*VITON is a Registered Trademark of Dupont



THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

tyco/Electronics

TO ELECTRONICS 307 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025

Revision: B
Date: 6/21/02

Part Number: 202D2XX-X-48

Description : Boot, Straight With Lip

CAD FILE MP02076

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Cable Boots category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

618235-000 622A014-3-0 CX4132-000 879103-4 879515-000 889092 982033-2 R280576000 1300830729 MTPSRBCL-C 1811481-1 200W531-3-0 202A121-386-0 202A142-4-00/42-0 202A163-4-0-CS5067 202B221-13-0 202B231-13-0 202B563-25-07-0 202C621710CS5361 202D132-4-07/42-0 202D221-4-0-CS5349 202D221-4-26-0 202D263-25-08-0 202D263-4-22/42-0 202D263-4-88-0 202D921-2542-0 202E336-71-0 202F211-50-22-0-CS8474 202F242-50-05-0 202F242-51-04/164-0 202K121-25-CS-1858-0 202K121-25-CS-2062-0 202K132-25-01/225-0CS8387 202K153-3-0186-0 202S132-25-UP-0 203W301-3/42-0 207W613-100/184-0-CS5657 207W623-100-01/184-0 207W634-100/184-0-CS5657 207W656-100-01/184-0 207W667-100-01/184-0 207W667-100/184-0 208A011-3-0 208A021-3-0 221A011-51164-0-CS7133 222A121-2586 222A152-342-0 222A213-25-0-CS5613 222D221-25-13/86-0 222D232-4-61-0-CS5078