


Raychem

TE Internal #: 096673-000 Heat Shrink Boots, 180°, Molded Part Shape Code 202, Lipped, 4, 10, Adhesive Pre-Coat, Operating Temperature Range -55 – 135 °C [-67 – 275 °F]

View on TE.com >



Wire Protection & Management > Heat Shrink Molded Shapes > Heat Shrink Boots > Low Profile Heat Shrink Boots: Poly Molded, Lipped, Straight



Molded Part Angle: 180 ° Molded Part Shape Code: 202 Lipped: Yes Material Code: 4 Heat Shrink Boot Material Systems Code: 10 All Low Profile Heat Shrink Boots: Poly Molded, Lipped, Straight (223)

Features

Product Type Features

Molded Part Angle

180°

Configuration Features

Lipped	Yes	
Body Features		
Material Code	4	
Heat Shrink Boot Material Systems Code	10	
Adhesive Pre-Coat	Yes	
Material	Polyolefin Flexible Modified	
Dimensions		
Wire/Cable Outside Diameter	.3 in, .31 in, .35 in, .39 in, .43 in, .433 in, .47 in, .55 in, 10 mm, 11 mm, 12 mm, 14 mm, 8 mm, 9 mm	
Cable Diameter Range	7.4 – 16 mm[7.4 – 17 in]	
Usage Conditions		
Operating Temperature Range	-55 – 135 °C[-67 – 275 °F]	
Operation/Application		
Power Cable Accessory	No	

C For support call+1 800 522 6752

202D221-4/86-0

Heat Shrink Boots, 180 °, Molded Part Shape Code 202, Lipped, 4, 10, Adhesive Pre-Coat, Operating Temperature Range -55 – 135 °C [-67 – 275 °F]



Industry Standards

Approved Standards	SAE AS I 81765/1, Type II, UL 224, File E85381	
Government Qualified	No	
Other		
Molded Part Shape Code	202	
Fluid & Chemical Resistance	Occasional Fluid Exposure	
Adhesive Options	/86 Precoat	
Adhesive Type	High Performance Pre-Coat Adhesive	
Product Compliance For compliance documentation, visit the product page on TE.com>		
•	Compliant	
For compliance documentation, visit the product page on TE.com>	Compliant Compliant	
For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU		

Does not contain REACH SVHC

Halogen Content

Not Low Halogen - contains Br or Cl > 900 ppm.

Not applicable for solder process capability

Solder Process Capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

202D221-4/86-0

Heat Shrink Boots, 180°, Molded Part Shape Code 202, Lipped, 4, 10, Adhesive Pre-Coat, Operating Temperature Range -55 – 135 °C [-67 – 275 °F]





Customers Also Bought



TE Part #YDTS26F09-98SNV001

TE Part #109858-000

TE Part #4-1617540-9 J1MAC-12XL=M39016/7-028L

PLU	G A	122	ŕ
-----	-----	-----	---

Documents

Product Drawings 202D221-4/86-0

English

Datasheets & Catalog Pages 1654025_Sec4_-4

English

Raychem Molded Parts Visual Guide

English

Product Specifications Product Specification

English

Product Environmental Compliance Safety Datasheet

Safety Datasheet

English

C For support call+1 800 522 6752

202D221-4/86-0

Heat Shrink Boots, 180 °, Molded Part Shape Code 202, Lipped, 4, 10, Adhesive Pre-Coat, Operating Temperature Range -55 – 135 °C [-67 – 275 °F]



Safety Datasheet

French

Safety Datasheet

German

Safety Datasheet

Safety Datasheet

Safety Datasheet

Safety Datasheet

Safety Datasheet

Safety Datasheet

English

Safety Datasheet

French

Safety Datasheet

German

Safety Datasheet

Safety Datasheet

Safety Datasheet

Safety Datasheet

Safety Datasheet

English

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heat Shrink Cable Boots & End Caps category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below :

577159N001 645494-000 CX4132-000 687025-000 705331-000 718446-000 725666N001 729257-000 F27131-000 F85868-000 770-003S106W2 770-013210W1 770-013311 770-013312 806542N001 807507-000 808059-000 808362-000 808618-000 809125-000 809130-000 809218-000 812014-000 812047-000 813166-000 813767N002 814741-000 819117N001 823026-000 823070-000 825002-000 841189N001 861471-000 866647-000 879515-000 937577-000 957073-000 982033-2 A77813-000 R280576000 D96192-000 163549-000 MTPSRBCL-C 1954015-1 200W531-3-0 202A163-4-0-CS5067 202A343-3-00-0 202B221-13-0 202B231-13-0 202B563-25-07-0