

Raychem

TE Internal #: 808489-000


Heat Shrink Boots, 180°, Molded Part Shape Code 202, Lipped, 3,

10, Operating Temperature Range -55 – 135 °C [-67 – 275 °F]

View on TE.com >



Wire Protection & Management > Heat Shrink Molded Shapes > Heat Shrink Boots > Low Profile Heat Shrink Boots: Poly Molded, Lipped, Straight



Molded Part Angle: 180°

Molded Part Shape Code: 202

Lipped: Yes

Material Code: 3

Heat Shrink Boot Material Systems Code: 10

All Low Profile Heat Shrink Boots: Poly Molded, Lipped, Straight (223)

Features

Product Type Features	
Molded Part Angle	180°
Configuration Features	
Lipped	Yes
Body Features	
Material Code	3
Heat Shrink Boot Material Systems Code	10
Adhesive Pre-Coat	No
Material	Semi-Rigid Modified Polyolefin
Dimensions	
Wire/Cable Outside Diameter	.43 in, .47 in, .55 in, .63 in, .71 in, 11 mm, 12 mm, 14 mm, 16 mm, 18 mm
Connector or Backshell Outside Diameter	1.02 in, 1.1 in, 1.18 in, 1.26 in, 26 mm, 28 mm, 30 mm, 32 mm
Usage Conditions	
Usage Conditions Operating Temperature Range	-55 – 135 °C[-67 – 275 °F]

BS-G-198-5-DA, DEF Std 59-97 Issue 3

Type DA, SAE AS 85049/140, SAE AS I

Approved Standards



	81765/1, Type I, UL 224, File E85381
Other	
Molded Part Shape Code	202
Fluid & Chemical Resistance	Occasional exposure to fluids
Adhesive Options	/42 Precoat

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts







Customers Also Bought

















Documents

Product Drawings 202D242-3-0

English

Datasheets & Catalog Pages

1654025_Sec4_-3

English

Raychem Molded Parts Visual Guide

English

Product Specifications

Product Specification

English

Product Environmental Compliance

Safety Datasheet

Safety Datasheet

Heat Shrink Boots, 180°, Molded Part Shape Code 202, Lipped, 3, 10, Operating Temperature Range -55 – 135°C [-67 – 275°F]



Safety Datasheet

English

Safety Datasheet

French

Safety Datasheet

German

Safety Datasheet

Safety Datasheet

Safety Datasheet

Safety Datasheet

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heat Shrink Cable Boots & End Caps category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

577159N001 645494-000 CX4132-000 687025-000 705331-000 718446-000 725666N001 729257-000 F27131-000 F85868-000 770003S106W2 806542N001 807507-000 808059-000 808362-000 808618-000 809125-000 809130-000 809218-000 812014-000 812047-000
813166-000 813767N002 814741-000 819117N001 823026-000 823070-000 825002-000 841189N001 861471-000 866647-000 879515000 937577-000 957073-000 982033-2 A77813-000 R280576000 D96192-000 163549-000 MTPSRBCL-C 1954015-1 200W531-3-0
202A163-4-0-CS5067 202A343-3-00-0 202B221-13-0 202B231-13-0 202B563-25-07-0 202C241-13-0 202D121-4-01/86-0 202D132-407/42-0