

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

CABLE ENTRY DIAMETER MINIMUM	
CONTACT	.021
HOUSING	.066
FERRULE	.126

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AJ	00	C2	REVISED PER ECO-11-005033	01APR11	RK HMR

Technical drawing of an OSM straight cable solder attachment. The drawing shows a cross-section of the assembly with the following dimensions and labels:

- Overall length: 1.187 MAX (30.1mm)
- Distance from REF PLANE to center of contact: .690 REF (17.5mm)
- Distance from REF PLANE to center of ferrule: .575 REF (14.6mm)
- Center contact diameter: .312 HEX (7.9mm)
- Labels: OSM PLUG, HEAT SHRINK TUBING

1	BRASS
2	STAINLESS STEEL
3	BERYLLIUM COPPER
4	PTFE
5	SILICONE RUBBER
6	GOLD PLATE
7	NICKEL PLATE
8	PASSIVATE
9	POLYOLEFIN COMPOUND

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 310.1	TEMPERATURE RATING -65°C TO +165°C
Frequency Range (GHz) DC to 12.4	Recommended Mating Torque 7 TO 10 INCH/LBS	DURABILITY:500 CYCLES
Volt Rating (VRMS MAX) @ Sea Level 250	Mating Characteristics:	.XXX = in (XX.X) = mm
VSWR 1.15 + .02F(GHZ)	Insertion (MAX Lbs) N/A	
Insertion Loss (dB MAX) .06 √ F(GHZ)@6GHZ	Withdrawal (MIN Oz) N/A	
RF Leakage (dB MIN) -60@ 6 to 8 GHZ	Force to Engage and Disengage (In/Lbs MAX) 2.0	
Corona, 70,000 Ft (VRMS MIN) 190	Center Contact Captivation	
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 750	Axial (Lbs) N/A	
Contact Resistance (Milliohms MAX)	Radial (In/Oz) N/A	
Center Contact 5.0	Cable Retention	
Outer Contact 3.0	Axial Force (Lbs) 20	
Cable to Housing 0.5	Torque (In/Oz) N/A	
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 500	Weight (Grams) 2.7	
I.R.(Megohms MIN) 5000		

---	1 6	1 7	4	1 6	1 6	3	5	1051643-3
9	2 6	2 6	4	1 6	1 6	3	5	1051643-1
SHRINK TUBING	HOUSING	COUPLING NUT	DIELE-CTRIC	CENTER CONTACT	FERRULE	RETAINING RING	GASKET	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN DRF 10/12/76	<b>STE</b> TE Connectivity	
DIMENSIONS: INCHES		CHK KWW 2/17/77		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD BWC 2/18/77	NAME	
0 PLC ± -		PRODUCT SPEC	OSM STRAIGHT CABLE	
1 PLC ± -		APPLICATION SPEC	PLUG SOLDER ATTACHMENT	
2 PLC ± -		408-4756	SIZE A2	CAGE CODE 00779
3 PLC ± .005		WEIGHT -	DRAWING NO C=1051643	RESTRICTED TO -
4 PLC ± ± 1°		CUSTOMER DRAWING	SCALE 5:1	SHEET 1 of 1
MATERIAL -		FINISH -	REV C2	

1471-9 (3/11)

1051643

B

A

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [RF Connectors / Coaxial Connectors](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[8915-1511-000](#) [89674-0827](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39030/3-01N](#) [6500-7071-046](#) [6769](#) [CX050L2AQ](#) [7002-1541-010](#) [7002-1542-011](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7105-1521-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-015](#) [7210-1511-019](#) [73137-5015](#) [73216-2241](#) [73404-2300](#) [7405-1521-005](#) [7405-1521-802](#) [8527](#) [8547](#) [FS11V](#) [877931](#) [9049-9513-000](#) [9074-9513-000](#) [9101-9573-002](#) [910A205F](#) [9130-9573-002](#) [PL11SC-026](#) [PL375-33](#) [PL40-5](#) [PL74C-221](#) [PL75MC-217](#) [PL803-7](#) [1200690078](#) [1-201144-1](#) [R107003010W](#) [R110A172100](#)