

4

3

2

1

THIS DRAWING IS UNPUBLISHED.		
RELEASED FOR PUBLICATION		N/A, N/A
COPYRIGHT N/A BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.		
COMPONENT	MATERIAL	FINISH
HOUSING	STAINLESS STEEL PER ASTM-A-484 OR ASTM-A-582 TYPE 303	GOLD PLATED PER ASTM-B-488
DIELECTRIC	PTFE FLUORCARBON PER ASTM-D-1457	---
---	---	---
---	---	---
---	---	---
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-194 ALLOY C17200, CONDITION H	GOLD PLATED PER ASTM-B-488
---	---	---
---	---	---
---	---	---
---	---	---
---	---	---
---	---	---

ENVIRONMENTAL	
TEMPERATURE RATING:	-65°C TO +105°C
VIBRATION:	MIL-STD-202, METHOD 204, CONDITION D
SHOCK:	MIL-STD-202, METHOD 213, CONDITION 1
MOISTURE RESISTANCE:	MIL-STD-202, METHOD 106
CORROSION:	MIL-STD-202, METHOD 101, CONDITION B. 5% SALT SPRAY
THERMAL SHOCK:	MIL-STD-202, METHOD 107, CONDITION B EXCEPT HIGH TEMP 125°C

MECHANICAL	
INTERFACE DIMENSIONS:	MIL-STD-348A FIG. 310.2
RECOMMENDED MATING TORQUE:	7-10 IN-LBS
FORCE TO ENGAGE & DISENGAGE (IN-LBS MAX):	2.0
WEIGHT (GRAMS):	TBD
MATING CHARACTERISTICS:	INSERTION (MAX LBS) 2 WITHDRAWAL (MIN OZ): 1
CABLE RETENTION:	AXIAL FORCE (LBS) N/A TORQUE (IN-OZ): N/A
CENTER CONTACT CAPTIVATION:	AXIAL (LBS): 6.0 MIN RADIAL (IN-OZ): 4.0 MIN

ELECTRICAL	
NORMAL IMPEDANCE (OHMS):	50
FREQUENCY RANGE (GHz):	DC TO 18
VOLT RATING @ SEA LEVEL (VRMS MAX):	335
VSWR:	N/A
INSERTION LOSS: (dB MAX):	N/A
RF LEAKAGE (dB MIN):	N/A
CORONA 70,000 FT (VRMS MIN):	250
DIELECTRIC WITHSTANDING VOLTAGE (VRMS MIN) AT SEA LEVEL:	1000
I.R. (MEGOHMS MIN):	5,000
RF HIGH POTENTIAL AT SEA LEVEL (VRMS MIN @ 5 MHz):	670
CONTACT RESISTANCE (MILLIOHMS MAX):	CENTER CONTACT: 3.0 OUTER CONTACT: 2.0 CABLE TO HOUSING: N/A

Side view drawing of the SMA straight PCB jack. Dimensions include: overall length .375 [9.53], distance from housing to contact .125±.010, contact thickness .065 [1.65], and contact diameter $\phi .050 \pm .001$ [1.27±0.03]. Labels include HOUSING, CONTACT, and .250-36 UNS-2A.

Top view drawing of the SMA straight PCB jack. Dimensions include: square width .250 SQ [6.35] 2 PLC, contact spacing .200±.002 [5.08±0.05] TYP, and contact diameter $\phi .060$ [1.54] MAX 4 PLC. Labels include DIELECTRIC and .100±.008 [2.54±0.20] TYP.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
DF	X0	REV PER ECO 05-1266	4-20-05	CT	FB

1053374-1
PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	10/10/02	AMP Tyco Electronics Corporation	
DIMENSIONS:		CHK	11-20-02	Harrisburg, Pa 17105-3608	
INCHES [mm]		APVD	11-20-02	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		SMA STRAIGHT PCB JACK (M39012/93-3002)	
0 PLC ± -		APPLICATION SPEC		SIZE	CAGE CODE
1 PLC ± -				A2	00779
2 PLC ± -				DRAWING NO	RESTRICTED TO
3 PLC ± .005 [0.13]				C=1053374	-
4 PLC ± -				SCALE	SHEET
ANGLES ± -				10:1	1 OF 1
FINISH		WEIGHT	TBD	REV	A
SEE TABLE		SEE TABLE	SEE TABLE	CUSTOMER DRAWING	
		MA/COM # 2062-8002-90			

AMP 1471-9 REV 31MAR2000

MA/COM # 2062-8002-90

1053374

A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors / Coaxial Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[8915-1511-000](#) [89674-0827](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39030/3-01N](#) [6500-7071-046](#) [6769](#) [CX050L2AQ](#) [7002-1541-010](#) [7002-1542-011](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7105-1521-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-015](#) [7210-1511-019](#) [73137-5015](#) [73216-2241](#) [73404-2300](#) [7405-1521-005](#) [7405-1521-802](#) [8527](#) [8547](#) [FS11V](#) [877931](#) [9049-9513-000](#) [9074-9513-000](#) [9101-9573-002](#) [910A205F](#) [9130-9573-002](#) [PL11SC-026](#) [PL375-33](#) [PL40-5](#) [PL74C-221](#) [PL75MC-217](#) [PL803-7](#) [1200690078](#) [1-201144-1](#) [R107003010W](#) [R110A172100](#)