


- 1 THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- 2 POINT OF MEASUREMENT FOR PLATING THICKNESS.
- 3 ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
- 4 BREAKAWAY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
- 5 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



RECOMMENDED HOLE LAYOUT

	3.984	3.900	39	80	4-103149-0
	3.884	3.800	38	78	-3-103149-9
	3.784	3.700	37	76	-3-103149-8
	3.684	3.600	36	74	-3-103149-7
5 SUPERSEDED BY 8-146308-6	3.584	3.500	35	72	-3-103149-6
	3.484	3.400	34	70	-3-103149-5
	3.384	3.300	33	68	-3-103149-4
	3.284	3.200	32	66	-3-103149-3
	3.184	3.100	31	64	-3-103149-2
	3.084	3.000	30	62	-3-103149-1
	2.984	2.900	29	60	-3-103149-0
	2.884	2.800	28	58	-2-103149-9
	2.784	2.700	27	56	-2-103149-8
	2.684	2.600	26	54	-2-103149-7
	2.584	2.500	25	52	-2-103149-6
	2.484	2.400	24	50	-2-103149-5
	2.384	2.300	23	48	-2-103149-4
	2.284	2.200	22	46	-2-103149-3
	2.184	2.100	21	44	-2-103149-2
	2.084	2.000	20	42	-2-103149-1
	1.984	1.900	19	40	2-103149-0
	1.884	1.800	18	38	+1-103149-9
	1.784	1.700	17	36	+1-103149-8
	1.684	1.600	16	34	1-103149-7
6 OBSOLETE	1.584	1.500	15	32	+1-103149-6
	1.484	1.400	14	30	1-103149-5
5 OBSOLETE	1.384	1.300	13	28	+1-103149-4
	1.284	1.200	12	26	1-103149-3
	1.184	1.100	11	24	+1-103149-2
	1.084	1.000	10	22	+1-103149-1
	.984	.900	9	20	1-103149-0
5 OBSOLETE	.884	.800	8	18	+03149-9
	.784	.700	7	16	103149-8
	.684	.600	6	14	103149-7
	.584	.500	5	12	103149-6
	.484	.400	4	10	103149-5
5 OBSOLETE	.384	.300	3	8	+03149-4
	.284	.200	2	6	103149-3
5 SUPERSEDED BY 5-146308-2	.184	.100	1	4	+03149-2
5 OBSOLETE	.084	—	—	2	+03149-1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN	H. MOLL	23OCT87	 TE Connectivity
DIMENSIONS: INCHES		CHK	T. CLARK	23OCT87	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	T. CLARK	29OCT87	NAME
0 PLC ± -		PRODUCT SPEC			HEADER ASSY, MOD II, BREAKAWAY, DOUBLE ROW, .100X.100 C, RIGHT ANGLE, WITH .025 SQ POSTS
1 PLC ± -		APPLICATION SPEC			SIZE
2 PLC ± -		WEIGHT			A1
3 PLC ± .005		CUSTOMER DRAWING			SCALE 4:1
4 PLC ± -		RESTRICTED TO			SHEET 1 OF 1
ANGLES ± -		REV			G
MATERIAL: HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR:BLACK; POST: COPPER ALLOY	FINISH: POST: .00050 GOLD IN THE CONTACT AREA; .00100 TO .00200 WHITE IN ALL OVER; .00050 NICKEL	DRAWING NO			103149

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)  
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)  
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)