

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

MATED WITH
PASSEND ZU
HA 16

COPYRIGHT - By -

ALL RIGHTS RESERVED.

PROJEKT NR.:

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D6	ECR-17-009069	09FEB2018	SG	MKO

SCREW TERMINATION 4 M3x10.5

CRIMP TERMINATION 5 M3x10.5

SPRING CLAMP TERMINATION 6 M3x10.5

Contact arrangement / view from termination side

Contact arrangement / view from termination side

Contact arrangement / view from termination side

Contact arrangement / view from termination side

NOTES:

1 SUITABLE CRIMP CONTACTS: SERIES HE/HA
OUTER DIMENSIONS OF INSULATION: MAX. $\phi 3,2$ MM

⚠ SUITABLE HOOD SIZE 5; 7; 9; 11: SERIES HA; HD
SUITABLE INSERTION AND EXTRACTION TOOL:
SCREWDRIVER 0,5x3 DIN 5264

⚠ Strip lenght: Screw conection 10mm
Spring clamp conection 10mm Crimp conection 7.5mm

⚠ STANDARDS:
DIN EN 61984; DIN EN 60664-1

⚠ PACKAGING:
5 SETS IN A CARTON, PRE-MOUNTED

⚠ SPECIAL PACKAGING: Krauss-Maffei
PACKAGING UNIT: 300 PIECES

⚠ SPECIAL PACKAGING: Krauss-Maffei
PACKAGING UNIT: 150 PIECES

⚠ SPECIAL PACKAGING: AIS
PACKAGING UNIT: 250 PIECES

⚠ SPECIAL PACKAGING: WIELAND
PACKAGING UNIT: 100 PIECES

⊠ SEE TE CONNECTIVITY QUALITYMANAGEMENT PROCEDURE NO. 1.12

Panel cut-out for contact insert

when used without housing

Assembling instruction

⚠ DISTANCE FOR SAFETY
CONTACT MARKING MAX. 24 mm

1-3	1-2	1-0	0-4	0-7	0-6	0-5	2-9	1-9	7-9	7-8	1-8	2-8	1-7	7-2	7-1	2-3	1-1	DESCRIPTION / BENENNUNG	MATERIAL	COLOR / FARBE	ITEM NO. POS.	REMARKS / BEMERKUNGEN	
																		Pin insert screw	PBT	light beige	8	with stainless steel-fixing screw	
																		Pin insert screw	PBT	light beige	7	with stainless steel-fixing screw	
																		Pin insert screw	PBT	light beige	6	with AU contact	
																		Cover	PBT	light beige	5		
																		Cover	PBT	light beige	4		
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	Cover	PBT	light beige	3		
																		pin insert spring clamp	PBT	light beige	2		
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	pin insert crimp/screw	PBT	light beige	1		
HA-16-Sti.S-B1-16-WIE	HA-16-Sti.S-B1-16-AIS	HA-16-Sti.S-B17-32-KM	HA-16-Sti.S-B1-16-KM	HA-16-Sti.S-VA-B1-16	HA-16-Sti.S-VA-B17-32	HA-16-Sti.S-AU-B1-16	HA-16-Sti.S-C-B-49-64	HA-16-Sti.S-B-49-64	HA-16-Sti.S-C-B-49-64	HA-16-Sti.S-C-B-33-48	HA-16-Sti.S-B-33-48	HA-16-Sti.S-C-B-33-48	HA-16-Sti.S-B-17-32	HA-16-Sti.S-C-B-17-32	HA-16-Sti.S-C-B-17-32	HA-16-Sti.S-C-B-1-16	HA-16-Sti.S-B-1-16						
THIS DRAWING IS A CONTROLLED DOCUMENT.																		DWN	Schneider	09.02.2000			
																		CHK	Schweiger	09.02.2000			
																		APVD					
DIMENSIONS: mm																		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME			
																		PRODUCT SPEC		108-74007			
MATERIAL																		APPLICATION SPEC		114-77009			
ORDERING TEXT / BESTELLTEXT																		WEIGHT		A2 00779			
CUSTOMER DRAWING																		SCALE		1:1			
																		SHEET		1 OF 1			
																		REV		D6			

1471-9 (1/15)

1103416

A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heavy Duty Power Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[647757-1](#) [6643411-1](#) [6646058-2](#) [6646137-1](#) [6646138-1](#) [6646479-1](#) [6646608-1](#) [6646786-1](#) [6646940-1](#) [6651091-1](#) [6651525-1](#) [6651529-1](#)
[6651788-1](#) [696475-1](#) [702-32-01109](#) [703-25-02205](#) [73000005059](#) [73000005642](#) [73080255059](#) [73080965046](#) [765-15-0080A](#) [765-16-0080B](#)
[765-18-0080D](#) [829992-1](#) [902-77-02113](#) [PS00/A0620/6300](#) [PS25/A0420/63](#) [129-1J](#) [1409400](#) [AN0024023](#) [E6374G1](#) [e6389g2](#) [157-43GW8](#)
[MS3117-14AC](#) [1643543-1](#) [1650540-1](#) [1651811-2](#) [1766260-1](#) [1766282-1](#) [1766966-1](#) [1791340000](#) [NLDFT-3-BL-L-S120-M40A](#) [NLDFT-N-](#)
[W-L-C240-M40B](#) [NLS-2-R-C240-M40B](#) [NLS-N-W-C240-M40B](#) [NPS-3-BL-T6](#) [1986615-1](#) [2-1589900-8](#) [2199314-1](#) [KA8102](#)