2-1747050-4 ACTIVE

GRACE INERTIA 7.92

TE Internal #: 2-1747050-4

Rectangular Power Connectors, Housing, Plug, Wire-to-Board, 2 Position, 7.92 mm [.312 in] Centerline, Wire & Cable, UL 94V-0,

GRACE INERTIA 7.92

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors > Glow Wire GRACE INERTIA Plug











Rectangular Power Connector Type: Housing

Connector & Housing Type: Plug
Connector System: Wire-to-Board

Number of Positions: 2

Centerline (Pitch): 7.92 mm [.312 in]

All Glow Wire GRACE INERTIA Plug (78)

Features

Product Type Features

Rectangular Power Connector Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	2
Number of Power Positions	2
Number of Signal Positions	2
Number of Rows	1
Electrical Characteristics	

300 VDC

Operating Voltage



Contact Features

Contact reatures	
Multiple Contact Types	Without
Contact Mating Area Plating Material	Tin
Contact Current Rating (Max)	10 A
Contact Retention Within Housing	With
Contact Type	Receptacle
Contact Mating Area Plating Material Thickness	.8 μm[31.5 μin]
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	7.92 mm[.312 in]
Housing Color	Yellow
Housing Material	Nylon 6/6 GF
Dimensions	
Wire Size	434.18 – 2723.46 CMA
Usage Conditions	
Operating Temperature Range	-30 - 105 °C[-22 - 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Identification Marking	
Circuit Identification Feature	Without
Industry Standards	
UL Flammability Rating	UL 94V-0
Glow Wire Rating	GWT 750°C (Without Flame)
Packaging Features	
Packaging Quantity	1500
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | GRACE INERTIA 7.92





Customers Also Bought

















Documents

Product Drawings

GIC 7.92 2POS PLUG YELLOW KEYING C

English

CAD Files

Customer View Model

ENG_CVM_CVM_2-1747050-4_F.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1747050-4_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1747050-4_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Rectangular Power Connectors, Housing, Plug, Wire-to-Board, 2 Position, 7.92 mm [. 312 in] Centerline, Wire & Cable, UL 94V-0, GRACE INERTIA 7.92



Product Specifications

5.0 POWER KEY CONNECTOR

Japanese

Application Specification

Japanese

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power to the Board category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

6643429-1 6651939-1 6766604-1 120959-1 1393557-2 1393532-2 1393532-3 1393557-1 1744132-7 1-6450850-6 1-6450869-6 1645526-2 2005243-2 377-0020-11130 MC116N TE34-12-16P-F0 51700-10201602AALF 51970-004 5-6450830-6 4-6600333-3 10130248-005LF 6600320-3 1888123-2 701-15-02109 6450810-7 46437-1112 6450813-2 6450842-4 1645523-1 6651670-1 1761385-3 46562-1175 2221861-1 98-1100-0230-4 MC4006D 46437-1545 46437-1650 46437-1652 46562-1476 46562-1650 46562-1652 6450551-8 10106262-0017101LF 10077488-N01006DLF 2085124-1 45985-0020 QE-POL-POST QE50-DC-60 DF22A-1416PCA DF22-1416PCA