



### General Information

<b>Kit Part Number:</b>	<a href="#">2-2110852-6</a>
<b>Description:</b>	Through Hole Dual Row Vertical Header and Receptacle Connector Kit
<b>Application:</b>	Commercial Lighting, Consumer Lighting, LED Lighting Applications
<b>Family:</b>	Micro MATE-N-LOK
<b>TE Brand:</b>	AMP Products
<b>Solution:</b>	Off the Board
<b>Product Type:</b>	Wire-to-Board Connectors
<b>Number of Pieces:</b>	136
<b>RoHS:</b>	Yes

### Specifications

<b>Circuit Size(s):</b>	2, 4, 6, 8, 10
<b>Color:</b>	Black
<b>Crimp Terminal:</b>	Female
<b>Current Rating:</b>	5A
<b>Flammability Rating:</b>	UL94V-0
<b>Mounting Style:</b>	PCB Through Hole
<b>Orientation:</b>	Vertical Headers
<b>Pitch:</b>	3.00mm (.118")
<b>Product/Type:</b>	Receptacle
<b>Rows:</b>	Dual Row
<b>Tool Included:</b>	No
<b>Voltage Rating:</b>	250V
<b>Wire Gauge (AWG):</b>	24-20

### Product Highlights

Contacts are on 3 mm [.118] centerline spacing; 2-12 contact positions &ndash; single row; 2-24 contact positions &ndash; dual row. Panel mount or free-hanging wire-to-wire configurations. Dual beam contact design for reliable interconnection. Contacts accept 24-20 [0.2-0.6] and 30-26 [0.05-0.15] AWG wire with insulation diameter of .060 [1.52] maximum. Contacts available in strip form or loose piece. PCB mount pin header assemblies in both vertical and right-angle styles. Surface mount or through hole PCB pin header attachment. PCB headers are IR reflow process compatible.

#### Features and Benefits

- Less than 4.7 mm in vertical height required
- Right angle surface mount headers with surface mount hold-downs
- Positive latching to prevent unmating
- 2, 3, and 4 positions available
- Black and natural colors available

#### Applications

- LED Lighting Applications
- Consumer Lighting:
- Shelf/Cabinet
- Under Counter



- Cove Lighting
- Commercial Lighting:
- Signage
- Refrigeration
- Display Cases



**Bill of Materials**

Part No.	Qty In Kit	Description	Datasheet	P/N Details	Search Distributors Inventory
<a href="#">794610-1-C</a>	100	Micro MATE-N-LOK Female Terminals 24-20 AWG	<a href="#">Datasheet</a>	<a href="#">Details</a>	<a href="#">Search</a>
<a href="#">794617-2</a>	5	Micro MATE-N-LOK, 2 Circuits, Receptacle Dual Row 3mm	<a href="#">Datasheet</a>	<a href="#">Details</a>	<a href="#">Search</a>
<a href="#">794617-6</a>	4	Micro MATE-N-LOK, 6 Circuits, Receptacle Dual Row 3mm	<a href="#">Datasheet</a>	<a href="#">Details</a>	<a href="#">Search</a>
<a href="#">794617-8</a>	3	Micro MATE-N-LOK, 8 Circuits, Receptacle Dual Row 3mm	<a href="#">Datasheet</a>	<a href="#">Details</a>	<a href="#">Search</a>
<a href="#">1-794617-0</a>	2	Micro MATE-N-LOK, 10 Circuits, Receptacle Dual Row 3mm	<a href="#">Datasheet</a>	<a href="#">Details</a>	<a href="#">Search</a>
<a href="#">3-794630-2</a>	5	Micro MATE-N-LOK, 2 Circuits, Vertical Header Dual Row 3mm	<a href="#">Datasheet</a>	<a href="#">Details</a>	<a href="#">Search</a>
<a href="#">3-794630-4</a>	4	Micro MATE-N-LOK, 4 Circuits, Vertical Header Dual Row 3mm	<a href="#">Datasheet</a>	<a href="#">Details</a>	<a href="#">Search</a>
<a href="#">3-794630-6</a>	4	Micro MATE-N-LOK, 6 Circuits, Vertical Header Dual Row 3mm	<a href="#">Datasheet</a>	<a href="#">Details</a>	<a href="#">Search</a>
<a href="#">3-794630-8</a>	3	Micro MATE-N-LOK, 8 Circuits, Vertical Header Dual Row 3mm	<a href="#">Datasheet</a>	<a href="#">Details</a>	<a href="#">Search</a>
<a href="#">4-794630-0</a>	2	Micro MATE-N-LOK, 10 Circuits, Vertical Header Dual Row 3mm	<a href="#">Datasheet</a>	<a href="#">Details</a>	<a href="#">Search</a>
<a href="#">794617-4</a>	4	Micro MATE-N-LOK, 4 Circuits, Receptacle Dual Row 3mm	<a href="#">Datasheet</a>	<a href="#">Details</a>	<a href="#">Search</a>

**Recommended Tool**

Part No.	Included in Kit
<a href="#">91501-1</a>	No







Kit Part No. **2-2110852-6**

## Micro MATE-N-LOK Connector Kit

Through Hole Dual Row Vertical Header and Receptacle

- 3.00mm Pitch
- 2, 4, 6, 8 and 10 Circuits
- Vertical Headers with Retention Feature
- Female Crimp Terminals: 24-26 AWG
- 5 Amps (Max.), 250 VDRS
- Flammability Rating: UL 94V-0

Additional kits available at: [www.productkits.com](http://www.productkits.com)

Micro MATE-N-LOK, TE Connectivity, TE connectivity logo and TE logo are trademarks of the TE Connectivity Ltd. family of companies.  
**WARNING:** Failure to follow all instructions in Application Specifications (1-11-0002) (available at [www.teconnectivity.com](http://www.teconnectivity.com)), including using only approved TE crimping (if applicable), can result in improper installation and/or operating effect in the product and may create an unsafe or hazardous situation. Please refer to our website for additional safety and proper installation information.

**136**  
pieces



Product from TE Connectivity, kits designed and assembled by Waldom Electronics.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)  
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)  
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [79531-3000](#) [FCN-](#)  
[360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)  
[801-43-006-10-002000](#)