

#### O.C.H. Micro Circular Connectors

TE Internal #: 2226920-1

O.C.H. Micro Circular Connectors, Standard Circular Connectors, Wire-to-Wire, 6 Position, Sealable, Wire & Cable, 5A Contact

Current Rating (Max)

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors



Connector System: Wire-to-Wire

Number of Positions: 6

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

Contact Current Rating (Max): 5 A

# **Features**

# **Product Type Features**

Accessory Color	Black
Prewired	No
Product Type	Connector Kit
Assembly Type	Electrical Connector
Connector System	Wire-to-Wire
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Circular Connector Type	Receptacle
Shell Type	Round Flange Receptacle

# **Configuration Features**

Keying & Polarized Position Locations	Normal
Factory Installed Backshell	Without
Keying	Triple Key
Number of Positions	6
Number of Power Positions	0
Number of Signal Positions	6
Contacts Preloaded	No



# **Body Features**

Shield Rating	100 - 10000 MHz
Environmental Protection Type	Elastomer Sealed
Entry Style	Rear Insertion
Peripheral Seal Material	Fluorosilicone Elastomer
Positive Stop Ferrule	Without
Environmental Protection	With
Weight	2.8 g[.006 lb]
O-Ring Material	Fluorosilicone
Fluid Type	None
Feedthrough Type	No
Shell Plating Material	Black Zinc Nickel
Shell Base Material	Aluminum 6061-T6
Circular Connector Insulation Material Type	LCP (Liquid Crystal Polymer)
Hermetically Sealed	No
Contact Footons	

### **Contact Features**

Contact Current Rating (Max)	5 A
Reverse Gender	No
Circular Connector Contact Type	Socket

### Mechanical Attachment

Mating Alignment	With
Mating Retention Type	Push-Pull Self-Locking
PCB Mount Alignment	Without
Panel Mount Feature	Without
PCB Mount Retention	Without
Panel Mount Feature Type	Round Flange
Mating Alignment Type	Keyed
Mating Retention	With
Housing Features	

Circular Connector Shell Size	6
Alignment Keyed	Insert Clocking

# Dimensions



Accepts Wire Insulation Diameter Range	.76 – 1.37 mm[.03 – .054 in]
Wire Size	22 – 24 AWG
Usage Conditions	
IP Dust Sealing Level	5
Fluid Resistance	Immersible
Operating Temperature Range	-10 – 70 °C
Operation/Application	
Durability Rating	2000 Cycles
Circuit Application	Signal
Shielded	Yes
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	1
Other	
Position Locations Omitted	All
Field Serviceable	No

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Pb (.6% in CONTACT) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





TE Part # 2101550-1 PLUG,7 POS,Sz103,w/SOLDER CUPS, 140 POT







# Also in the Series | O.C.H. Micro Circular Connectors



Connector Contacts(2)




Crimp Wire Pins, Tabs & Ferrules(1)



Standard Circular Connectors(6)

# Customers Also Bought













TE Part #2226913-2 CONTACT, PIN, CRIMPED, SIZE 23, GND



TE Part #2226923-1 CONTACT, SOCKET, HOODED, CRIMP, SIZE23



TE Part #2828420-1
RECEPTACLE CONNECTOR
ASSEMBLY PCB TAIL



TE Part #1214-202-2378 R SNAP

### **Documents**

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2226920-1\_N.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2226920-1\_N.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2226920-1\_N.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# Datasheets & Catalog Pages

O.C.H. Micro Circular Connectors

English

# **Product Specifications**

**Product Specification** 

English

#### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular MIL Spec Connector category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

0025-262-542 0025-264-3014 58-570121-04S 0134-202-1200 0134-207-1206 0134-207-1800 0134-207-2207 0134-213-0806 0134-213-1007 0134-213-1009 0134-213-1208 0134-213-1800 0134-213-2209 0025-258-000 015-9516-002 60-042722-19P 0114-201-1278 602GB06EG24-61SN 0134-201-1207 0134-201-1806 0134-201-2006 0134-201-2007 0134-201-2010 0134-202-1400 0134-207-0809 0134-207-1208 0134-207-2009 0134-213-1006 6104-207-2302 6104-208-1902 6104-215-0902 6131-202-19149P 6131-204-21149P 6131-207-13149P 6131-208-13149P 6131-209-17149P 6131-210-11149P 6131-211-19149P 6131-216-19149P 6131-220-25149P 6131-259-11149P 6131-259-23149P 6131-263-19149P 6131-265-17149P 6131-265-19149P CS3102A-20-15P CS3102A-20-15S CS3106A-10SL-53S CS3106A-10SL-64S