

# Sockets & Accessories, KHA Relays

- **O** Sockets for 2 4 pole relays with solder terminals
- □ Solder, PCB or screw terminal sockets
- **Choice of grounding provision on sockets**
- **I** Hold down springs
- **D** Plates and brackets permit various mounting options



Approvals UL E22575 and E59244, CSA LR15734 Technical data of approved types on request


Technical Data	
Socket contact material	Spring brass, tin plated
Socket body material	
27E006, 27E220, 27E023, 27E007	Nylon
& 27E894	-
27E166	Glass-filled polyester
Maximum current	5A

### **Ordering Code**

Product Code	Poles	Terminal type	Grounding provision	Part number
27E006	4	solder terminals	yes	1419106-1
27E220	2	pcb terminals	no	1419106-7
27E023	4			1419106-3
27E007	4		yes	1419106-2

#### Dimensions


Sockets with PCB or solder terminals



Recommended chassis cutout for solder terminal socket



Recommended Chassis Thickness .031 (.79) to .062 (1.57)



.525 →

(13.34)

350

(8.89)


Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at <a href="http://relays.te.com/definitions">http://relays.te.com/definitions</a>

(1.78)


Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change. 1

### **Dimensions (continued)**

Socket with pierced solder terminals



Socket with printed circuit terminals



**Caution:** Printed circuit sockets are manufactured with "floating" (Loose) terminals. This permits them to align with holes in the circuit board and with the relay terminals. During the mounting and soldering of the socket, vertical float should be eliminated and the terminals seated on the board. (This may be accomplished by inserting a durmy relay in the socket.) Failure to eliminate float may cause fracture of the solder joint or separation of the copper conductor from the printed circuit board when a relay is inserted in the socket after soldering.

PC board layout (bottom view) for PCB terminal socket

**FL** ()

11-2015, Rev. 1115 www.te.com © 2012 Tyco Electronics Corporation, a TE Connectivity Ltd. company Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.




# Sockets & Accessories, KHA Relays (Continued)

## **Ordering Code**

Product Code	Poles	Terminal type	Grounding provision	Part number
27E166	4	screw terminals	yes	1-1393143-9
27E894	4		no	2-1419106-6

#### **Dimensions and terminal location**

Screw terminal socket 27E166




## **Ordering Code**

Product Code	Description	Part number
20C217	Relay hold down spring	1419111-2
20C297	Relay hold down spring - use with 27E166	4-1393159-3
20C426	Relay hold down spring - use with 27E894	5-1393159-1
37D633	Mounting strip - accepts eight 27E006	1419111-7
24A110	Mounting track	1419111-6
24A071	Steel mounting clip with #6-32 screw -	1419111-5
	use with 27E166 on 24A110 track	
24A072	Plastic twist mounting clip -	5-1393159-4
	use with 27E166 on 24A110 track	
40G432	Plastic insulator - use with 24A071 to make	9-1393159-5
	end clip for 24A110 track	

All accessories must be ordered separately.


#### Dimensions


37D633 mounting strip



37D633 will mount eight solder terminal sockets in one length of aluminum strip measuring 10.97" x 2.25" x .062 (278.6 x 57.15 x 1.57)

Screw terminal, DIN rail, snap-mount socket 27E894






Top view

20C217 hold down spring (shown with relay in 27E006 socket)



24A110 DIN rail style mounting track



24A110 mounting track is designed to accept snap-mount sockets, as well as other P&B screw terminal sockets. Track is made of lightweight, sturdy extruded aluminum and is shipped in three-foot (914cm) lengths with mounting holes on six-inch (152mm) centers. Track can be cut to shorter lengths or used end-to-end.

Track and mounting accessories



24A071

11-2015, Rev. 1115 www.te.com © 2012 Tyco Electronics Corporation, a TE Connectivity Ltd. company

2

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section. Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Relay Sockets & Fixings category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below :

00008258500
00111976502
0000-825-81-00
60SY4S05
M41G
670-0125
670-0127
6700152
670-0153
6700156
D258-2TS00
70-309
7 

1393143-3
7-1616360-5
8000-DG2-5
911361
9-1616339-5
PJF11N
GDA12HA
GDA12SA
GDA12SD
GDA16HD
GDA22HA

GDA95A
GDA95D
GFX20
PT08QN
PT 1/8 D = 3.2
GUA1
GUA2-11
GUA4-04
GUA4-31
GUM5R
GUR-120
GUR-24
GUR-240

GUR-277
GURX-277
GUW12
GUW95
GUZ63L
R99-11
FOR MY(NAMEPLATE)
D52PR2T
RES100K
1310H-HDC
1390H-1ST

1393824-3
1390H-2PC
1410-2SM
6000-2SM
6000-2SM</td