

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

| P | LTR | DESCRIPTION | DATE | DWN | APVD |
|---|-----|---------------------------|-----------|-----|------|
| | A1 | REVISED PER ECO-11-005033 | 02APR2011 | RK | HMR |
| | A2 | REDRAW IN TO CREO | 14APR2017 | GH | JP |
| | | | | | |
| | | | | | |

Technical drawing of a Mini Mic SRS Tab Contact. The drawing includes a front view, a side view, and a cross-sectional view. Key dimensions are provided in millimeters:

- Front view: Total length 22.7 ±0.3 mm, Zone A length 5.6 mm, Zone B length 6.2 mm, contact width 1.6 ±0.2 mm, and a 0.8 ±0.2 mm diameter feature.
- Side view: Total length 10.4 ±0.2 mm, Zone A length 5.6 mm, and a 2 ±0.2 mm diameter feature.
- Cross-sectional view: Contact width 5.2 ±0.3 mm, contact height 4.7 ±0.3 mm, and a 2.5 ±0.2 mm diameter feature.

Two cross-sectional views, A-A and B-B, showing the internal profile of the contact. View A-A shows a width of 2.5 ±0.2 mm and a height of 2.3 ±0.3 mm. View B-B shows a width of 5.2 ±0.3 mm and a height of 4.7 ±0.3 mm.

1 GOLD PLATED 0.8 μm OVER "ZONE A". TIN PLATED OVER "ZONE B" AND NICKEL UNDERPLATING ALL OVER. DORATURA 0.8 μm NELLA "ZONA A". STAGNATURA NELLA "ZONA B" E NICHELATURA SU TUTTO IL CONTATTO.

2 SUITABLE FOR SINGLE WIRE SEAL TE P/N 281934-4 ADATTO PER GOMMINO PASSACAVO TE P/N 281934-4

A2 3 ITEM IS SUPPLIED REELED ON CARTON REEL WITH STRIP PITCH = 11.9 ±0.1mm STATO DI FORNITURA: AVVOLTI SU BOBINA CON PASSO TRA TERMINALI DI = 11.9 ±0.1mm

| | |
|----------------------------------|----------------------------|
| INS. DIA. RANGE (DIAM. ISOLANTE) | WIRE RANGE (RANGO FILO) |
| 2 | Ø0.35 - 0.5mm ² |

DIRECTION OFF TOP OF REEL
SENSO DI USCITA DALLA BOBINA

Diagram showing the direction of the reel, with an arrow indicating the direction of travel.

THIS DRAWING IS A CONTROLLED DOCUMENT.

| DIMENSIONS: | TOLERANCES UNLESS OTHERWISE SPECIFIED: |
|-------------|--|
| mm | |
| | 0 PLC ± |
| | 1 PLC ±- |
| | 2 PLC ±- |
| | 3 PLC ±- |
| | 4 PLC ±- |
| | ANGLES ±2° |
| MATERIAL | FINISH |
| - | - |
| - | - |

| | | |
|------------------|-----------|---------|
| DWN | C.BERTINI | JUN1992 |
| CHK | A.BRUNI | JUN1992 |
| APVD | - | - |
| PRODUCT SPEC | 108-20090 | |
| APPLICATION SPEC | 114-20045 | |
| WEIGHT | - | |
| CUSTOMER DRAWING | | |

| | | | | |
|---------------------------------|-----------|----------------------|----------------------|--------|
| GOLD PLTD (DORATO) 1 | | BRASS (OTTONE) | 282404-3 | A |
| PRE-TIN (PRE STAGNATO) | | BRASS (OTTONE) | 282404-1 | A |
| FINISH/COLOUR (FINITURA/COLORE) | | MATERIAL (MATERIALE) | TE PART NO. (NUMERO) | REV |
| STE TE Connectivity | | | | |
| NAME: MINI MIC SRS TAB CONTACT | | | | |
| SIZE | CAGE CODE | DRAWING NO | RESTRICTED TO | |
| A3 | 00779 | ©=282404 | - | |
| SCALE 5:1 | | | SHEET 1 OF 1 | REV A2 |

1470-19 (3/13)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Automotive Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[003-018-000](#) [60403001](#) [60993906-B](#) [M902-2131](#) [M902-2161](#) [72.330.1035.1](#) [73.353.4028.0](#) [F119300-B](#) [F166900](#) [F258300-B](#) [F358300-B](#)
[F407400](#) [F444110](#) [F487000](#) [F509500B-B](#) [827153-1](#) [8N1515-32-24P](#) [9-1326729-8](#) [925474-1](#) [928905-1](#) [964562-4](#) [968782-1](#) [GT17SA-8DS-](#)
[HU](#) [98891-1012](#) [98947-1016](#) [12004147](#) [12004475-L](#) [12010290](#) [12010309-B](#) [12015454](#) [12020219-B](#) [12020308](#) [12041318-B](#) [12052225-L](#)
[12052466](#) [12059125](#) [12064869](#) [12004327-B](#) [12010503-B](#) [12015308](#) [12015384](#) [12015909](#) [1-21030-1](#) [12041254](#) [12041318](#) [12047946-B](#)
[12047957](#) [12047957-L](#) [12059473](#) [12066261](#)