

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION .19
 BY AMP INCORPORATED. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
ES	00	D4	REVISED ECR-17-010413	20JUL17	T.Z H.W

PC BOARD MOUNTING DIMENSIONS $\Delta 4$

$\Delta 1$ MATERIAL:
 $\Delta 1$ SHELL : STAINLESS STEEL.
 CONTACTS: COPPER ALLOY.
 HOUSING: UL 94V-0 RATED, THERMOPLASTIC, BLACK.

$\Delta 2$ PLATING:
 CONTACTS: 0.076 μ m MINIMUM GOLD OVER 0.76 μ m MINIMUM PALLADIUM-NICKEL ON MATING AREA.
 3.8 μ m MINIMUM MATTE TIN ON SOLDER TAILS.
 BOTH OVER 1.27 μ m MINIMUM NICKEL.
 CONTACT ALTERNATE PLATING: 0.76 μ m MIN GOLD ON MATING AREA, 3.8 μ m MIN MATTE TIN ON SOLDER TAILS, BOTH OVER 1.27 μ m MIN NICKEL.
 SHELL: 2.0~5.0 μ m MINIMUM TIN.

$\Delta 3$ DATUM AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.

$\Delta 4$ RECOMMENDED PC BOARD THICKNESS OF 1.57.

$\Delta 5$ PLATING:
 CONTACTS: 0.76 μ m MINIMUM GOLD ON MATING AREA, 3.8 μ m MINIMUM MATTE TIN ON SOLDER TAILS, BOTH OVER 1.27 μ m MINIMUM NICKEL.
 SHELL: 2.0~5.0 μ m MINIMUM TIN.

$\Delta 6$ PLATING:
 CONTACTS: 0.38 μ m MINIMUM GOLD ON MATING AREA, 3.8 μ m MINIMUM MATTE TIN ON SOLDER TAILS, BOTH OVER 1.27 μ m MINIMUM NICKEL.
 SHELL: 2.0~5.0 μ m MINIMUM TIN.

7 RECOMMEND:
 MATING FORCE: 35N MAX.
 UNMATING FORCE: 13N MIN.
 RECOMMENDED MATING PLUG SHOULD MEET USB2.0 STANDARD.

SECTION X-X

$\Delta 6$	NO	BLACK	292304-5
$\Delta 5$	NO	BLACK	292304-4
$\Delta 2$	YES	BLACK	292304-3
$\Delta 2$	YES	NATURAL	292304-2
$\Delta 2$	NO	BLACK	292304-1
PLATING	HIGH TEMPERATURE COMPATIBLE	HOUSING COLOR	PART NUMBER

DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN J.JIANG 23FEB04	Tyco Electronics Tyco electronics coporation Shanghai, P.R.China, 200233
$\begin{matrix} 0 \text{ PLC} & \pm \\ 1 \text{ PLC} & \pm \\ 2 \text{ PLC} & \pm 0.1 \\ 3 \text{ PLC} & \pm \\ 4 \text{ PLC} & \pm \\ \text{ANGLES} & \pm \\ \text{FINISH} & \pm \end{matrix}$		$\begin{matrix} \Delta 1 \\ \Delta 2 \end{matrix}$		CHK S.YAO 23FEB04	
MATERIAL $\Delta 1$		FINISH $\Delta 2$		APVD T.SASAKI 23FEB04	NAME RECEPTACLE ASSEMBLY, RIGHT ANGLE, 4 POSITION, THRU-HOLE, TYPE B UNIVERSAL SERIAL BUS, LEAD FREE VERSION
CUSTOMER DRAWING		SCALE 5:1		PRODUCT SPEC	SIZE A2
		SHEET 1 OF 1		APPLICATION SPEC	CAGE CODE 00779
		REV D4		WEIGHT -	DRAWING NO C-292304

AMP 1471-9 REV 10/93 Translated 040217.101735 (YYMDD.HHMMSS) from Computervision, Inc., Medusa Revision 12.2.5T

292304

B

A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[65-647-8-BK-BU](#) [950](#) [952](#) [E8144-B01021-L](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBD11135](#) [217450-1](#) [KMBVX-TH-5S-B30](#) [896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [17-210051](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [A-USB A-2P-C](#) [MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SMT-AS1N-W30](#) [4689-1](#) [1-1734084-2](#) [E8110-001-01](#) [33UBARS1-04SW11](#) [33UBAR-04SW11](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#) [10135326-001LF](#) [USB-A-S-F-B-VT](#) [925](#) [4198](#) [690-024-633-031](#) [KUSBEX-BSFS1N-W](#) [USBFTVC6MRG](#) [UA-20BMFA-SL8001](#) [17-250101](#) [USBFTVC7ZC](#) [USBFTV75NF459](#)