



DESIGNED FOR USE WITH	.141 SR CABLE
CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.144 (3.66)
CONTACT	.037 (0.94)

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
B1	REVISED PER ECO-11-005294	13APR11	HMR

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204
COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BRASS PER ASTM-B-16, HALF HARD	GOLD PLATE PER MIL-G-45204
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
RETAINING RING	PHOSPHOR BRONZE PER QQ-B-750, GRADE B2	N/A

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348A, Fig. 304.1	Temperature Rating -65°C TO +105°C
Frequency Range (GHz) DC to 18	Recommended Mating Torque 12-15 LBS	Vibration MIL-STD-1344, Method 2005, Condition IV, 30g Peak.
Volt Rating (VRMS MAX) @ Sea Level 500	Force to Engage and Disengage (In/Lbs MAX) 6.0	Shock MIL-STD-1344, Method 2004, Condition G
VSWR 1.06 + .007 f(GHz)	Cable Retention Axial Force (Lbs) 60	Thermal Shock MIL-STD-1344, Method 1003, Condition A, Except High Temp 115°C
Insertion Loss (dB MAX) .05 √f(GHz)	Torque (In/Oz) 55	Humidity MIL-STD-1344, Method 1002.
RF Leakage (dB MIN) -90 @ 2-3 GHz	Weight (Grams) 20.6	No measurements at high humidity.
Corona, 70,000 Ft (VRMS MIN) 375		Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1,500		
Contact Resistance (Milliohms MAX)		
Center Contact 1.5		
Outer Contact 2.0		
Cable to Housing 2.0		
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 1,000		
I.R.(Megohms MIN) 5,000		

COMPONENT	MATERIAL	FINISH
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON		
FRAC.	DEC.	ANGLES
± 1/64	±.005	± °
DRAWN BY DRB	DATE 6-15-67	
CHECKED BY EDT	7-19-67	
APPD BY D.NANIA	9-25-67	
USE ASS'Y PROCEDURE		
408-04915 (30-001)		
NO. AP.		
TITLE TYPE N STRAIGHT CABLE PLUG DIRECT SOLDER ATTACHMENT		
SIZE B	CODE IDENT NO. 26805	1057088-1
SCALE 4:1		REV B1
SHEET 1 OF 1		

CUSTOMER DRAWING

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors](#) / [Coaxial Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[8915-1511-000](#) [89674-0827](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39030/3-01N](#) [6500-7071-046](#) [6769](#) [CX050L2AQ](#) [7002-1541-010](#) [7002-1542-011](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-015](#) [7210-1511-019](#) [73137-5015](#) [73216-2241](#) [73404-2300](#) [7405-1521-005](#) [7405-1521-802](#) [8527](#) [8547](#) [FS11V](#) [877931](#) [8808-1511-001](#) [9049-9513-000](#) [9074-9513-000](#) [9101-9573-002](#) [910A205F](#) [9130-9573-002](#) [PL11SC-026](#) [PL375-33](#) [PL40-5](#) [PL74C-221](#) [PL75MC-217](#) [PL803-7](#) [1200690078](#) [1-201144-1](#) [R107003010W](#) [R110A172100](#)