


REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
042	UPDATED	8/1/94	BB



.XXX = in  
XX.X = mm

ELECTRICAL	MECHANICAL	ENVIRONMENTAL	HOUSING	DIELECTRIC	CENTER CONTACT	COMPONENT	MATERIAL	FINISH
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions MIL-STD-348A, Fig. 304.2	Temperature Rating <u>-65°C to +125°C</u>	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	TFE FLUOROCARBON PER ASTM-D-1457	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	NICKEL PLATE PER QQ-N-290
Frequency Range (GHz) DC to <u>11</u>	Recommended Mating Torque <u>N/A</u>	Vibration MIL-STD-202, Method 204, Condition B				TOLERANCE ON	TFE FLUOROCARBON PER ASTM-D-1457	N/A
Volt Rating (VRMS MAX) @ Sea Level <u>1000</u>	Mating Characteristics: Insertion (MAX lbs) <u>2.0</u>	Shock MIL-STD-202, Method 213, Condition I				FRAC. DEC. ANGLES	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
VSWR <u>N/A</u>	Withdrawal (MIN oz) <u>2.0</u>	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +115°C				± 1/64 ±.005 ± °		
Insertion Loss (dB MAX) <u>N/A</u>	Force to Engage and Disengage (in-lbs MAX) <u>3.0</u>	Moisture Resistance MIL-STD-202, Method 106						
RF Leakage (dB MIN) <u>N/A</u>	Center Contact Captivation Axial (lbs) <u>6.0</u>	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray						
Corona, 70,000 Ft (VRMS MIN) <u>500</u>	Radial (in-oz) <u>4.0</u>							
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>2500</u>								
Contact Resistance (Milliohms MAX) Center Contact <u>1.0</u>								
Outer Contact <u>.2</u>								
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>1500</u>								
I.R.(Megohms MIN) <u>5000</u>								
			USE ASS'Y PROCEDURE	TITLE OSN FLANGE MOUNT JACK RECEPTACLE SOLDER POT TERMINAL		AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599		
			NO. AP. <u>N/A</u>	SCALE <u>2:1</u>	SIZE <u>B</u>	CODE IDENT NO. <u>26805</u>	<u>3052-0000-10</u>	REV <u>042</u>
								SHEET 1 OF 1

CUSTOMER DRAWING

AMP PART # 1057284-1  
SHEET 1 OF 1 REV A

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [RF Connectors](#) / [Coaxial Connectors](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[8915-1511-000](#) [89674-0827](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39030/3-01N](#) [6500-7071-046](#) [6769](#) [CX050L2AQ](#) [7002-1541-010](#) [7002-1542-011](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-015](#) [7210-1511-019](#) [73137-5015](#) [73216-2241](#) [73404-2300](#) [7405-1521-005](#) [7405-1521-802](#) [8527](#) [8547](#) [FS11V](#) [877931](#) [8808-1511-001](#) [9074-9513-000](#) [9101-9573-002](#) [910A205F](#) [9130-9573-002](#) [PL11SC-026](#) [PL375-33](#) [PL40-5](#) [PL74C-221](#) [PL75MC-217](#) [PL803-7](#) [1200690078](#) [1-201144-1](#) [R107003010W](#) [R110A172100](#) [R112186000](#)