



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A1	REVISED PER ECO-11-005294	13APR11	HMR

COMPONENT	MATERIAL	FINISH
HOUSING MOUNTING NUT	BRASS PER QQ-B-626 COMP. 360, HALF HARD	NICKEL PLATE PER QQ-N-290 OVER COPPER PLATE PER MIL-C-14550
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
LOCKWASHER	PHOSPHOR BRONZE PER QQ-B-750, GRADE B2	NICKEL PLATE PER QQ-N-290 OVER COPPER PLATE PER MIL-C-14550
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) <u>50</u>	Interface Dimensions	Temperature Rating <u>-65°C to +125°C</u>
Frequency Range (GHz) DC to <u>4</u>	BNC <u>MIL-STD-348A Fig. 301.2</u>	Vibration <u>MIL-STD-202, Method 204, Condition D</u>
Volt Rating (VRMS MAX) <u>Sea Level 335</u>	OSM <u>MIL-STD-348A Fig. 310.2</u>	Shock <u>MIL-STD-202, Method 213, Condition I</u>
VSWR <u>1.30 Max at 0.5 to 4.0 GHz</u>	Recommended Mating Torque <u>4-6 In-Lbs</u>	Thermal Shock <u>MIL-STD-202, Method 107, Condition C, Except High Temp</u>
Insertion Loss (dB MAX) <u>0.2√f(GHz)</u>	Mating Characteristics:	Moisture Resistance <u>MIL-STD-202, Method 106 Shall Be Omitted</u>
RF Leakage (dB MIN) <u>-55, 2 to 3 GHz</u>		Corrosion - <u>MIL-STD-202, Method 101, Condition B, 5% salt spray</u>
Corona, 70,000 Ft (VRMS MIN) <u>250</u>	Insertion (Lbs Max) <u>2.0 3.0</u>	
Dielectric Withstanding Voltage (VRMS MIN) <u>Sea Level 1500</u>	Withdrawal (Oz Min) <u>2.0 1.0</u>	
Contact Resistance (Milliohms MAX)	Force to Engage/Disengage	
Center Contact <u>4.1</u>	Longitudinal	
Outer Contact <u>2.2</u>	Force (Lb Max) <u>3.0 N/A</u>	
RF High Potential <u>Sea Level (VRMS MIN @ 5 MHz) 670</u>	Torque (In-Lb Max) <u>2.5 2.0</u>	
I.R.(Megohms MIN) <u>5000</u>	Contact Retention	
	Axial (Lbs) <u>6.0</u>	
	Radial (In-Oz) <u>4.0</u>	
	Weight (Grams) _____	

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY <u>AUGUST TARDIFF</u> DATE <u>5/18/90</u>		
TOLERANCE ON	CHECKED BY <u>S. ALLERDICE</u> DATE <u>6/6/90</u>		
FRAC. DEC. ANGLES	APPD BY <u>B. CLEVELAND</u> DATE <u>8/3/90</u>		
$\pm 1/64$	$\pm .005$	$\pm 1^\circ$	TITLE <u>BNC JACK TO OSM JACK BULKHEAD FEEDTHROUGH ADAPTER</u>
	USE ASS'Y PROCEDURE		
	NO. AP. <u>N/A</u>		
		SIZE <u>B</u>	CODE IDENT NO. <u>26805</u>
		SCALE <u>2:1</u>	1058117-1
			REV <u>A1</u>
			SHEET 1 OF 1

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [RF Adapters - Between Series](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[5945-9503-000](#) [MCX/F-SMA/M](#) [R192417010](#) [ADBJ20-E1-BJ379](#) [ADM2](#) [ADPL75-A1-PL75](#) [242191](#) [9317505](#) [29-3835P](#) [AD130](#) [ADBJ20-E1-PL74](#) [ADBJ77-A1PL3155](#) [ADBJ77-E1-UPL20](#) [ADRMF370](#) [242215](#) [242228](#) [R125680000W](#) [R192430000](#) [UAD95](#) [1057367-1](#) [8311505](#) [R114704000](#) [R451034500](#) [R451030500](#) [R451543000](#) [HDVDPN](#) [ADBJ20-K1-PL20](#) [R451570000](#) [R192419000](#) [R451034000](#) [J9](#) [J3WE-5](#) [R451032500](#) [242201RP](#) [17K132-K00S5](#) [03K719-S22S3](#) [AD-RSMAF-RTNC](#) [53K156-K00N5](#) [53K160-KIMN1](#) [02K119-K00E3](#) [29S132-K01N5](#) [53S156-K00N5](#) [02S119-S00E3](#) [28K132-K00N5](#) [02S109-K00S3](#) [27-8200TP](#) [242235](#) [ADBJ20-E1-BJ89](#) [ADP-SMAF-MMCXM](#) [000-2900](#)