



- 1 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 2 ASSEMBLIES MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
- 3 TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADERS ARE HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- 4 .000030 GOLD ON THE CONTACT AREA, .000100-.000200 MATTE TIN-LEAD ON THE SOLDER TAIL, ALL OVER .000050 NICKEL
- 5 BREAKAWAY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
- 6 .000030 GOLD ON THE CONTACT AREA, .000100-.000200 MATTE TIN ON THE SOLDER TAIL, ALL OVER .000050 NICKEL
- 7 HIGH TEMPERATURE CONFIGURATION
- 8 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



REMARKS	PLATING	C	B	A	NO OF POS	ASSEMBLY PART NUMBER	REMARKS	PLATING	C	B	A	NO OF POS	ASSEMBLY PART NUMBER
		3.984	3.900	39	80	9-103801-0			3.984	3.900	39	80	4-103801-0
		3.884	3.800	38	78	8-103801-9			3.884	3.800	38	78	3-103801-9
		3.784	3.700	37	76	8-103801-8			3.784	3.700	37	76	3-103801-8
		3.684	3.600	36	74	8-103801-7			3.684	3.600	36	74	3-103801-7
		3.584	3.500	35	72	8-103801-6			3.584	3.500	35	72	3-103801-6
		3.484	3.400	34	70	8-103801-5			3.484	3.400	34	70	3-103801-5
		3.284	3.300	33	68	8-103801-4			3.284	3.300	33	68	3-103801-4
		3.284	3.200	32	66	8-103801-3			3.284	3.200	32	66	3-103801-3
		3.184	3.100	31	64	8-103801-2			3.184	3.100	31	64	3-103801-2
		3.084	3.000	30	62	8-103801-1			3.084	3.000	30	62	3-103801-1
		2.984	2.900	29	60	3-103801-0			2.984	2.900	29	60	3-103801-0
		2.884	2.800	28	58	7-103801-9			2.884	2.800	28	58	2-103801-9
		2.784	2.700	27	56	7-103801-8			2.784	2.700	27	56	2-103801-8
		2.684	2.600	26	54	7-103801-7			2.684	2.600	26	54	2-103801-7
		2.584	2.500	25	52	7-103801-6			2.584	2.500	25	52	2-103801-6
		2.484	2.400	24	50	7-103801-5			2.484	2.400	24	50	2-103801-5
		2.384	2.300	23	48	7-103801-4			2.384	2.300	23	48	2-103801-4
		2.284	2.200	22	46	7-103801-3			2.284	2.200	22	46	2-103801-3
		2.184	2.100	21	44	7-103801-2			2.184	2.100	21	44	2-103801-2
		2.084	2.000	20	42	7-103801-1			2.084	2.000	20	42	2-103801-1
		1.984	1.900	19	40	7-103801-0			1.984	1.900	19	40	2-103801-0
		1.884	1.800	18	38	6-103801-9			1.884	1.800	18	38	1-103801-9
		1.784	1.700	17	36	6-103801-8			1.784	1.700	17	36	1-103801-8
		1.684	1.600	16	34	6-103801-7			1.684	1.600	16	34	1-103801-7
		1.584	1.500	15	32	6-103801-6			1.584	1.500	15	32	1-103801-6
		1.484	1.400	14	30	6-103801-5			1.484	1.400	14	30	1-103801-5
		1.384	1.300	13	28	6-103801-4			1.384	1.300	13	28	1-103801-4
		1.284	1.200	12	26	6-103801-3			1.284	1.200	12	26	1-103801-3
		1.184	1.100	11	24	6-103801-2			1.184	1.100	11	24	1-103801-2
		1.084	1.000	10	22	6-103801-1			1.084	1.000	10	22	1-103801-1
		.984	.900	9	20	6-103801-0			.984	.900	9	20	1-103801-0
		.884	.800	8	18	5-103801-9			.884	.800	8	18	103801-9
		.784	.700	7	16	5-103801-8			.784	.700	7	16	103801-8
		.684	.600	6	14	5-103801-7			.684	.600	6	14	103801-7
		.584	.500	5	12	5-103801-6			.584	.500	5	12	103801-6
		.484	.400	4	10	5-103801-5			.484	.400	4	10	103801-5
		.384	.300	3	8	5-103801-4			.384	.300	3	8	103801-4
		.284	.200	2	6	5-103801-3			.284	.200	2	6	103801-3
		.184	.100	1	4	5-103801-2			.184	.100	1	4	103801-2
		.084			2	5-103801-1			.084			2	103801-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

INCHES: DIMENSIONS: 0 PLC ± .005, 1 PLC ± .005, 2 PLC ± .005, 3 PLC ± .005, 4 PLC ± .005. TOLERANCES UNLESS OTHERWISE SPECIFIED: SEE TABLE.

MATERIAL: HOUSING - FLAME RETARDANT THERMOPLASTIC, COLOR - BLACK, POSTS - COPPER ALLOY. FINISH: SEE TABLE.

APPROVED: R. FLICKER, DATE: 31-7-85. NAME: ASSEMBLY, MOD II, HEADER, BREAKAWAY, DOUBLE ROW, RIGHT ANGLE, .100X.100 C/L, WITH .025 SQUARE POSTS.

SIZE: A1, CASE CODE: 00779, DRAWING NO: 103801. WEIGHT: -. RESTRICTED TO: -. SCALE: 4:1, SHEET: 1 OF 1, REV: J.

STE TE Connectivity

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)