



RECOMMENDED HOLE LAYOUT

- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
- TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK. CONTACT: COPPER ALLOY
- FINISH: 0.000381 [.000015] GOLD ON CONTACT AREA, 0.00254-0.00508 [.000100-.000200] MATTE TIN-LEAD ON SOLDER TAIL, ALL OVER 0.00127 [.000050] NICKEL.
- FINISH: 0.000381 [.000015] GOLD ON CONTACT AREA, 0.00254-0.00508 [.000100-.000200] MATTE TIN ON SOLDER TAIL, ALL OVER 0.00127 [.000050] NICKEL.

| PLATING | G | F | E | NO. OF POSITIONS | PART NUMBER |
|---------|----------------|---------------|----|------------------|-------------|
| 6 | 101.19 [3.984] | 99.06 [3.900] | 39 | 40 | 9-146466-0 |
| 6 | 98.65 [3.884] | 96.52 [3.800] | 38 | 39 | 8-146466-9 |
| 6 | 96.11 [3.784] | 93.98 [3.700] | 37 | 38 | 8-146466-8 |
| 6 | 93.57 [3.684] | 91.44 [3.600] | 36 | 37 | 8-146466-7 |
| 6 | 91.03 [3.584] | 88.90 [3.500] | 35 | 36 | 8-146466-6 |
| 6 | 88.49 [3.484] | 86.36 [3.400] | 34 | 35 | 8-146466-5 |
| 6 | 85.95 [3.384] | 83.82 [3.300] | 33 | 34 | 8-146466-4 |
| 6 | 83.41 [3.284] | 81.28 [3.200] | 32 | 33 | 8-146466-3 |
| 6 | 80.87 [3.184] | 78.74 [3.100] | 31 | 32 | 8-146466-2 |
| 6 | 78.33 [3.084] | 76.20 [3.000] | 30 | 31 | 8-146466-1 |
| 6 | 75.79 [2.984] | 73.66 [2.900] | 29 | 30 | 8-146466-0 |
| 6 | 73.25 [2.884] | 71.12 [2.800] | 28 | 29 | 7-146466-9 |
| 6 | 70.71 [2.784] | 68.58 [2.700] | 27 | 28 | 7-146466-8 |
| 6 | 68.17 [2.684] | 66.04 [2.600] | 26 | 27 | 7-146466-7 |
| 6 | 65.63 [2.584] | 63.50 [2.500] | 25 | 26 | 7-146466-6 |
| 6 | 63.09 [2.484] | 60.96 [2.400] | 24 | 25 | 7-146466-5 |
| 6 | 60.55 [2.384] | 58.42 [2.300] | 23 | 24 | 7-146466-4 |
| 6 | 58.01 [2.284] | 55.88 [2.200] | 22 | 23 | 7-146466-3 |
| 6 | 55.47 [2.184] | 53.34 [2.100] | 21 | 22 | 7-146466-2 |
| 6 | 52.93 [2.084] | 50.80 [2.000] | 20 | 21 | 7-146466-1 |
| 6 | 50.39 [1.984] | 48.26 [1.900] | 19 | 20 | 7-146466-0 |
| 6 | 47.85 [1.884] | 45.72 [1.800] | 18 | 19 | 6-146466-9 |
| 6 | 45.31 [1.784] | 43.18 [1.700] | 17 | 18 | 6-146466-8 |
| 6 | 42.77 [1.684] | 40.64 [1.600] | 16 | 17 | 6-146466-7 |
| 6 | 40.23 [1.584] | 38.10 [1.500] | 15 | 16 | 6-146466-6 |
| 6 | 37.69 [1.484] | 35.56 [1.400] | 14 | 15 | 6-146466-5 |
| 6 | 35.15 [1.384] | 33.02 [1.300] | 13 | 14 | 6-146466-4 |
| 6 | 32.61 [1.284] | 30.48 [1.200] | 12 | 13 | 6-146466-3 |
| 6 | 30.07 [1.184] | 27.94 [1.100] | 11 | 12 | 6-146466-2 |
| 6 | 27.53 [1.084] | 25.40 [1.000] | 10 | 11 | 6-146466-1 |
| 6 | 24.99 [0.984] | 22.86 [0.900] | 9 | 10 | 6-146466-0 |
| 6 | 22.45 [0.884] | 20.32 [0.800] | 8 | 9 | 5-146466-9 |
| 6 | 19.91 [0.784] | 17.78 [0.700] | 7 | 8 | 5-146466-8 |
| 6 | 17.37 [0.684] | 15.24 [0.600] | 6 | 7 | 5-146466-7 |
| 6 | 14.83 [0.584] | 12.70 [0.500] | 5 | 6 | 5-146466-6 |
| 6 | 12.29 [0.484] | 10.16 [0.400] | 4 | 5 | 5-146466-5 |
| 6 | 9.75 [0.384] | 7.62 [0.300] | 3 | 4 | 5-146466-4 |
| 6 | 7.21 [0.284] | 5.08 [0.200] | 2 | 3 | 5-146466-3 |
| 6 | 4.67 [0.184] | 2.54 [0.100] | 1 | 2 | 5-146466-2 |
| 6 | 2.13 [0.084] | - | - | 1 | 5-146466-1 |

| PLATING | G | F | E | NO. OF POSITIONS | PART NUMBER |
|---------|----------------|---------------|----|------------------|-------------|
| 5 | 101.19 [3.984] | 99.06 [3.900] | 39 | 40 | 4-146466-0 |
| 5 | 98.65 [3.884] | 96.52 [3.800] | 38 | 39 | 3-146466-9 |
| 5 | 96.11 [3.784] | 93.98 [3.700] | 37 | 38 | 3-146466-8 |
| 5 | 93.57 [3.684] | 91.44 [3.600] | 36 | 37 | 3-146466-7 |
| 5 | 91.03 [3.584] | 88.90 [3.500] | 35 | 36 | 3-146466-6 |
| 5 | 88.49 [3.484] | 86.36 [3.400] | 34 | 35 | 3-146466-5 |
| 5 | 85.95 [3.384] | 83.82 [3.300] | 33 | 34 | 3-146466-4 |
| 5 | 83.41 [3.284] | 81.28 [3.200] | 32 | 33 | 3-146466-3 |
| 5 | 80.87 [3.184] | 78.74 [3.100] | 31 | 32 | 3-146466-2 |
| 5 | 78.33 [3.084] | 76.20 [3.000] | 30 | 31 | 3-146466-1 |
| 5 | 75.79 [2.984] | 73.66 [2.900] | 29 | 30 | 3-146466-0 |
| 5 | 73.25 [2.884] | 71.12 [2.800] | 28 | 29 | 2-146466-9 |
| 5 | 70.71 [2.784] | 68.58 [2.700] | 27 | 28 | 2-146466-8 |
| 5 | 68.17 [2.684] | 66.04 [2.600] | 26 | 27 | 2-146466-7 |
| 5 | 65.63 [2.584] | 63.50 [2.500] | 25 | 26 | 2-146466-6 |
| 5 | 63.09 [2.484] | 60.96 [2.400] | 24 | 25 | 2-146466-5 |
| 5 | 60.55 [2.384] | 58.42 [2.300] | 23 | 24 | 2-146466-4 |
| 5 | 58.01 [2.284] | 55.88 [2.200] | 22 | 23 | 2-146466-3 |
| 5 | 55.47 [2.184] | 53.34 [2.100] | 21 | 22 | 2-146466-2 |
| 5 | 52.93 [2.084] | 50.80 [2.000] | 20 | 21 | 2-146466-1 |
| 5 | 50.39 [1.984] | 48.26 [1.900] | 19 | 20 | 2-146466-0 |
| 5 | 47.85 [1.884] | 45.72 [1.800] | 18 | 19 | 1-146466-9 |
| 5 | 45.31 [1.784] | 43.18 [1.700] | 17 | 18 | 1-146466-8 |
| 5 | 42.77 [1.684] | 40.64 [1.600] | 16 | 17 | 1-146466-7 |
| 5 | 40.23 [1.584] | 38.10 [1.500] | 15 | 16 | 1-146466-6 |
| 5 | 37.69 [1.484] | 35.56 [1.400] | 14 | 15 | 1-146466-5 |
| 5 | 35.15 [1.384] | 33.02 [1.300] | 13 | 14 | 1-146466-4 |
| 5 | 32.61 [1.284] | 30.48 [1.200] | 12 | 13 | 1-146466-3 |
| 5 | 30.07 [1.184] | 27.94 [1.100] | 11 | 12 | 1-146466-2 |
| 5 | 27.53 [1.084] | 25.40 [1.000] | 10 | 11 | 1-146466-1 |
| 5 | 24.99 [0.984] | 22.86 [0.900] | 9 | 10 | 1-146466-0 |
| 5 | 22.45 [0.884] | 20.32 [0.800] | 8 | 9 | 146466-9 |
| 5 | 19.91 [0.784] | 17.78 [0.700] | 7 | 8 | 146466-8 |
| 5 | 17.37 [0.684] | 15.24 [0.600] | 6 | 7 | 146466-7 |
| 5 | 14.83 [0.584] | 12.70 [0.500] | 5 | 6 | 146466-6 |
| 5 | 12.29 [0.484] | 10.16 [0.400] | 4 | 5 | 146466-5 |
| 5 | 9.75 [0.384] | 7.62 [0.300] | 3 | 4 | 146466-4 |
| 5 | 7.21 [0.284] | 5.08 [0.200] | 2 | 3 | 146466-3 |
| 5 | 4.67 [0.184] | 2.54 [0.100] | 1 | 2 | 146466-2 |
| 5 | 2.13 [0.084] | - | - | 1 | 146466-1 |

THIS DRAWING IS A CONTROLLED DOCUMENT.

| | | | | | | | |
|-------------------------|--|-----------|-----------|-------------------|--------------------|----------------------|---------------|
| DIMENSIONS: mm [INCHES] | TOLERANCES UNLESS OTHERWISE SPECIFIED: | 0 PLC ± - | 1 PLC ± - | 2 PLC ± 0.51[.02] | 3 PLC ± 0.12[.005] | 4 PLC ± 0.012[.0005] | ANGLES ± - |
| MATERIAL | FINISH SEE TABLE | WEIGHT | — | SIZE | CAGE CODE | DRAWING NO | RESTRICTED TO |
| 4 | | | | A1 | 00779 | 146466 | — |

CUSTOMER DRAWING SCALE 4:1 SHEET 1 OF 1 REV B

STE TE Connectivity
 HOFFMAN 18JAN96
 DUBNICZKI 4MAR96
 DUBNICZKI 4MAR96
 NAME
 PRODUCT SPEC
 APPLICATION SPEC
 HEADER ASSEMBLY, MOD II, STACKING, SINGLE ROW, .025 SQ.POST, UNSHROUDED

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009508121](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#) [67095-007LF](#) [68002-116](#) [68016-236H](#) [68648-049](#)