


LOC		DIST		REVISIONS				
AD	00	P	LTR	DESCRIPTION	DATE	DN	APVO	
S	REVISED PER	ECO-15-008006			17NOV2015	NK	MM	



- 1 HOUSING: PBT, UL 94V-0 RATED, COLOR-BLACK
CONTACTS: COPPER ALLOY PER ASTM B103
- 2 MOLDED CIRCUIT #1 IDENTIFIER IN LOCATION SHOWN.
- 3 0.00076[.000030] MIN GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] TIN-LEAD IN AREA E, ALL OVER 0.00127[.000050] MIN NICKEL.
- 4 0.00076[.000030] MIN GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] TIN IN AREA E, ALL OVER 0.00127[.000050] MIN NICKEL.
- 5 USE WITH #20-#22 AWG WIRE SIZE, .050 MAX INSULATION DIA., .015 MAX INSULATION WALL THICKNESS.
- 6 CONTACT IDENTIFICATION NUMBER "3" LOCATED IN THIS AREA.
- 7 AMP TRADEMARK (EITHER SIDE).
- 8 OBSOLETE PART NUMBER.
- 9 ROHS 2002/95/EC COMPLIANT.
- 10 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

FINISH	B	A	NO. OF POSN	PART NO.
4 9	81.28 [3.200]	31	64	8-102448-0
4 9	76.20 [3.000]	29	60	7-102448-8
4 9	68.58 [2.700]	26	54	7-102448-5
4 9	63.50 [2.500]	24	50	7-102448-3
4 9	50.80 [2.000]	19	40	6-102448-8
4 9	43.18 [1.700]	16	34	6-102448-5
4 9	40.64 [1.600]	15	32	6-102448-4
4 9	38.10 [1.500]	14	30	6-102448-3
4 9	35.56 [1.400]	13	28	6-102448-2
4 9	33.02 [1.300]	12	26	6-102448-1
4 9	30.48 [1.200]	11	24	6-102448-0
4 9	27.94 [1.100]	10	22	5-102448-9
4 9	25.40 [1.000]	9	20	5-102448-8
4 9	22.86 [.900]	8	18	5-102448-7
4 9	20.32 [.800]	7	16	5-102448-6
4 9	17.78 [.700]	6	14	5-102448-5
4 9	15.24 [.600]	5	12	5-102448-4
4 9	12.70 [.500]	4	10	5-102448-3
4 9	10.16 [.400]	3	8	5-102448-2
4 9	7.62 [.300]	2	6	5-102448-1

FINISH	B	A	NO. OF POSN	PART NO.
3	91.44 [3.600]	35	72	3-102448-4
3	88.90 [3.500]	34	70	3-102448-3
3	86.36 [3.400]	33	68	3-102448-2
3	83.82 [3.300]	32	66	3-102448-1
3	81.28 [3.200]	31	64	3-102448-0
3	78.74 [3.100]	30	62	2-102448-9
3	76.20 [3.000]	29	60	2-102448-8
3	73.66 [2.900]	28	58	2-102448-7
3	71.12 [2.800]	27	56	2-102448-6
3	68.58 [2.700]	26	54	2-102448-5
3	66.04 [2.600]	25	52	2-102448-4
3	63.50 [2.500]	24	50	2-102448-3
3	60.96 [2.400]	23	48	2-102448-2
3	58.42 [2.300]	22	46	2-102448-1
3	55.88 [2.200]	21	44	2-102448-0
3	53.34 [2.100]	20	42	1-102448-9
3	50.80 [2.000]	19	40	1-102448-8
3	48.26 [1.900]	18	38	1-102448-7
3	45.72 [1.800]	17	36	1-102448-6
3	43.18 [1.700]	16	34	1-102448-5
3	40.64 [1.600]	15	32	1-102448-4
3	38.10 [1.500]	14	30	1-102448-3
3	35.56 [1.400]	13	28	1-102448-2
3	33.02 [1.300]	12	26	1-102448-1
3	30.48 [1.200]	11	24	1-102448-0
3	27.94 [1.100]	10	22	102448-9
3	25.40 [1.000]	9	20	102448-8
3	22.86 [.900]	8	18	102448-7
3	20.32 [.800]	7	16	102448-6
3	17.78 [.700]	6	14	102448-5
3	15.24 [.600]	5	12	102448-4
3	12.70 [.500]	4	10	102448-3
3	10.16 [.400]	3	8	102448-2
3	7.62 [.300]	2	6	102448-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

APPROVED: S. SHUEY, 06JAN92, M. RIDER, 07JAN92

PRODUCT SPEC: 108-25015

APPLICATION SPEC: 114-25032

WEIGHT: -

CUSTOMER DRAWING

SCALE: 4:1

SHEET 1 OF 1

REV S

STE TE Connectivity

AMPMODU MT, RCPT ASSY, STANDARD PRESSURE CONTACTS FOR 20-22 AWG WIRE SIZE

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)