


LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD		
	N2	REVISED PER ECO-11-004587	11MAR11	RK	HMR		



- 1 CONTACTS ARE LATCHED INTO THE PRELOAD WINDOWS
- 2 USE WITH #22-#26 AWG WIRE SIZE, .054/.030 INSULATION DIAMETER, .015 MAXIMUM INSULATION THICKNESS
- 3 THE DIMENSION APPLIES WITH THE FORWARD PRELOAD STOP IN CONTACT WITH THE HOUSING SURFACE
- 4 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 5 FOR INDIVIDUAL ASSEMBLIES SEE PART NUMBER 103644
- 6 ASSEMBLIES ARE JOINED BY THE CARRIER STRIP. ORDER QUANTITY REFLECTS TOTAL NUMBER OF INDIVIDUAL ASSEMBLIES REQUIRED. SEE TABLE FOR NUMBER OF ASSEMBLIES PER STRIP.
- 7 POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE BEAMS)
- 8 MAXIMUM ALLOWABLE BOW OF ASSEMBLY NOT TO EXCEED .055.
- 9 .000015 GOLD IN THE CONTACT AREA. .000050-.000100 BRIGHT TIN-LEAD ON THE TERMINATION AREA. ALL OVER .000050 NICKEL.
- 10 .000015 GOLD IN THE CONTACT AREA. .000050-.000100 BRIGHT TIN ON THE TERMINATION AREA. ALL OVER .000050 NICKEL.
- 11 PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
- 12 .000015 GOLD IN THE CONTACT AREA. .000050-.000100 MATTE TIN ON THE TERMINATION AREA. ALL OVER .000050 NICKEL.
- 13 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



EXAMPLE: STRIP ASSEMBLY  
SCALE 2:1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	L A MAYER	11-4-86	<b>STE</b> TE Connectivity																					
DIMENSIONS: INCHES		CHK	P de Jong	11-12-86																						
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	P de Jong	11-12-86																						
<table border="0"> <tr><td>0 PLC</td><td>±</td><td>-</td></tr> <tr><td>1 PLC</td><td>±</td><td>-</td></tr> <tr><td>2 PLC</td><td>±</td><td>.02</td></tr> <tr><td>3 PLC</td><td>±</td><td>.005</td></tr> <tr><td>4 PLC</td><td>±</td><td>-</td></tr> <tr><td>ANGLES</td><td>±</td><td>-</td></tr> <tr><td>FINISH</td><td>±</td><td>-</td></tr> </table>		0 PLC	±	-		1 PLC	±	-	2 PLC	±	.02	3 PLC	±	.005	4 PLC	±	-	ANGLES	±	-	FINISH	±	-	PRODUCT SPEC	108-25034	NAME
0 PLC	±	-																								
1 PLC	±	-																								
2 PLC	±	.02																								
3 PLC	±	.005																								
4 PLC	±	-																								
ANGLES	±	-																								
FINISH	±	-																								
MATERIAL	HOUSING: SEE TABLE	APPLICATION SPEC	114-25026	SIZE	A2																					
		WEIGHT	-	CAGE CODE	00779																					
		CUSTOMER DRAWING		DRAWING NO	C=103957																					
		SCALE	4:1	SHEET	1 of 2																					
		REV	N2																							

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AD	00	SEE SHEET 1	-	-	-

△12	2	2.40	1.198	1-104257-1	12	6-103957-1	
△12	2	2.20	1.098	1-104257-0	11	6-103957-0	
△12	2	2.00	.998	104257-9	10	5-103957-9	
△12	2	1.80	.898	104257-8	9	5-103957-8	
△12	2	1.60	.798	104257-7	8	5-103957-7	
△12	2	1.40	.698	104257-6	7	5-103957-6	
△12	4	2.39	.598	104257-5	6	5-103957-5	
△12	4	1.99	.498	104257-4	5	5-103957-4	
△12	5	1.99	.398	104257-3	4	5-103957-3	
△12	8	2.40	.298	104257-2	3	5-103957-2	
△12	10	2.00	.198	104257-1	2	5-103957-1	
△10	2	1.40	.698	104257-6	7	2-103957-0	
△11	△11	2	2.40	1.198	1-104257-1	12	1-103957-9
△11	△11	2	2.00	.998	104257-9	10	1-103957-8
△10	2	1.60	.798	104257-7	8	1-103957-7	
△10	4	2.39	.598	104257-5	6	1-103957-6	
△10	4	1.99	.498	104257-4	5	1-103957-5	
△10	5	1.99	.398	104257-3	4	1-103957-4	
△10	8	2.40	.298	104257-2	3	1-103957-3	
△10	10	2.00	.198	104257-1	2	1-103957-2	
△9	2	2.40	1.198	1-104257-1	12	1-103957-1	
△9	2	2.20	1.098	1-104257-0	11	1-103957-0	
△9	2	2.00	.998	104257-9	10	103957-9	
△9	2	1.80	.898	104257-8	9	103957-8	
△9	2	1.60	.798	104257-7	8	103957-7	
△9	2	1.40	.698	104257-6	7	103957-6	
△9	4	2.39	.598	104257-5	6	103957-5	
△9	4	1.99	.498	104257-4	5	103957-4	
△9	5	1.99	.398	104257-3	4	103957-3	
△9	8	2.40	.298	104257-2	3	103957-2	
△9	10	2.00	.198	104257-1	2	103957-1	
PLATING	△6	B	A	HOUSING PART NUMBER	NO OF POSN	ASSEMBLY PART NUMBER ON STRIP	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L A MAYER 11-4-86	<b>STE</b> TE Connectivity	
DIMENSIONS: INCHES		CHK P de Jong 11-12-86		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD P de Jong 11-12-86	NAME	
0 PLC ± -		PRODUCT SPEC	RCPT ASSY, AMPMODU MTE, SINGLE	
1 PLC ± -		108-25034	ROW, .100 C/L, LATCHED & POLARIZED	
2 PLC ± .02		APPLICATION SPEC	FOR #22-#25 AWG WIRE SIZE, STRIP FORM	
3 PLC ± .005		114-25026	SIZE	RESTRICTED TO
4 PLC ± -		WEIGHT	A2 00779	103957
ANGLES ± -		CUSTOMER DRAWING	SCALE	REV
FINISH SEE TABLE		SCALE 1:1	SHEET 2 OF 2	N2

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)  
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)  
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)  
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)