



- 1 CONTACTS ARE LATCHED INTO THE PRELOAD WINDOWS
- 2 USE WITH #26-#30 AWG WIRE SIZE, .054/.030 INSULATION DIAMETER, .015 MAXIMUM INSULATION THICKNESS
- 3 THE DIMENSION APPLIES WITH THE FORWARD PRELOAD STOP IN CONTACT WITH THE HOUSING SURFACE
- 4 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 5 FOR INDIVIDUAL ASSEMBLIES SEE PART NUMBER 103641
- 6 ASSEMBLIES ARE JOINED BY THE CARRIER STRIP. ORDER QUANTITY REFLECTS TOTAL NUMBER OF INDIVIDUAL ASSEMBLIES REQUIRED. SEE TABLE FOR NUMBER OF ASSEMBLIES PER STRIP.
- 7 POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE BEAMS)
- 8 MAXIMUM ALLOWABLE BOW OF ASSEMBLY NOT TO EXCEED .055.
- 9 .000100-.000200 BRIGHT TIN-LEAD OVER .000050 NICKEL.
- 10 .000100-.000200 BRIGHT TIN OVER .000050 NICKEL.
- 11 PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
- 12 .000100-.000200 MATTE TIN OVER .000050 NICKEL.
- 13 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

PLATING	6	B	A	HOUSING PART NUMBER	NO OF POSN	ASSEMBLY PART NUMBER ON STRIP	
13	12	2	2.40	1.198	1-104257-1	12	6-103959-1
13	12	2	2.20	1.098	1-104257-0	11	6-103959-0
	12	2	2.00	.998	104257-9	10	5-103959-9
	12	2	1.80	.898	104257-8	9	5-103959-8
	12	2	1.60	.798	104257-7	8	5-103959-7
13	12	2	1.40	.698	104257-6	7	5-103959-6
	12	4	2.39	.598	104257-5	6	5-103959-5
	12	4	1.99	.498	104257-4	5	5-103959-4
	12	5	1.99	.398	104257-3	4	5-103959-3
	12	8	2.40	.298	104257-2	3	5-103959-2
	12	10	2.00	.198	104257-1	2	5-103959-1
	10	5	1.99	.398	104257-3	4	1-103959-3
	11	4	1.99	.498	104257-4	5	1-103959-2
13	9	2	2.40	1.198	1-104257-1	12	1-103959-1
13	9	2	2.20	1.098	1-104257-0	11	1-103959-0
	9	2	2.00	.998	104257-9	10	103959-9
13 SUPERSEDED	9	2	1.80	.898	104257-8	9	103959-8
	9	2	1.60	.798	104257-7	8	103959-7
13	9	2	1.40	.698	104257-6	7	103959-6
	9	4	2.39	.598	104257-5	6	103959-5
	9	4	1.99	.498	104257-4	5	103959-4
	9	5	1.99	.398	104257-3	4	103959-3
	9	8	2.40	.298	104257-2	3	103959-2
	9	10	2.00	.198	104257-1	2	103959-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN	L A MAYER	11-4-86
CHK	P de Jong	11-12-86
APVD	P de Jong	11-12-86

TE Connectivity

RCPT ASSY, AMPMODU MTE, SINGLE ROW .100 C/L, LATCHED AND POLARIZED FOR #26-#30 AWG WIRE SIZE, STRIP FORM

108-25034
114-25026

SIZE: A2 CAGE CODE: 00779 DRAWING NO: C=103959

SCALE: 4:1 SHEET: 1 of 1 REV: M2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)