



- 1 MATERIAL:  
RECEPTACLE CONTACTS- PHOSPHOR BRONZE  
RECEPTACLE HOUSING AND TERMINATING COVERS- THERMOPLASTIC,  
COLOR: BLACK.
- 2 PLATING:  
RECEPTACLE CONTACTS- 0.00076 [.000030] MINIMUM GOLD PLATE IN CONTACT AREA,  
0.00127 [.000050] MINIMUM BRIGHT TIN-LEAD PLATE IN TERMINATION AREA,  
ALL OVER 0.00127 [.000050] MINIMUM NICKEL.
- 3 RECOMMENDED WIRE:  
28 AWG- 0.91 [.036] MAX O.D. PVC OR POLYETHYLENE INSULATION.
- 4 SHORT-LONG CONTACT SEQUENCE MUST ALTERNATE BUT MAY BEGIN WITH EITHER  
A SHORT OR LONG CONTACT.
- 5 PLATING:  
RECEPTACLE CONTACTS- 0.00076 [.000030] MINIMUM GOLD PLATE IN CONTACT AREA,  
0.00127 [.000050] MINIMUM MATTE TIN PLATE IN TERMINATION AREA,  
ALL OVER 0.00127 [.000050] MINIMUM NICKEL.
- 6 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

		71.83 [2.828]	63.91 [2.516]	62.23 [2.450]	49	100	6-104892-0
	5	65.48 [2.578]	57.56 [2.266]	55.88 [2.200]	44	90	<del>5-104892-9</del>
	5	59.13 [2.328]	51.21 [2.016]	49.53 [1.950]	39	80	5-104892-8
	5	52.78 [2.078]	44.86 [1.766]	43.18 [1.700]	34	70	5-104892-7
	5	46.43 [1.828]	38.51 [1.516]	36.83 [1.450]	29	60	<del>5-104892-6</del>
	5	40.08 [1.578]	32.16 [1.266]	30.48 [1.200]	24	50	5-104892-5
	5	33.73 [1.328]	25.81 [1.016]	24.13 [.950]	19	40	5-104892-4
	5	27.38 [1.078]	19.46 [.766]	17.78 [.700]	14	30	5-104892-3
	5	21.03 [.828]	13.11 [.516]	11.43 [.450]	9	20	5-104892-2
	5	14.68 [.578]	6.76 [.266]	5.08 [.200]	4	10	5-104892-1
	6	71.83 [2.828]	63.91 [2.516]	62.23 [2.450]	49	100	<del>1-104892-0</del>
	6	65.48 [2.578]	57.56 [2.266]	55.88 [2.200]	44	90	<del>104892-9</del>
	6	59.13 [2.328]	51.21 [2.016]	49.53 [1.950]	39	80	104892-8
	6	52.78 [2.078]	44.86 [1.766]	43.18 [1.700]	34	70	104892-7
	6	46.43 [1.828]	38.51 [1.516]	36.83 [1.450]	29	60	<del>104892-6</del>
	6	40.08 [1.578]	32.16 [1.266]	30.48 [1.200]	24	50	104892-5
	6	33.73 [1.328]	25.81 [1.016]	24.13 [.950]	19	40	104892-4
	6	27.38 [1.078]	19.46 [.766]	17.78 [.700]	14	30	104892-3
	6	21.03 [.828]	13.11 [.516]	11.43 [.450]	9	20	104892-2
	6	14.68 [.578]	6.76 [.266]	5.08 [.200]	4	10	<del>104892-1</del>
		D	C	B	A	NO OF POSN	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN: J. HERRINGTON 6-18-93  
CHK: P. SREMCICH 6-24-93

STE TE Connectivity

PRODUCT SPEC: AMPMODU 108-1443  
APPLICATION SPEC: 50/50 GRID CABLE CONN. ASSY WITH LATCH

SIZE: A1 CAGE CODE: 00779C DRAWING NO: 104892

RESTRICTED TO: CUSTOMER DRAWING

SCALE: 10:1 SHEET: 1 of 1 REV: G3

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)  
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)  
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)  
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)