



RECOMMENDED PC BOARD MOUNTING DIMENSIONS FOR .063[1.60] THICK PC BOARD AND .012[.305] STENCIL THICK

- TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD.
- THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING.
- RETENTION FEATURES ON SOLDER TAILS, LOCATED AT MANUFACTURERS OPTION.
- ϕ 0.51[.020]Ⓜ FOR KINKED TAILS.
- HOUSING: LCP, COLOR-BLACK. POST: COPPER ALLOY.
- 0.000381 [.000015] GOLD IN CONTACT AREA, 0.00254-0.00508 [.0000100-.0000200] MATTE TIN-LEAD ON SOLDER TAIL, ALL OVER 0.00127 [.000050] NICKEL.
- 0.000381 [.000015] GOLD IN CONTACT AREA, 0.00254-0.00508 [.0000100-.0000200] MATTE TIN ON SOLDER TAIL, ALL OVER 0.00127 [.000050] NICKEL.
- OBsolete PARTS: OBsolete CIS STREAMLINING PER D.RENAUD/D.SINISI

PLATING	C	B	A	NO. OF POSITIONS	PART NUMBER	PLATING	C	B	A	NO. OF POSITIONS	PART NUMBER
△	101.19 [3.984]	99.06 [3.900]	39	80	9-146268-0	△	101.19 [3.984]	99.06 [3.900]	39	80	4-146268-0
△	98.65 [3.884]	96.52 [3.800]	38	78	8-146268-9	△	98.65 [3.884]	96.52 [3.800]	38	78	△ 3-146268-9
△	96.11 [3.784]	93.98 [3.700]	37	76	8-146268-8	△	96.11 [3.784]	93.98 [3.700]	37	76	△ 3-146268-8
△	93.57 [3.684]	91.44 [3.600]	36	74	8-146268-7	△	93.57 [3.684]	91.44 [3.600]	36	74	△ 3-146268-7
△	91.03 [3.584]	88.90 [3.500]	35	72	8-146268-6	△	91.03 [3.584]	88.90 [3.500]	35	72	△ 3-146268-6
△	88.49 [3.484]	86.36 [3.400]	34	70	8-146268-5	△	88.49 [3.484]	86.36 [3.400]	34	70	△ 3-146268-5
△	85.95 [3.384]	83.82 [3.300]	33	68	8-146268-4	△	85.95 [3.384]	83.82 [3.300]	33	68	△ 3-146268-4
△	83.41 [3.284]	81.28 [3.200]	32	66	8-146268-3	△	83.41 [3.284]	81.28 [3.200]	32	66	△ 3-146268-3
△	80.87 [3.184]	78.74 [3.100]	31	64	8-146268-2	△	80.87 [3.184]	78.74 [3.100]	31	64	△ 3-146268-2
△	78.33 [3.084]	76.20 [3.000]	30	62	8-146268-1	△	78.33 [3.084]	76.20 [3.000]	30	62	△ 3-146268-1
△	75.79 [2.984]	73.66 [2.900]	29	60	8-146268-0	△	75.79 [2.984]	73.66 [2.900]	29	60	△ 3-146268-0
△	73.25 [2.884]	71.12 [2.800]	28	58	7-146268-9	△	73.25 [2.884]	71.12 [2.800]	28	58	△ 2-146268-9
△	70.71 [2.784]	68.58 [2.700]	27	56	7-146268-8	△	70.71 [2.784]	68.58 [2.700]	27	56	△ 2-146268-8
△	68.17 [2.684]	66.04 [2.600]	26	54	7-146268-7	△	68.17 [2.684]	66.04 [2.600]	26	54	△ 2-146268-7
△	65.63 [2.584]	63.5 [2.500]	25	52	7-146268-6	△	65.63 [2.584]	63.5 [2.500]	25	52	△ 2-146268-6
△	63.09 [2.484]	60.96 [2.400]	24	50	7-146268-5	△	63.09 [2.484]	60.96 [2.400]	24	50	△ 2-146268-5
△	60.55 [2.384]	58.42 [2.300]	23	48	7-146268-4	△	60.55 [2.384]	58.42 [2.300]	23	48	△ 2-146268-4
△	58.01 [2.284]	55.88 [2.200]	22	46	7-146268-3	△	58.01 [2.284]	55.88 [2.200]	22	46	△ 2-146268-3
△	55.47 [2.184]	53.34 [2.100]	21	44	7-146268-2	△	55.47 [2.184]	53.34 [2.100]	21	44	△ 2-146268-2
△	52.93 [2.084]	50.80 [2.000]	20	42	7-146268-1	△	52.93 [2.084]	50.80 [2.000]	20	42	△ 2-146268-1
△	50.39 [1.984]	48.26 [1.900]	19	40	7-146268-0	△	50.39 [1.984]	48.26 [1.900]	19	40	△ 2-146268-0
△	47.85 [1.884]	45.72 [1.800]	18	38	6-146268-9	△	47.85 [1.884]	45.72 [1.800]	18	38	△ 1-146268-9
△	45.31 [1.784]	43.18 [1.700]	17	36	6-146268-8	△	45.31 [1.784]	43.18 [1.700]	17	36	△ 1-146268-8
△	42.77 [1.684]	40.64 [1.600]	16	34	6-146268-7	△	42.77 [1.684]	40.64 [1.600]	16	34	△ 1-146268-7
△	40.23 [1.584]	38.10 [1.500]	15	32	6-146268-6	△	40.23 [1.584]	38.10 [1.500]	15	32	△ 1-146268-6
△	37.69 [1.484]	35.56 [1.400]	14	30	6-146268-5	△	37.69 [1.484]	35.56 [1.400]	14	30	△ 1-146268-5
△	35.15 [1.384]	33.02 [1.300]	13	28	6-146268-4	△	35.15 [1.384]	33.02 [1.300]	13	28	△ 1-146268-4
△	32.61 [1.284]	30.48 [1.200]	12	26	6-146268-3	△	32.61 [1.284]	30.48 [1.200]	12	26	△ 1-146268-3
△	30.07 [1.184]	27.94 [1.100]	11	24	6-146268-2	△	30.07 [1.184]	27.94 [1.100]	11	24	△ 1-146268-2
△	27.53 [1.084]	25.40 [1.000]	10	22	6-146268-1	△	27.53 [1.084]	25.40 [1.000]	10	22	△ 1-146268-1
△	24.99 [.984]	22.86 [.900]	9	20	6-146268-0	△	24.99 [.984]	22.86 [.900]	9	20	△ 1-146268-0
△	22.45 [.884]	20.32 [.800]	8	18	5-146268-9	△	22.45 [.884]	20.32 [.800]	8	18	△ 1-146268-9
△	19.91 [.784]	17.78 [.700]	7	16	5-146268-8	△	19.91 [.784]	17.78 [.700]	7	16	△ 1-146268-8
△	17.37 [.684]	15.24 [.600]	6	14	5-146268-7	△	17.37 [.684]	15.24 [.600]	6	14	△ 1-146268-7
△	14.83 [.584]	12.70 [.500]	5	12	5-146268-6	△	14.83 [.584]	12.70 [.500]	5	12	△ 1-146268-6
△	12.29 [.484]	10.16 [.400]	4	10	5-146268-5	△	12.29 [.484]	10.16 [.400]	4	10	△ 1-146268-5
△	9.75 [.384]	7.62 [.300]	3	8	5-146268-4	△	9.75 [.384]	7.62 [.300]	3	8	146268-4
△	7.21 [.284]	5.08 [.200]	2	6	5-146268-3	△	7.21 [.284]	5.08 [.200]	2	6	146268-3
△	4.67 [.184]	2.54 [.100]	1	4	5-146268-2	△	4.67 [.184]	2.54 [.100]	1	4	△ 146268-2
△	2.13 [.084]	- [-]	-	2	5-146268-1	△	2.13 [.084]	- [-]	-	2	△ 146268-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN T. HOFFMAN DBMAY95	STE TE Connectivity
0 PLC ± -	1 PLC ± -	CHK G. DUBNICZKI 04MAR96	NAME
2 PLC ± 0.51[.02]	3 PLC ± 0.127[.005]	APVO G. DUBNICZKI 04MAR96	HEADER ASSEMBLY, MOD II , BREAKAWAY, DOUBLE ROW, .100 X 100 CL , VERTICAL, WITH RETENTION FEATURE, .025 SQ.POSTS, HIGH TEMPERATURE
4 PLC ± 0.0127[.0005]	ANGLES ± -	PRODUCT SPEC	APPLICATION SPEC
MATERIAL	FINISH	WEIGHT	SIZE CASE CODE DRAWING NO RESTRICTED TO
SEE TABLE	SEE TABLE	A1 00779	146268
CUSTOMER DRAWING	SCALE 4:1	SHEET 1 of 1	REV H

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)  
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)  
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)  
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)