



RECOMMENDED PC BOARD MOUNTING DIMENSIONS FOR .063[1.60] THICK PC BOARD AND .012[.305] STENCIL THICK

			101.19 [3.984]	99.06 [3.900]	39	80	4-146269-0
8	OBSOLETE	6	98.65 [3.884]	96.52 [3.800]	38	78	3-146269-9
8	OBSOLETE	6	96.11 [3.784]	93.98 [3.700]	37	76	3-146269-8
8	OBSOLETE	6	93.57 [3.684]	91.44 [3.600]	36	74	3-146269-7
8	OBSOLETE	6	91.03 [3.584]	88.90 [3.500]	35	72	3-146269-6
8	OBSOLETE	6	88.49 [3.484]	86.36 [3.400]	34	70	3-146269-5
8	OBSOLETE	6	85.95 [3.384]	83.82 [3.300]	33	68	3-146269-4
8	OBSOLETE	6	83.41 [3.284]	81.28 [3.200]	32	66	3-146269-3
8	OBSOLETE	6	80.87 [3.184]	78.74 [3.100]	31	64	3-146269-2
8	OBSOLETE	6	78.33 [3.084]	76.20 [3.000]	30	62	3-146269-1
8	OBSOLETE	6	75.79 [2.984]	73.66 [2.900]	29	60	3-146269-0
8	OBSOLETE	6	73.25 [2.884]	71.12 [2.800]	28	58	2-146269-9
8	OBSOLETE	6	70.71 [2.784]	68.58 [2.700]	27	56	2-146269-8
8	OBSOLETE	6	68.17 [2.684]	66.04 [2.600]	26	54	2-146269-7
8	OBSOLETE	6	65.63 [2.584]	63.5 [2.500]	25	52	2-146269-6
8	OBSOLETE	6	63.09 [2.484]	60.96 [2.400]	24	50	2-146269-5
8	OBSOLETE	6	60.55 [2.384]	58.42 [2.300]	23	48	2-146269-4
8	OBSOLETE	6	58.01 [2.284]	55.88 [2.200]	22	46	2-146269-3
8	OBSOLETE	6	55.47 [2.184]	53.34 [2.100]	21	44	2-146269-2
8	OBSOLETE	6	52.93 [2.084]	50.80 [2.000]	20	42	2-146269-1
8	OBSOLETE	6	50.39 [1.984]	48.26 [1.900]	19	40	2-146269-0
8	OBSOLETE	6	47.85 [1.884]	45.72 [1.800]	18	38	1-146269-9
8	OBSOLETE	6	45.31 [1.784]	43.18 [1.700]	17	36	1-146269-8
8	OBSOLETE	6	42.77 [1.684]	40.64 [1.600]	16	34	1-146269-7
8	OBSOLETE	6	40.23 [1.584]	38.10 [1.500]	15	32	1-146269-6
8	OBSOLETE	6	37.69 [1.484]	35.56 [1.400]	14	30	1-146269-5
8	OBSOLETE	6	35.15 [1.384]	33.02 [1.300]	13	28	1-146269-4
8	OBSOLETE	6	32.61 [1.284]	30.48 [1.200]	12	26	1-146269-3
8	OBSOLETE	6	30.07 [1.184]	27.94 [1.100]	11	24	1-146269-2
8	OBSOLETE	6	27.53 [1.084]	25.40 [1.000]	10	22	1-146269-1
8	OBSOLETE	6	24.99 [0.984]	22.86 [0.900]	9	20	1-146269-0
8	OBSOLETE	6	22.45 [0.884]	20.32 [0.800]	8	18	146269-9
8	OBSOLETE	6	19.91 [0.784]	17.78 [0.700]	7	16	146269-8
8	OBSOLETE	6	17.37 [0.684]	15.24 [0.600]	6	14	146269-7
8	OBSOLETE	6	14.83 [0.584]	12.70 [0.500]	5	12	146269-6
8	OBSOLETE	6	12.29 [0.484]	10.16 [0.400]	4	10	146269-5
8	OBSOLETE	6	9.75 [0.384]	7.62 [0.300]	3	8	146269-4
8	OBSOLETE	6	7.21 [0.284]	5.08 [0.200]	2	6	146269-3
8	OBSOLETE	6	4.67 [0.184]	2.54 [0.100]	1	4	146269-2
8	SUPSD BY 5-146269-1	6	2.13 [0.084]	[ - ]	-	2	146269-1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN T. HOFFMAN DBMAY95	 TE Connectivity	
DIMENSIONS: mm [INCHES]		CHK G. DUBNICZKI 04MAR96		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD G. DUBNICZKI 04MAR96	NAME: HEADER ASSEMBLY, MOD II, BREAKAWAY, DOUBLE ROW, .100 X.100 CL, VERTICAL, WITH RETENTION FEATURE, .025 SQ. POSTS, HIGH TEMPERATURE	
0 PLC ± - 1 PLC ± - 2 PLC ± 0.51[.02] 3 PLC ± 0.127[.005] 4 PLC ± 0.0127[.0005] ANGLES ±		APPLICATION SPEC	RESTRICTED TO	
MATERIAL	FINISH SEE TABLE	WEIGHT	SIZE A1	SCALE 4:1
CUSTOMER DRAWING		DRAWING NO. 00779	REV C	SHEET 1 OF 2

1. TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD.
2. THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING.
3. RETENTION FEATURES ON SOLDER TAILS, LOCATED AT MANUFACTURERS OPTION.
4.  $\text{⌀} 0.51 [0.020]$  FOR KINKED TAILS.
5. HOUSING: LCP, COLOR-BLACK.  
POST: COPPER ALLOY.
6. 0.000762 [0.00030] GOLD IN CONTACT AREA.  
0.00254-0.00508 [0.000100-0.000200] MATTE TIN-LEAD ON SOLDER TAIL,  
ALL OVER 0.00127 [0.00050] NICKEL.
7. 0.000762 [0.00030] GOLD IN CONTACT AREA.  
0.00254-0.00508 [0.000100-0.000200] MATTE TIN ON SOLDER TAIL,  
ALL OVER 0.00127 [0.00050] NICKEL.
8. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

		7	101.19 [3.984]	99.06 [3.900]	39	80	9-146269-0
8	OBSOLETE	7	98.65 [3.884]	96.52 [3.800]	38	78	8-146269-9
8	OBSOLETE	7	96.11 [3.784]	93.98 [3.700]	37	76	8-146269-8
8	OBSOLETE	7	93.57 [3.684]	91.44 [3.600]	36	74	8-146269-7
8	OBSOLETE	7	91.03 [3.584]	88.90 [3.500]	35	72	8-146269-6
8	OBSOLETE	7	88.49 [3.484]	86.36 [3.400]	34	70	8-146269-5
8	OBSOLETE	7	85.95 [3.384]	83.82 [3.300]	33	68	8-146269-4
8	OBSOLETE	7	83.41 [3.284]	81.28 [3.200]	32	66	8-146269-3
8	OBSOLETE	7	80.87 [3.184]	78.74 [3.100]	31	64	8-146269-2
8	OBSOLETE	7	78.33 [3.084]	76.20 [3.000]	30	62	8-146269-1
8	OBSOLETE	7	75.79 [2.984]	73.66 [2.900]	29	60	8-146269-0
8	OBSOLETE	7	73.25 [2.884]	71.12 [2.800]	28	58	7-146269-9
8	OBSOLETE	7	70.71 [2.784]	68.58 [2.700]	27	56	7-146269-8
8	OBSOLETE	7	68.17 [2.684]	66.04 [2.600]	26	54	7-146269-7
8	OBSOLETE	7	65.63 [2.584]	63.5 [2.500]	25	52	7-146269-6
8	OBSOLETE	7	63.09 [2.484]	60.96 [2.400]	24	50	7-146269-5
8	OBSOLETE	7	60.55 [2.384]	58.42 [2.300]	23	48	7-146269-4
8	OBSOLETE	7	58.01 [2.284]	55.88 [2.200]	22	46	7-146269-3
8	OBSOLETE	7	55.47 [2.184]	53.34 [2.100]	21	44	7-146269-2
8	OBSOLETE	7	52.93 [2.084]	50.80 [2.000]	20	42	7-146269-1
		7	50.39 [1.984]	48.26 [1.900]	19	40	7-146269-0
8	OBSOLETE	7	47.85 [1.884]	45.72 [1.800]	18	38	6-146269-9
8	OBSOLETE	7	45.31 [1.784]	43.18 [1.700]	17	36	6-146269-8
8	OBSOLETE	7	42.77 [1.684]	40.64 [1.600]	16	34	6-146269-7
8	OBSOLETE	7	40.23 [1.584]	38.10 [1.500]	15	32	6-146269-6
		7	37.69 [1.484]	35.56 [1.400]	14	30	6-146269-5
8	OBSOLETE	7	35.15 [1.384]	33.02 [1.300]	13	28	6-146269-4
8	OBSOLETE	7	32.61 [1.284]	30.48 [1.200]	12	26	6-146269-3
8	OBSOLETE	7	30.07 [1.184]	27.94 [1.100]	11	24	6-146269-2
8	OBSOLETE	7	27.53 [1.084]	25.40 [1.000]	10	22	6-146269-1
		7	24.99 [0.984]	22.86 [0.900]	9	20	6-146269-0
8	OBSOLETE	7	22.45 [0.884]	20.32 [0.800]	8	18	5-146269-9
		7	19.91 [0.784]	17.78 [0.700]	7	16	5-146269-8
		7	17.37 [0.684]	15.24 [0.600]	6	14	5-146269-7
		7	14.83 [0.584]	12.70 [0.500]	5	12	5-146269-6
		7	12.29 [0.484]	10.16 [0.400]	4	10	5-146269-5
		7	9.75 [0.384]	7.62 [0.300]	3	8	5-146269-4
		7	7.21 [0.284]	5.08 [0.200]	2	6	5-146269-3
8	OBSOLETE	7	4.67 [0.184]	2.54 [0.100]	1	4	5-146269-2
		7	2.13 [0.084]	-	-	2	5-146269-1
			FINISH	C B A		NO. OF POSITIONS	LEAD FREE PART NO.S

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN T. HOFFMAN DBMAY95		TE Connectivity	
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:			
0. PLC ± - 1. PLC ± - 2. PLC ± 0.51[0.02] 3. PLC ± 0.127[0.005] 4. PLC ± 0.0127[0.0005] ANGLES ±		CJK G. DUBNICZKI 04MAR96 APVO G. DUBNICZKI 04MAR96 PRODUCT SPEC		NAME: HEADER ASSEMBLY, MOD II, BREAKAWAY, DOUBLE ROW, .100 X.100 CL, VERTICAL, WITH RETENTION FEATURE, .025 SQ. POSTS, HIGH TEMPERATURE APPLICATION SPEC	
MATERIAL 5		FINISH SEE TABLE		SIZE: A1 WEIGHT: - CUSTOMER DRAWING	
				DRAWING NO: 00779 SCALE: 1:1 SHEET 2 OF 2 REV H	

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)  
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)  
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)  
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)