



RECOMENDED PC BOARD MOUNTING DIMENSIONS FOR .063 [1.60] THICK PC BOARD AND .012 [.305] STENCIL THICK.

PLATING	C	B	A	NO. OF POSITIONS	PART NUMBER
6	101.19 [3.984]	99.06 [3.900]	39	40	9-146277-0
6	98.65 [3.884]	96.52 [3.800]	38	39	8-146277-9
6	96.11 [3.784]	93.98 [3.700]	37	38	8-146277-8
6	93.57 [3.684]	91.44 [3.600]	36	37	8-146277-7
6	91.03 [3.584]	88.90 [3.500]	35	36	8-146277-6
6	88.49 [3.484]	86.36 [3.400]	34	35	8-146277-5
6	85.95 [3.384]	83.82 [3.300]	33	34	8-146277-4
6	83.41 [3.284]	81.28 [3.200]	32	33	8-146277-3
6	80.87 [3.184]	78.74 [3.100]	31	32	8-146277-2
6	78.33 [3.084]	76.20 [3.000]	30	31	8-146277-1
6	75.79 [2.984]	73.66 [2.900]	29	30	8-146277-0
6	73.25 [2.884]	71.12 [2.800]	28	29	7-146277-9
6	70.71 [2.784]	68.58 [2.700]	27	28	7-146277-8
6	68.17 [2.684]	66.04 [2.600]	26	27	7-146277-7
6	65.63 [2.584]	63.5 [2.500]	25	26	7-146277-6
6	63.09 [2.484]	60.96 [2.400]	24	25	7-146277-5
6	60.55 [2.384]	58.42 [2.300]	23	24	7-146277-4
6	58.01 [2.284]	55.88 [2.200]	22	23	7-146277-3
6	55.47 [2.184]	53.34 [2.100]	21	22	7-146277-2
7	OBSOLETE	52.93 [2.084]	20	21	7-146277-1
6	50.39 [1.984]	48.26 [1.900]	19	20	7-146277-0
7	OBSOLETE	47.85 [1.884]	18	19	6-146277-9
6	45.31 [1.784]	43.18 [1.700]	17	18	6-146277-8
7	OBSOLETE	42.77 [1.684]	16	17	6-146277-7
6	40.23 [1.584]	38.10 [1.500]	15	16	6-146277-6
7	OBSOLETE	37.69 [1.484]	14	15	6-146277-5
6	35.15 [1.384]	33.02 [1.300]	13	14	6-146277-4
7	OBSOLETE	32.61 [1.284]	12	13	6-146277-3
6	30.07 [1.184]	27.94 [1.100]	11	12	6-146277-2
7	OBSOLETE	27.53 [1.084]	10	11	6-146277-1
6	24.99 [.984]	22.86 [.900]	9	10	6-146277-0
7	OBSOLETE	22.45 [.884]	8	9	5-146277-9
6	19.91 [.784]	17.78 [.700]	7	8	5-146277-8
6	17.37 [.684]	15.24 [.600]	6	7	5-146277-7
6	14.83 [.584]	12.70 [.500]	5	6	5-146277-6
6	12.29 [.484]	10.16 [.400]	4	5	5-146277-5
6	9.75 [.384]	7.62 [.300]	3	4	5-146277-4
6	7.21 [.284]	5.08 [.200]	2	3	5-146277-3
6	4.67 [.184]	2.54 [.100]	1	2	5-146277-2
6	2.13 [.084]	- [-]	0	1	5-146277-1
PLATING	C	B	A	NO. OF POSITIONS	PART NUMBER

PLATING	C	B	A	NO. OF POSITIONS	PART NUMBER
5	101.19 [3.984]	99.06 [3.900]	39	40	4-146277-0
5	98.65 [3.884]	96.52 [3.800]	38	39	3-146277-9
5	96.11 [3.784]	93.98 [3.700]	37	38	3-146277-8
5	93.57 [3.684]	91.44 [3.600]	36	37	3-146277-7
5	91.03 [3.584]	88.90 [3.500]	35	36	3-146277-6
5	88.49 [3.484]	86.36 [3.400]	34	35	3-146277-5
5	85.95 [3.384]	83.82 [3.300]	33	34	3-146277-4
5	83.41 [3.284]	81.28 [3.200]	32	33	3-146277-3
5	80.87 [3.184]	78.74 [3.100]	31	32	3-146277-2
5	78.33 [3.084]	76.20 [3.000]	30	31	3-146277-1
5	75.79 [2.984]	73.66 [2.900]	29	30	3-146277-0
5	73.25 [2.884]	71.12 [2.800]	28	29	2-146277-9
5	70.71 [2.784]	68.58 [2.700]	27	28	2-146277-8
5	68.17 [2.684]	66.04 [2.600]	26	27	2-146277-7
5	65.63 [2.584]	63.5 [2.500]	25	26	2-146277-6
5	63.09 [2.484]	60.96 [2.400]	24	25	2-146277-5
5	60.55 [2.384]	58.42 [2.300]	23	24	2-146277-4
5	58.01 [2.284]	55.88 [2.200]	22	23	2-146277-3
5	55.47 [2.184]	53.34 [2.100]	21	22	2-146277-2
7	SUP BY 7-146277-2	52.93 [2.084]	20	21	2-146277-1
7	OBSOLETE	50.39 [1.984]	19	20	2-146277-0
7	SUP BY 7-146277-0	47.85 [1.884]	18	19	1-146277-9
7	OBSOLETE	45.31 [1.784]	17	18	1-146277-8
7	OBSOLETE	42.77 [1.684]	16	17	1-146277-7
7	SUP BY 6-146277-6	40.23 [1.584]	15	16	1-146277-6
7	OBSOLETE	37.69 [1.484]	14	15	1-146277-5
7	SUP BY 6-146277-4	35.15 [1.384]	13	14	1-146277-4
7	OBSOLETE	32.61 [1.284]	12	13	1-146277-3
7	SUP BY 6-146277-2	30.07 [1.184]	11	12	1-146277-2
7	OBSOLETE	27.53 [1.084]	10	11	1-146277-1
7	SUP BY 6-146277-0	24.99 [.984]	9	10	1-146277-0
7	OBSOLETE	22.45 [.884]	8	9	146277-9
7	SUP BY 5-146277-8	19.91 [.784]	7	8	146277-8
7	SUP BY 5-146277-7	17.37 [.684]	6	7	146277-7
7	SUP BY 5-146277-6	14.83 [.584]	5	6	146277-6
7	SUP BY 5-146277-5	12.29 [.484]	4	5	146277-5
7	SUP BY 5-146277-4	9.75 [.384]	3	4	146277-4
7	SUP BY 5-146277-3	7.21 [.284]	2	3	146277-3
7	SUP BY 5-146277-2	4.67 [.184]	1	2	146277-2
7	SUP BY 5-146277-1	2.13 [.084]	0	1	146277-1
PLATING	C	B	A	NO. OF POSITIONS	PART NUMBER

- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
- TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- MATERIAL: HOUSING - LCP, COLOR: BLACK.  
POSTS - COPPER ALLOY.
- 0.00076 [.000030] GOLD IN CONTACT AREA,  
0.00254-0.00508 [.0000100-.0000200] MATTE TIN-LEAD ON SOLDER TAIL,  
ALL OVER 0.00127 [.000050] NICKEL.
- 0.00076 [.000030] GOLD IN CONTACT AREA,  
0.00254-0.00508 [.0000100-.0000200] MATTE TIN ON SOLDER TAIL,  
ALL OVER 0.00127 [.000050] NICKEL.
- OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN T. HOFFMAN 6/20/95	TE Connectivity
0 PLC ± -	1 PLC ± .01	CHK G. DUBNICZKI 1/5/96	NAME
2 PLC ± 0.51 [.02]	3 PLC ± 0.127 [.005]	APVO G. DUBNICZKI 1/5/96	PRODUCT SPEC
4 PLC ± 0.0127 [.0005]	ANGLES ± -	APPLICATION SPEC	SIZE CASE CODE DRAWING NO
MATERIAL 4	FINISH SEE TABLE	WEIGHT -	A1 00779 C=146277
		CUSTOMER DRAWING	SCALE 4:1 SHEET 1 of 1 REV H

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)  
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)  
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)  
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)