



RECOMMENDED PC BOARD MOUNTING DIMENSIONS FOR .063 [1.60] THICK PC BOARD AND .012 [0.305] STENCIL THICK.

- 1 THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING.
- 2 BREAKAWAY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
- 3 0.000762 [0.000030] GOLD ON CONTACT AREA, 0.00254-0.00508 [0.000100-0.000200] MATTE TIN-LEAD ON SOLDER TAIL, ALL OVER 0.00127 [0.000050] NICKEL.
- 4 HOUSING: GLASS FILLED THERMOPLASTIC, COLOR - BLACK. (WILL WITHSTAND VAPOR PHASE REFLOW.) POST: COPPER ALLOY
- 5 0.000762 [0.000030] GOLD ON CONTACT AREA, 0.00254-0.00508 [0.000100-0.000200] MATTE TIN ON SOLDER TAIL, ALL OVER 0.00127 [0.000050] NICKEL.
- 6 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

| PLATING | C | B | A | NO. OF POSITIONS | PART NUMBER | PLATING | C | B | A | NO. OF POSITIONS | PART NUMBER |
|---------|--------|-------|----|------------------|-------------|---------|--------|-------|----|------------------|-------------|
| 5 | 101.19 | 99.06 | 39 | 80 | 9-146309-0 | 3 | 101.19 | 99.06 | 39 | 80 | 4-146309-0 |
| 5 | 98.65 | 96.52 | 38 | 78 | 8-146309-9 | 3 | 98.65 | 96.52 | 38 | 78 | 3-146309-9 |
| 5 | 96.11 | 93.98 | 37 | 76 | 8-146309-8 | 3 | 96.11 | 93.98 | 37 | 76 | 3-146309-8 |
| 5 | 93.57 | 91.44 | 36 | 74 | 8-146309-7 | 3 | 93.57 | 91.44 | 36 | 74 | 3-146309-7 |
| 5 | 91.03 | 88.90 | 35 | 72 | 8-146309-6 | 3 | 91.03 | 88.90 | 35 | 72 | 3-146309-6 |
| 5 | 88.49 | 86.36 | 34 | 70 | 8-146309-5 | 3 | 88.49 | 86.36 | 34 | 70 | 3-146309-5 |
| 5 | 85.95 | 83.82 | 33 | 68 | 8-146309-4 | 3 | 85.95 | 83.82 | 33 | 68 | 3-146309-4 |
| 5 | 83.41 | 81.28 | 32 | 66 | 8-146309-3 | 3 | 83.41 | 81.28 | 32 | 66 | 3-146309-3 |
| 5 | 80.87 | 78.74 | 31 | 64 | 8-146309-2 | 3 | 80.87 | 78.74 | 31 | 64 | 3-146309-2 |
| 5 | 78.33 | 76.20 | 30 | 62 | 8-146309-1 | 3 | 78.33 | 76.20 | 30 | 62 | 3-146309-1 |
| 5 | 75.79 | 73.66 | 29 | 60 | 8-146309-0 | 3 | 75.79 | 73.66 | 29 | 60 | 3-146309-0 |
| 5 | 73.25 | 71.12 | 28 | 58 | 7-146309-9 | 3 | 73.25 | 71.12 | 28 | 58 | 2-146309-9 |
| 5 | 70.71 | 68.58 | 27 | 56 | 7-146309-8 | 3 | 70.71 | 68.58 | 27 | 56 | 2-146309-8 |
| 5 | 68.17 | 66.04 | 26 | 54 | 7-146309-7 | 3 | 68.17 | 66.04 | 26 | 54 | 2-146309-7 |
| 5 | 65.63 | 63.5 | 25 | 52 | 7-146309-6 | 3 | 65.63 | 63.5 | 25 | 52 | 2-146309-6 |
| 5 | 63.09 | 60.96 | 24 | 50 | 7-146309-5 | 3 | 63.09 | 60.96 | 24 | 50 | 2-146309-5 |
| 5 | 60.55 | 58.42 | 23 | 48 | 7-146309-4 | 3 | 60.55 | 58.42 | 23 | 48 | 2-146309-4 |
| 5 | 58.01 | 55.88 | 22 | 46 | 7-146309-3 | 3 | 58.01 | 55.88 | 22 | 46 | 2-146309-3 |
| 5 | 55.47 | 53.34 | 21 | 44 | 7-146309-2 | 3 | 55.47 | 53.34 | 21 | 44 | 2-146309-2 |
| 5 | 52.93 | 50.80 | 20 | 42 | 7-146309-1 | 3 | 52.93 | 50.80 | 20 | 42 | 2-146309-1 |
| 5 | 50.39 | 48.26 | 19 | 40 | 7-146309-0 | 3 | 50.39 | 48.26 | 19 | 40 | 2-146309-0 |
| 5 | 47.85 | 45.72 | 18 | 38 | 6-146309-9 | 3 | 47.85 | 45.72 | 18 | 38 | 1-146309-9 |
| 5 | 45.31 | 43.18 | 17 | 36 | 6-146309-8 | 3 | 45.31 | 43.18 | 17 | 36 | 1-146309-8 |
| 5 | 42.77 | 40.64 | 16 | 34 | 6-146309-7 | 3 | 42.77 | 40.64 | 16 | 34 | 1-146309-7 |
| 5 | 40.23 | 38.10 | 15 | 32 | 6-146309-6 | 3 | 40.23 | 38.10 | 15 | 32 | 1-146309-6 |
| 5 | 37.69 | 35.56 | 14 | 30 | 6-146309-5 | 3 | 37.69 | 35.56 | 14 | 30 | 1-146309-5 |
| 5 | 35.15 | 33.02 | 13 | 28 | 6-146309-4 | 3 | 35.15 | 33.02 | 13 | 28 | 1-146309-4 |
| 5 | 32.61 | 30.48 | 12 | 26 | 6-146309-3 | 3 | 32.61 | 30.48 | 12 | 26 | 1-146309-3 |
| 5 | 30.07 | 27.94 | 11 | 24 | 6-146309-2 | 3 | 30.07 | 27.94 | 11 | 24 | 1-146309-2 |
| 5 | 27.53 | 25.40 | 10 | 22 | 6-146309-1 | 3 | 27.53 | 25.40 | 10 | 22 | 1-146309-1 |
| 6 | 24.99 | 22.86 | 9 | 20 | 6-146309-0 | 3 | 24.99 | 22.86 | 9 | 20 | 1-146309-0 |
| 6 | 22.45 | 20.32 | 8 | 18 | 5-146309-9 | 3 | 22.45 | 20.32 | 8 | 18 | 1-146309-9 |
| 6 | 19.91 | 17.78 | 7 | 16 | 5-146309-8 | 3 | 19.91 | 17.78 | 7 | 16 | 1-146309-8 |
| 6 | 17.37 | 15.24 | 6 | 14 | 5-146309-7 | 3 | 17.37 | 15.24 | 6 | 14 | 1-146309-7 |
| 6 | 14.83 | 12.70 | 5 | 12 | 5-146309-6 | 3 | 14.83 | 12.70 | 5 | 12 | 1-146309-6 |
| 6 | 12.29 | 10.16 | 4 | 10 | 5-146309-5 | 3 | 12.29 | 10.16 | 4 | 10 | 1-146309-5 |
| 6 | 9.75 | 7.62 | 3 | 8 | 5-146309-4 | 3 | 9.75 | 7.62 | 3 | 8 | 1-146309-4 |
| 6 | 7.21 | 5.08 | 2 | 6 | 5-146309-3 | 3 | 7.21 | 5.08 | 2 | 6 | 1-146309-3 |
| 6 | 4.67 | 2.54 | 1 | 4 | 5-146309-2 | 3 | 4.67 | 2.54 | 1 | 4 | 146309-2 |
| 6 | 2.13 | - | 0 | 2 | 5-146309-1 | 3 | 2.13 | - | 0 | 2 | 146309-1 |

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIN T. HOFFMAN 21-6-95
 CHK G. DUBNICZKI 4-12-95
 APVO G. DUBNICZKI 4-12-95

STE TE Connectivity

NAME: HEADER ASSEMBLY, MOD II, BREAKAWAY, HIGH TEMPERATURE, RIGHT ANGLE, DOUBLE ROW, .100 X .100 C/L, W/.025 SQUARE POSTS

APPLICATION SPEC: -
 SIZE: A1
 WEIGHT: -
 CUSTOMER DRAWING: 00779

SCALE: 4:1 SHEET 1 OF 1 REV B

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)