



RECOMMENDED P.C. BOARD HOLE LAYOUT

- ① "AMP", "CSA", "▼", AND "DATE CODE" WITH .062±.015 HIGH CHARACTERS WHERE SIZE PERMITS.
- ② HOUSING: 1-70 POSITION SIZES MAY BE PPS, GLASS-FILLED OR PCT, GLASS-FILLED. POSITION SIZES GREATER THAN 70 WILL BE PPS, GLASS-FILLED.
- ③ CONTACT: PHOSPHOR BRONZE.
- ④ CONTACT FINISH: DUPLEX PLATED 0.00076 [.000030] GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] BRIGHT TIN-LEAD ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
- ⑤ THESE DIMENSIONS PERTAIN TO CAVITY C'S ONLY, NOT TO CONTACT LOCATIONS.
- ⑥ POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE CONTACT BEAMS).
- ⑦ CSA LOGO INK STAMPED WHITE ON HOUSING.
- ⑧ PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
- ⑨ CONTACT FINISH: DUPLEX PLATED 0.00076 [.000030] GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] MATTE TIN ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
- ⑩ ROHS 2002/95/EC COMPLIANT.
- ⑪ RECESSED AREA AROUND MOLD GATE IS OPTIONAL. THIS FEATURE IS ALLOWABLE ON EITHER SIDE OF HOUSING OR MAY NOT BE PRESENT AT ALL.
- ⑫ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

FINISH	B	A	NO OF POSN	PART NUMBER	FINISH	B	A	NO OF POSN	PART NUMBER
			10	8-532956-0	OBSOLETE			10	3-532956-0
			12	7-532956-9	OBSOLETE			12	2-532956-9
			21	7-532956-8	OBSOLETE			21	2-532956-8
			79	7-532956-7	OBSOLETE				2-532956-7
			6	7-532956-6	OBSOLETE				2-532956-6
			6	7-532956-5	OBSOLETE				2-532956-5
			89	7-532956-4	OBSOLETE			89	2-532956-4
			99	7-532956-3	OBSOLETE			99	2-532956-3
			73	7-532956-2	OBSOLETE			73	2-532956-2
			69	7-532956-1	OBSOLETE			69	2-532956-1
			64	7-532956-0	OBSOLETE			64	2-532956-0
			63	6-532956-9	OBSOLETE			63	1-532956-9
			59	6-532956-8	OBSOLETE			59	1-532956-8
			54	6-532956-7	OBSOLETE			54	1-532956-7
			49	6-532956-6	OBSOLETE			49	1-532956-6
			47	6-532956-5	OBSOLETE			47	1-532956-5
			44	6-532956-4	OBSOLETE			44	1-532956-4
			42	6-532956-3	OBSOLETE			42	1-532956-3
			39	6-532956-2	OBSOLETE			39	1-532956-2
			35	6-532956-1	OBSOLETE			35	1-532956-1
			34	6-532956-0	OBSOLETE			34	1-532956-0
			29	5-532956-9	SUPERSEDED BY 6-532956-0			29	532956-9
			24	5-532956-8				24	532956-8
			19	5-532956-7				19	532956-7
			17	5-532956-6				17	532956-6
			14	5-532956-5				14	532956-5
			11	5-532956-4				11	532956-4
			9	5-532956-3				9	532956-3
			7	5-532956-2				7	532956-2
			5	5-532956-1				5	532956-1

THIS DRAWING IS A CONTROLLED DOCUMENT. 17JAN01
K.L.CLOUSER/UTA
05/14/91

DIMENSIONS: mm [INCHES] TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± 0.13 [.005]
3 PLC ± -
4 PLC ± -
ANGLES ± -

MATERIAL HOUSING: ② FINISH SEE TABLE

CONTACT: ③ WEIGHT -

STE TE Connectivity

NAME: RECEPTACLE ASSY, MOD II, DBL ROW, 2.54 X 2.54 [.100 X .100] CL, GUIDE PIN EARS, CLOSED ENTRY, SHORT-POINT-OF-CONTACT

SIZE: A1 CAGE CODE: 00779 **C** DRAWING NO: 532956

CUSTOMER DRAWING SCALE: 6:1 SHEET 1 OF 1 REV: AF3

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[589158040000018](#) [MDF7C-18P-2.54DSA\(55\)](#) [FCN-230C068-11](#) [FCN-268F012-G/BD](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [FX4C-80S-1.27DSA](#) [FCN-214Q030-G/0](#) [FCN-234P048-G/0](#) [FCN-235D050-G/C](#) [210-93-314-41-105000](#) [2-22603-0](#) [MDF7-40DP-2.54DSA\(55\)](#) [AXG720047](#) [5031084030](#) [MIT-114-03-F-D-K](#) [55323-1519](#) [DF33-2P-3.3DSA\(24\)](#) [YFT-20-05-H-03-SB-K](#) [503308-3040](#) [026-6203-PDB](#) [027-6203-PDB](#) [069159702701000](#) [10123981-102LF](#) [101A10019X](#) [55650-0588-C](#) [68682-310LF](#) [68684-306](#) [75140-7012](#) [87471-650](#) [194261-1](#) [FCN-268F024-G0D](#) [10124054-515LF](#) [68685-603](#) [8-1616154-3](#) [MIS-019-01-F-D](#) [FCN-268M024-G/3D](#) [20021832-06016C1LF](#) [KX15-20KLDL-E1000E](#) [MDF7-16DP-2.54DSA\(55\)](#) [AXE810124](#) [FCN-214J100-G/0](#) [FCN-230C068-E/S](#) [AXE812124](#) [AXE816124](#) [AXE720127](#)