

SPECIFICATION CONTROL DRAWING

55PC0211

TITLE WIRE, RADIATION-CROSSLINKED, MODIFIED, ETFE-INSULATED, GENERAL PURPOSE, LIGHT AIRFRAME Date 07-08-04 Revision H

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.



CONSTRUCTION DETAILS

| PART NUMBER 1/ | WIRE SIZE (AWG) | CONDUCTOR STRANDING (number x AWG) | CONDUCTOR DIAMETER (in.) | | | MAXIMUM RESISTANCE AT 20°C (ohms/1000 ft.) | FINISHED WIRE | | | WEIGHT (lbs/1000 ft.) | |
|-------------------|--------------------|---------------------------------------|-------------------------------|--------------|------------------|--|---------------------|--------------|------------------|----------------------------|------------------|
| | | | LOWER SPEC LIMIT | TARGET VALUE | UPPER SPEC LIMIT | | DIAMETER (in.) | | | TARGET VALUE | UPPER SPEC LIMIT |
| | | | | | | | LOWER SPEC LIMIT | TARGET VALUE | UPPER SPEC LIMIT | | |
| 55PC0211-26-* | 26 | 19 x 38 | .0175 | .0183 | .0191 | 41.3 | .0328 | .0345 | .0362 | 1.38 | 1.52 |
| 55PC0211-24-* | 24 | 19 x 36 | .0225 | .0233 | .0241 | 26.2 | .0378 | .0395 | .0412 | 1.98 | 2.13 |
| 55PC0211-22-* | 22 | 19 x 34 | .0285 | .0293 | .0301 | 16.2 | .0438 | .0455 | .0472 | 2.90 | 3.06 |
| 55PC0211-20-* | 20 | 19 x 32 | .0365 | .0375 | .0385 | 9.88 | .0523 | .0540 | .0557 | 4.38 | 4.57 |
| 55PC0211-18-* | 18 | 19 x 30 | .0452 | .0464 | .0476 | 6.23 | .0616 | .0635 | .0654 | 6.59 | 6.90 |
| 55PC0211-16-* | 16 | 19 x 29 | .0514 | .0527 | .0538 | 4.81 | .0690 | .0710 | .0730 | 8.37 | 8.70 |
| 55PC0211-14-* | 14 | 19 x 27 | .0644 | .0659 | .0674 | 3.06 | .0838 | .0860 | .0882 | 12.88 | 13.33 |
| 55PC0211-12-* | 12 | 37 x 28 | .0825 | .0845 | .0865 | 2.02 | .1020 | .1047 | .1074 | 19.73 | 20.30 |
| 55PC0211-10-* | 10 | 37 x 26 | .1050 | .1070 | .1090 | 1.26 | .1252 | .1290 | .1328 | 31.12 | 32.13 |
| 55PC0211- 8-* | 8 | 133 x 29 | .158 | .163 | .169 | .701 | .188 | .196 | .203 | 56.8 | 59.9 |
| 55PC0211- 6-* | 6 | 133 x 27 | .198 | .205 | .212 | .445 | .233 | .242 | .251 | 89.7 | 94.7 |
| 55PC0211- 4-* | 4 | 133 x 25 | .250 | .260 | .268 | .280 | .300 | .311 | .322 | 145. | 154. |
| 55PC0211- 2-* | 2 | 665 x 30 | .320 | .330 | .340 | .183 | .370 | .383 | .397 | 227. | 240. |
| 55PC0211- 1-* | 1 | 817 x 30 | .360 | .370 | .380 | .152 | .410 | .424 | .438 | 278. | 291. |
| 55PC0211- 0-* | 0 | 1045 x 30 | .395 | .415 | .425 | .116 | .449 | .466 | .483 | 343. | 366. |
| 55PC0211-00-* | 00 | 1330 x 30 | .440 | .462 | .475 | .091 | .505 | .525 | .545 | 450. | 481. |

WIRE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 150°C
 Maximum continuous conductor temperature
 VOLTAGE RATING: 600 volts (rms) at sea level
 COLOR: White preferred
 CROSSLINK VERIFICATION: 300 ± 3°C for 1 hour
 IDENTIFICATION AND COLOR STRIPING DURABILITY:
 125 cycles (250 strokes) (minimum), 500 g weight

INSULATION ELONGATION AND TENSILE STRENGTH:
 Total Insulation,
 Elongation, 50% (minimum)
 Tensile Strength, 5000 lbf/in² (minimum)
 INSULATION FLAWS:
 Spark Test, 3.0 kV (rms)
 Impulse Dielectric Test, 8.0 kV (peak)
 INSULATION THICKNESS: .008 in. (nominal) total insulation

SHRINKAGE: 230 ± 3°C for 1 hour, 0.125 in. (maximum) in 12 in.
 VOLTAGE WITHSTAND TEST (Post Environmental):
 2500 volts (rms)
 PART NUMBER:
 The "*" in the part numbers above shall be replaced by color code designators.
 1/ Example: AWG 22, white: 55PC0211-22-9
 AWG 22, white with black stripe: 55PC0211-22-90

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.

DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.



Raychem Wire & Cable
 501 Oakside Avenue
 Redwood City, CA 94063-3800
 Phone: 1-800-227-8816
 Fax: 1-650-361-6297

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Conductor Cables](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[89504-002-1000](#) [89705-008-500](#) [6000FE-877-1000](#) [CS2885-000](#) [M27500-20SP2S23](#) [6309UE-877-1000](#) [M3905-BK005](#) [6502FE 8771000](#)
[CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#)
[CXA-0140-16-6/9-9CS2405](#) [CY0660-000](#) [720451-000](#) [752687-000](#) [768146-000](#) [773159-000](#) [83318E-009-500](#) [8348-060-500](#) [83559-002-](#)
[1000](#) [83653-002-5000](#) [8404-060-500](#) [8469 060100](#) [858171-000](#) [8628-060-500](#) [868361-001](#) [8730-060-1000](#) [8737-060-U1000](#) [8747-060-100](#)
[8747-060-1000](#) [8769-060-1000](#) [8775-060-500](#) [8780-060-1000](#) [8782-001-U1000](#) [9159-060-500](#) [9318-060-1000](#) [939870-000](#) [9423 060U500](#)
[9444 060U1000](#) [9497 0001000](#) [9520-060-1000](#) [9524-060-1000](#) [9546-060-500](#) [9572-002-U500](#) [9774-060-1000](#) [A43962-000](#) [1232A1-008-](#)
[1000](#)