



9	OBSOLETE	8	2-104257-4	25	7-103644-4
9	OBSOLETE	8	2-104257-3	24	7-103644-3
9	OBSOLETE	8	2-104257-2	23	7-103644-2
9	OBSOLETE	8	2-104257-1	22	7-103644-1
		8	2-104257-0	21	7-103644-0
9	OBSOLETE	8	1-104257-9	20	6-103644-9
9	OBSOLETE	8	1-104257-8	19	6-103644-8
9	OBSOLETE	8	1-104257-7	18	6-103644-7
9	OBSOLETE	8	1-104257-6	17	6-103644-6
9	OBSOLETE	8	1-104257-5	16	6-103644-5
9	OBSOLETE	8	1-104257-4	15	6-103644-4
		8	1-104257-3	14	6-103644-3
		8	1-104257-2	13	6-103644-2
		7	2-104257-4	25	2-103644-4
9	OBSOLETE	7	2-104257-3	24	2-103644-3
9	OBSOLETE	7	2-104257-2	23	2-103644-2
9	OBSOLETE	7	2-104257-1	22	2-103644-1
9	SUPERSEDED BY 7-103644-0	7	2-104257-0	21	2-103644-0
		7	1-104257-9	20	1-103644-9
9	OBSOLETE	7	1-104257-8	19	1-103644-8
		7	1-104257-7	18	1-103644-7
		7	1-104257-6	17	1-103644-6
		7	1-104257-5	16	1-103644-5
		7	1-104257-4	15	1-103644-4
		7	1-104257-3	14	1-103644-3
		7	1-104257-2	13	1-103644-2
		7	1-104257-1	12	1-103644-1
		7	1-104257-0	11	1-103644-0
		7	104257-9	10	103644-9
		7	104257-8	9	103644-8
		7	104257-7	8	103644-7
		7	104257-6	7	103644-6
		7	104257-5	6	103644-5
		7	104257-4	5	103644-4
		7	104257-3	4	103644-3
		7	104257-2	3	103644-2
		7	104257-1	2	103644-1

- 1 CONTACTS ARE LATCHED INTO THE PRELOAD WINDOWS
- 2 USE WITH #22-#26 AWG WIRE SIZE, .054/.030 INSULATION DIAMETER, .015 MAXIMUM INSULATION THICKNESS
- 3 THE DIMENSION APPLIES WITH THE FORWARD PRELOAD STOP IN CONTACT WITH THE HOUSING SURFACE
- 4 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 5 FOR STRIP ASSEMBLIES SEE PART NUMBER 103957
- 6 POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE BEAMS)
- 7 FINISH: CONTACTS: .000015 GOLD IN THE CONTACT AREA,.000050-.000100 BRIGHT TIN-LEAD ON THE TERMINATION AREA, ALL OVER .000050 NICKEL
- 8 .000015 GOLD IN THE CONTACT AREA,.000050-.000100 MATTE TIN ON THE TERMINATION AREA, ALL OVER .000050 NICKEL
- 9 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

SUPERSEDED BY 1-103957-1	1-104257-1	12	1-103644-1
SUPERSEDED BY 1-103957-0	1-104257-0	11	1-103644-0
SUPERSEDED BY 103957-9	104257-9	10	103644-9
SUPERSEDED BY 103957-8	104257-8	9	103644-8
SUPERSEDED BY 103957-7	104257-7	8	103644-7
SUPERSEDED BY 103957-6	104257-6	7	103644-6
SUPERSEDED BY 103957-5	104257-5	6	103644-5
SUPERSEDED BY 103957-4	104257-4	5	103644-4
SUPERSEDED BY 103957-3	104257-3	4	103644-3
SUPERSEDED BY 103957-2	104257-2	3	103644-2
SUPERSEDED BY 103957-1	104257-1	2	103644-1

PLATING	HOUSING PART NUMBER	NO OF POSN	ASSEMBLY PART NUMBER
---------	---------------------	------------	----------------------

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 11-4-86 L A MAYER	TE Connectivity	
DIMENSIONS: INCHES		CHK 11-12-86 P de Jong		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD -	NAME	
0 PLC ± -		PRODUCT SPEC	RCPT ASSY, AMPMODU MTE, SINGLE ROW,.100 C/L	
1 PLC ± -		APPLICATION SPEC	LATCHED AND POLARIZED,	
2 PLC ± .02		114-25026	FOR NO 22- NO 26 AWG WIRE SIZE	
3 PLC ± .005		114-25026	SIZE	CAGE CODE
4 PLC ± -		WEIGHT -	A2	00779
ANGLES ± -		CUSTOMER DRAWING	DRAWING NO	
FINISH SEE TABLE		SCALE 4:1	RESTRICTED TO	
		SHEET 1 of 1	REV R2	

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)  
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)  
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)  
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)