



- 1 OBSOLETE PART NUMBER
- 2 POST TO WITHSTAND 13 NEWTONS (3 LBS) MINIMUM AXIAL FORCE IN BOTH DIRECTIONS SHOWN WITHOUT DISLODGING.
- 3 TOLERANCES APPLY TO SOLDER SIDE OF BOARD.
- 4 MEASURED AT -A-
- 5 PLASTIC FLASH PERMITTED IN THIS AREA.
- 6 PARTS COMPLY WITH AMP SOLDERABILITY SPEC. NO. 109-11-2.
- 7 ONE HOLE MAY BE UNDERSIZED 0.81-0.89 [.032-.035] DIA. FOR ASSEMBLY RETENTION DURING WAVE SOLDERING.
- 8 MATERIAL: HEADER-THERMOPLASTIC POLYESTER
 94V-0 (NATURAL)
 POST-COPPER ALLOY
 FINISH-USE PLATING NOTES 13 & 14 FOR -2 THRU -28
 AND NOTES 13 & 15 FOR -32 THRU -58
- 9 COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.
- 10 PLASTIC BURRS CAUSED BY CUT-OFF TOOLING ARE PERMITTED WITHIN THE MAXIMUM TOLERANCE ENVELOPE.
- 11 POSTS TO BE MEASURED WHEN STRIP IS HELD FLAT.
- 12 POST MUST WITHSTAND TWO 90° BENDS AGAINST EXTRUSION WITHOUT BREAKING.
- 13 DIMENSION SHOULD BE 2.79-4.06 [.110-.160] MIN WHEN MATING WITH A MTA-100 CONNECTOR ASSEMBLY OR 2.79-3.05 [.110-.120] WHEN MATING WITH A CST-100 CONNECTOR ASSEMBLY.
- 14 PLATING: GOLD PLATE AREA, 0.00038 [.000015] GOLD OR 0.00008 [.000003] MIN GOLD FLASH OVER 0.00030 [.000012] PALLADIUM NICKEL, PER TE CONNECTIVITY'S DISCRETION, ALL SIDES, OVER NICKEL UNDERPLATE, 0.00127 [.000050] MIN, ALL SIDES AND ENTIRE LENGTH OF POST.
- 15 PLATING: MATTE TIN PLATE AREA, 0.00381-0.00889 [.000150-.000350] THICK, ALL FOUR SIDES 3.56 [.140] MINIMUM.
- 16 PLATING: MATTE TIN PLATE AREA, 0.00381-0.00889 [.000150-.000350] THICK, ALL FOUR SIDES 3.56 [.140] MINIMUM.
- 17 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

DIM (L)	NO.OF POSN	ASSEMBLY	DIM (L)	NO.OF POSN	ASSEMBLY
71.12 [2.800]	28	5-641127-8	71.12 [2.800]	28	2-641127-8
68.58 [2.700]	27	5-641127-7	68.58 [2.700]	27	2-641127-7
66.04 [2.600]	26	5-641127-6	66.04 [2.600]	26	2-641127-6
63.50 [2.500]	25	5-641127-5	63.50 [2.500]	25	2-641127-5
60.96 [2.400]	24	5-641127-4	60.96 [2.400]	24	2-641127-4
58.42 [2.300]	23	5-641127-3	58.42 [2.300]	23	2-641127-3
55.88 [2.200]	22	5-641127-2	55.88 [2.200]	22	2-641127-2
53.34 [2.100]	21	5-641127-1	53.34 [2.100]	21	2-641127-1
50.80 [2.000]	20	5-641127-0	50.80 [2.000]	20	2-641127-0
48.26 [1.900]	19	4-641127-9	48.26 [1.900]	19	1-641127-9
45.72 [1.800]	18	4-641127-8	45.72 [1.800]	18	1-641127-8
43.18 [1.700]	17	4-641127-7	43.18 [1.700]	17	1-641127-7
40.64 [1.600]	16	4-641127-6	40.64 [1.600]	16	1-641127-6
38.10 [1.500]	15	4-641127-5	38.10 [1.500]	15	1-641127-5
35.56 [1.400]	14	4-641127-4	35.56 [1.400]	14	1-641127-4
33.02 [1.300]	13	4-641127-3	33.02 [1.300]	13	1-641127-3
30.48 [1.200]	12	4-641127-2	30.48 [1.200]	12	1-641127-2
27.94 [1.100]	11	4-641127-1	27.94 [1.100]	11	1-641127-1
25.40 [1.000]	10	4-641127-0	25.40 [1.000]	10	1-641127-0
22.86 [.900]	9	3-641127-9	22.86 [.900]	9	-641127-9
20.32 [.800]	8	3-641127-8	20.32 [.800]	8	-641127-8
17.78 [.700]	7	3-641127-7	17.78 [.700]	7	-641127-7
15.24 [.600]	6	3-641127-6	15.24 [.600]	6	-641127-6
12.70 [.500]	5	3-641127-5	12.70 [.500]	5	-641127-5
10.16 [.400]	4	3-641127-4	10.16 [.400]	4	-641127-4
7.62 [.300]	3	3-641127-3	7.62 [.300]	3	-641127-3
5.08 [.200]	2	3-641127-2	5.08 [.200]	2	-641127-2

RECOMMENDED MOUNTING HOLE PATTERN FOR 1.60 [.063] THICK P.C. BOARD

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIN S. HOOVER 26-JAN-2005
 CJK D. ROSSI 26-JAN-2005
 APVO D. ROSSI 26-JAN-2005

TE Connectivity

MTA-100 HEADER ASSEMBLY, FRICTION LOCK, NOTCHED, .025 SQUARE RIGHT ANGLE POST, .000015 GOLD PLATED

APPLIC. SPEC: PRODUCT SPEC

SIZE: A1 CAGE CODE: 00779 DRAWING NO: 641127

WEIGHT: CUSTOMER DRAWING SCALE: 8:1 SHEET: 1 of 1 REV: AC2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for te connectivity manufacturer:

Other Similar products are found below :

[570416-000](#) [CLTEQ-M81CE-SSRELAY-4-20V](#) [D38999/24FJ4AN](#) [358838-000](#) [4-1195131-0](#) [650069-000](#) [SMD100-2](#) [CB-1022B-78](#)
[RM707012](#) [RP410012](#) [MMS42](#) [1-640426-8](#) [2EDL4CM](#) [DTS20W19-11PD-3028-LC](#) [RM202615](#) [NC6-P104-06](#) [MSPS103B](#) [DTS26F21-41AE](#) [DTS26F21-41PE-LC](#) [DTS26F21-11SE-3028-LC](#) [1932144-1](#) [293545-4](#) [LVR125S](#) [MS27466T25F4PB](#) [CKB-38-78010](#)
[1206SFF150F/63-2](#) [D38999/20JB35HA](#) [D38999/24WJ20PA](#) [1754138-1](#) [TE1500A2R2J](#) [DTS24F25-29PC-3028-LC](#) [D38999/24WG11HA](#)
[D38999/24WG11HN](#) [MS27467T21F11H](#) [DJT16E21-11HA](#) [1206SFH150F/24-2](#) [DTS24F19-11SC-3028-LC](#) [DTS24F21-41HN-LC](#)
[DTS24F21-41AN](#) [DTS24F21-41PN-LC](#) [RP330024](#) [MS27467T21F35J](#) [MS27467T21F11J](#) [MS27467T21F16H-LC](#) [MS27467T21F35H](#)
[MS27467T21F41H-LC](#) [DJT16E21-11PA-LC](#) [DJT16E21-11HA-LC](#) [DJT16E21-11AA](#) [MS27467T21B11JA](#)