



FINISH	NO. OF POSITIONS	PART NO.
OBSOLETE	18	6-644611-8
OBSOLETE	17	6-644611-7
OBSOLETE	16	6-644611-6
OBSOLETE	15	6-644611-5
OBSOLETE	14	6-644611-4
OBSOLETE	13	6-644611-3
OBSOLETE	12	6-644611-2
OBSOLETE	11	6-644611-1
OBSOLETE	10	6-644611-0
OBSOLETE	9	6-644611-9
OBSOLETE	8	6-644611-8
OBSOLETE	7	6-644611-7
OBSOLETE	6	6-644611-6
OBSOLETE	5	6-644611-5
OBSOLETE	4	6-644611-4
OBSOLETE	3	6-644611-3
OBSOLETE	2	6-644611-2
OBSOLETE	1	6-644611-1

- △ MATERIAL: THERMOPLASTIC POLYESTER/GLASS FILLED/UL94V-0.
- △ FINISH: COPPER ALLOY
- △ FINISH: NATURAL
- △ POST: BRIGHT TIN-LEAD (93/7) PLATE, 0.00350-0.00860, 0.00150-0.00350 THK OVER NICKEL UNDERPLATE, 0.00130(0.00095) MIN THK.
- △ UL MARKING MAY NOT APPEAR ON THE 2 OR 3 POSITION SIZES.
- △ CSA MARKING MAY NOT APPEAR ON THE 2 POSITION SIZE.
- △ POST SOLDERTALS COMPLY WITH AMP SOLDERABILITY SPEC 109-11-2.
- △ POST WITHSTANDS 1.3, 3.4N [3 LB] MIN AXIAL FORCE IN EITHER DIRECTION WITHOUT DISLODGING.
- △ APPLIES AT [E-1].
- △ APPLIES WHEN THE HEADER IS STRAIGHT.
- △ PLASTIC PROJECTIONS PERMITTED IN THIS ZONE.
- △ COORDINATE DIMENSIONS APPLIES FROM THE CENTER OF THE ACTUAL FEATURE.
- △ SOLDER SIDE OF BOARD IS SHOWN.
- △ 1 1 DIMENSIONS IN BRACKETS ARE IN INCHES.
- △ ALL POSITION SIZES HAVE THE BACKWALL NOTCHED ON BOTH ENDS TO ALLOW THE POST TO BE POSITIONED AT THE CENTER OF THE ACTUAL FEATURE.
- △ AT VARIOUS LOCATIONS (SEE TABLE FOR INTERRUPTION(S) LOCATIONS).
- △ WITHIN ±0.13 [0.005]
- △ EDGE OF POLARIZING LOOK WALL TO BE IN LINE WITH CENTERLINE OF ADJACENT POST
- △ NOTCH SHOWN MAY OR MAY NOT APPEAR.
- △ FINISH: NATURAL
- △ HOUSING: NATURAL
- △ POST: WHITE TIN PLATE 0.000150 MIN THICK OVER NICKEL.
- △ OBSOLETE PARTS: OBSOLETE DIS STREAMLINING PER DRAWING/D/SINISI.

RECOMMENDED MOUNTING HOLE PATTERN FOR 1.57[0.062] THICK P.C. BOARD

FINISH	NO. OF POSITIONS	PART NO.
OBSOLETE	18	6-644611-8
OBSOLETE	17	6-644611-7
OBSOLETE	16	6-644611-6
OBSOLETE	15	6-644611-5
OBSOLETE	14	6-644611-4
OBSOLETE	13	6-644611-3
OBSOLETE	12	6-644611-2
OBSOLETE	11	6-644611-1
OBSOLETE	10	6-644611-0
OBSOLETE	9	6-644611-9
OBSOLETE	8	6-644611-8
OBSOLETE	7	6-644611-7
OBSOLETE	6	6-644611-6
OBSOLETE	5	6-644611-5
OBSOLETE	4	6-644611-4
OBSOLETE	3	6-644611-3
OBSOLETE	2	6-644611-2
OBSOLETE	1	6-644611-1

THIS DRAWING IS A CONTROLLED DOCUMENT

DATE	REV	DESCRIPTION
01/01/00	1	INITIAL RELEASE
01/01/00	2	REVISION
01/01/00	3	REVISION
01/01/00	4	REVISION
01/01/00	5	REVISION
01/01/00	6	REVISION
01/01/00	7	REVISION
01/01/00	8	REVISION
01/01/00	9	REVISION
01/01/00	10	REVISION
01/01/00	11	REVISION
01/01/00	12	REVISION
01/01/00	13	REVISION
01/01/00	14	REVISION
01/01/00	15	REVISION
01/01/00	16	REVISION
01/01/00	17	REVISION
01/01/00	18	REVISION

MINI-156 HIGH ASYM. POLARIZED LOCK.
 SRT 045 S3 POSITION#R-B
 SRT 045 S3 POSITION#R-B
 SRT 045 S3 POSITION#R-B
 SRT 045 S3 POSITION#R-B

CUSTOMER DRAWING: A100779-644611

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009508121](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#) [67095-007LF](#) [68002-116](#) [68016-236H](#) [68648-049](#)