



RECOMMENDED P.C. BOARD HOLE LAYOUT

- 1 "AMP", "CSA", "V", AND "DATE CODE" WITH .062±.015 HIGH CHARACTERS WHERE SIZE PERMITS.
- 2 HOUSING: 1-70 POSITION SIZES MAY BE PPS, GLASS-FILLED OR PCT, GLASS-FILLED. POSITION SIZES GREATER THAN 70 WILL BE PPS, GLASS-FILLED.
- 3 CONTACT: PHOSPHOR BRONZE.
- 4 CONTACT FINISH: DUPLX PLATED 0.00076 [.000030] GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] BRIGHT TIN-LEAD ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
- 5 THESE DIMENSIONS PERTAIN TO CAVITY C'S ONLY, NOT TO CONTACT LOCATIONS.
- 6 POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE CONTACT BEAMS).
- 7 CSA LOGO INK STAMPED WHITE ON HOUSING.
- 8 PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
- 9 CONTACT FINISH: DUPLX PLATED 0.00076 [.000030] GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] MATTE TIN ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
- 10 ROHS 2002/95/EC COMPLIANT.
- 11 RECESSED AREA AROUND MOLD GATE IS OPTIONAL. THIS FEATURE IS ALLOWABLE ON EITHER SIDE OF HOUSING OR MAY NOT BE PRESENT AT ALL.
- 12 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

OBSOLETE	34.49	10	22	8-532956-0	
OBSOLETE	[1.358]				
OBSOLETE	39.57	12	26	7-532956-9	
OBSOLETE	[1.558]				
OBSOLETE	62.43	21	44	7-532956-8	
OBSOLETE	[2.458]				
OBSOLETE		79	160	7-532956-7	
OBSOLETE					
OBSOLETE	24.33	6	14	7-532956-6	
OBSOLETE	[.958]				
OBSOLETE	24.33	6	14	7-532956-5	
OBSOLETE	[.958]				
OBSOLETE	235.15	89	180	7-532956-4	
OBSOLETE	[9.258]				
OBSOLETE	260.55	99	200	7-532956-3	
OBSOLETE	[10.258]				
OBSOLETE	194.51	73	148	7-532956-2	
OBSOLETE	[7.658]				
OBSOLETE	184.35	69	140	7-532956-1	
OBSOLETE	[7.258]				
OBSOLETE	171.65	64	130	7-532956-0	
OBSOLETE	[6.758]				
OBSOLETE	169.11	63	128	6-532956-9	
OBSOLETE	[6.658]				
OBSOLETE	158.95	59	120	6-532956-8	
OBSOLETE	[6.258]				
OBSOLETE	146.25	54	110	6-532956-7	
OBSOLETE	[5.758]				
OBSOLETE	133.55	49	100	6-532956-6	
OBSOLETE	[5.258]				
OBSOLETE	128.47	47	96	6-532956-5	
OBSOLETE	[5.058]				
OBSOLETE	120.85	44	90	6-532956-4	
OBSOLETE	[4.758]				
OBSOLETE	113.23	42	86	6-532956-3	
OBSOLETE	[4.558]				
OBSOLETE	108.15	39	80	6-532956-2	
OBSOLETE	[4.258]				
OBSOLETE	97.99	35	72	6-532956-1	
OBSOLETE	[3.858]				
OBSOLETE	95.45	34	70	6-532956-0	
OBSOLETE	[3.758]				
OBSOLETE	82.75	29	60	5-532956-9	
OBSOLETE	[3.258]				
OBSOLETE	70.05	24	50	5-532956-8	
OBSOLETE	[2.758]				
OBSOLETE	57.35	19	40	5-532956-7	
OBSOLETE	[2.258]				
OBSOLETE	52.27	17	36	5-532956-6	
OBSOLETE	[2.058]				
OBSOLETE	44.65	14	30	5-532956-5	
OBSOLETE	[1.758]				
OBSOLETE	37.03	11	24	5-532956-4	
OBSOLETE	[1.458]				
OBSOLETE	31.95	9	20	5-532956-3	
OBSOLETE	[1.258]				
OBSOLETE	26.87	7	16	5-532956-2	
OBSOLETE	[1.058]				
OBSOLETE	21.79	5	12	5-532956-1	
OBSOLETE	[.858]				
FINISH	B	A	NO OF POSN	PART NUMBER	

OBSOLETE	34.49	10	22	3-532956-0	
OBSOLETE	[1.358]				
OBSOLETE	39.57	12	26	2-532956-9	
OBSOLETE	[1.558]				
OBSOLETE	62.43	21	44	2-532956-8	
OBSOLETE	[2.458]				
OBSOLETE					
OBSOLETE					
OBSOLETE	24.33	6	14	2-532956-6	
OBSOLETE	[.958]				
OBSOLETE	235.15	89	180	2-532956-4	
OBSOLETE	[9.258]				
OBSOLETE	260.55	99	200	2-532956-3	
OBSOLETE	[10.258]				
OBSOLETE	194.51	73	148	2-532956-2	
OBSOLETE	[7.658]				
OBSOLETE	184.35	69	140	2-532956-1	
OBSOLETE	[7.258]				
OBSOLETE	171.65	64	130	2-532956-0	
OBSOLETE	[6.758]				
OBSOLETE	169.11	63	128	1-532956-9	
OBSOLETE	[6.658]				
OBSOLETE	158.95	59	120	1-532956-8	
OBSOLETE	[6.258]				
OBSOLETE	146.25	54	110	1-532956-7	
OBSOLETE	[5.758]				
OBSOLETE	133.55	49	100	1-532956-6	
OBSOLETE	[5.258]				
OBSOLETE	128.47	47	96	1-532956-5	
OBSOLETE	[5.058]				
OBSOLETE	120.85	44	90	1-532956-4	
OBSOLETE	[4.758]				
OBSOLETE	113.23	42	86	1-532956-3	
OBSOLETE	[4.558]				
OBSOLETE	108.15	39	80	1-532956-2	
OBSOLETE	[4.258]				
OBSOLETE	97.99	35	72	1-532956-1	
OBSOLETE	[3.858]				
OBSOLETE	95.45	34	70	1-532956-0	
OBSOLETE	[3.758]				
OBSOLETE	82.75	29	60	532956-9	
OBSOLETE	[3.258]				
OBSOLETE	70.05	24	50	532956-8	
OBSOLETE	[2.758]				
OBSOLETE	57.35	19	40	532956-7	
OBSOLETE	[2.258]				
OBSOLETE	52.27	17	36	532956-6	
OBSOLETE	[2.058]				
OBSOLETE	44.65	14	30	532956-5	
OBSOLETE	[1.758]				
OBSOLETE	37.03	11	24	532956-4	
OBSOLETE	[1.458]				
OBSOLETE	31.95	9	20	532956-3	
OBSOLETE	[1.258]				
OBSOLETE	26.87	7	16	532956-2	
OBSOLETE	[1.058]				
OBSOLETE	21.79	5	12	532956-1	
OBSOLETE	[.858]				
FINISH	B	A	NO OF POSN	PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT. DIN K.L.CLOUSER/UTA 17JAN01 05/14/91
 CHK DOUG SARVER
 APVD DON FORKER 05/15/91
 NAME RECEPTACLE ASSY, MOD II, DBL ROW, 2.54 X 2.54 [.100 X .100] CL, GUIDE PIN EARS, CLOSED ENTRY, SHORT-POINT-OF-CONTACT

TOLERANCES UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS: mm [INCHES]
 0 PLC ± -
 1 PLC ± -
 2 PLC ± 0.13 [.005]
 3 PLC ± -
 4 PLC ± -
 ANGLES ± -

MATERIAL HOUSING: 2
 CONTACT: 3
 FINISH SEE TABLE

WEIGHT -
 A1 00779 C=532956
 CUSTOMER DRAWING SCALE 6:1 SHEET 1 OF 1 REV AF3

STE TE Connectivity

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[589158040000018](#) [MDF7C-18P-2.54DSA\(55\)](#) [FCN-230C068-11](#) [FCN-268F012-G/BD](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [FX4C-80S-1.27DSA](#) [FCN-214Q030-G/0](#) [FCN-234P048-G/0](#) [FCN-235D050-G/C](#) [210-93-314-41-105000](#) [2-22603-0](#) [MDF7-40DP-2.54DSA\(55\)](#) [AXG720047](#) [5031084030](#) [MIT-114-03-F-D-K](#) [55323-1519](#) [DF33-2P-3.3DSA\(24\)](#) [YFT-20-05-H-03-SB-K](#) [503308-3040](#) [026-6203-PDB](#) [027-6203-PDB](#) [069159702701000](#) [10123981-102LF](#) [101A10019X](#) [55650-0588-C](#) [68684-306](#) [75140-7012](#) [589159005003045](#) [194261-1](#) [FCN-268F024-G0D](#) [10124054-515LF](#) [68685-603](#) [8-1616154-3](#) [MIS-019-01-F-D](#) [589159005002045](#) [541371078](#) [IL-WX-10PB-HF-B-E1000E](#) [FCN-268M024-G/3D](#) [20021832-06016C1LF](#) [KX15-20KLDL-E1000E](#) [MDF7-16DP-2.54DSA\(55\)](#) [AXE810124](#) [FCN-214J100-G/0](#) [FCN-230C068-E/S](#) [AXE812124](#)