

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

MATED WITH
PASSEND ZU
HA 16

COPYRIGHT - By -

ALL RIGHTS RESERVED.

PROJEKT NR.:

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D6	ECR-17-009069	09FEB2018	SG	MKO

SCREW TERMINATION 4 M3x10.5

CRIMP TERMINATION 5 M3x10.5

SPRING CLAMP TERMINATION 6 M3x10.5

Contact arrangement / view from termination side

Contact arrangement / view from termination side

Contact arrangement / view from termination side

Contact arrangement / view from termination side

NOTES:

1 SUITABLE CRIMP CONTACTS: SERIES HE/HA
OUTER DIMENSIONS OF INSULATION: MAX. $\phi 3,2$ MMSUITABLE HOOD SIZE 5; 7; 9; 11: SERIES HA; HD
SUITABLE INSERTION AND EXTRACTION TOOL:
SCREWDRIVER 0,5x3 DIN 5264Strip lenght: Screw conection 10mm
Spring clamp conection 10mm Crimp conection 7.5mmSTANDARDS:
DIN EN 61984; DIN EN 60664-1PACKAGING:
5 SETS IN A CARTON, PRE-MOUNTEDSPECIAL PACKAGING: Krauss-Maffei
PACKAGING UNIT: 300 PIECESSPECIAL PACKAGING: Krauss-Maffei
PACKAGING UNIT: 150 PIECESSPECIAL PACKAGING: AIS
PACKAGING UNIT: 250 PIECESSPECIAL PACKAGING: WIELAND
PACKAGING UNIT: 100 PIECES

SEE TE CONNECTIVITY QUALITYMANAGEMENT PROCEDURE NO. 1.12

Panel cut-out for contact insert

when used without housing

Assembling instruction

DISTANCE FOR SAFETY
CONTACT MARKING MAX. 24 mm

1-3	1-2	1-0	0-4	0-7	0-6	0-5	2-9	1-9	7-9	7-8	1-8	2-8	1-7	7-2	7-1	2-3	1-1	DESCRIPTION / BENENNUNG	MATERIAL	COLOR / FARBE	ITEM NO. POS.	REMARKS / BEMERKUNGEN	
																		Pin insert screw	PBT	light beige	8	with stainless steel-fixing screw	
																		Pin insert screw	PBT	light beige	7	with stainless steel-fixing screw	
																		Pin insert screw	PBT	light beige	6	with AU contact	
																		Cover	PBT	light beige	5		
																		Cover	PBT	light beige	4		
																		Cover	PBT	light beige	3		
																		pin insert spring clamp	PBT	light beige	2		
																		pin insert crimp/screw	PBT	light beige	1		
HA-16-Sti.S-B1-16-WIE	HA-16-Sti.S-B1-16-AIS	HA-16-Sti.S-B17-32-KM	HA-16-Sti.S-B1-16-KM	HA-16-Sti.S-VA-B1-16	HA-16-Sti.S-VA-B17-32	HA-16-Sti.S-AU-B1-16	HA-16-Sti.S-C-B-49-64	HA-16-Sti.S-B-49-64	HA-16-Sti.S-C-B-49-64	HA-16-Sti.S-C-B-33-48	HA-16-Sti.S-B-33-48	HA-16-Sti.S-C-B-33-48	HA-16-Sti.S-B-17-32	HA-16-Sti.S-C-B-17-32	HA-16-Sti.S-C-B-17-32	HA-16-Sti.S-C-B-1-16	HA-16-Sti.S-B-1-16	HA-16-Sti.S-B-1-16	THIS DRAWING IS A CONTROLLED DOCUMENT.	DWN Schneider 09.02.2000			
																		DIMENSIONS: mm	CHK Schweiger 09.02.2000				
																		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC 1 PLC 2 PLC 3 PLC 4 PLC ANGLES FINISH	APVD Schweiger				
																		MATERIAL	PRODUCT SPEC 108-74007	NAME TE Connectivity			
																			APPLICATION SPEC 114-77009	SIZE A2	CAGE CODE 00779	DRAWING NO C=1103416	
																			WEIGHT	RESTRICTED TO			
																			CUSTOMER DRAWING	SCALE 1:1	SHEET 1 OF 1	REV D6	

1471-9 (1/15)

1103416

A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heavy Duty Power Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[1424439](#) [1424438](#) [09330062652](#) [605601-1](#) [6340G1](#) [6341G1](#) [6360G1](#) [6373G1](#) [6374g2](#) [6396G1](#) [647757-1](#) [6643411-1](#) [6646058-2](#) [6646137-1](#)
[6646138-1](#) [6646348-1](#) [6646479-1](#) [6646608-1](#) [6646786-1](#) [6646940-1](#) [6651525-1](#) [6651529-1](#) [6651778-1](#) [6651788-1](#) [696465-1](#) [696475-1](#)
[73000005059](#) [73000005349](#) [73000005642](#) [73080965046](#) [765-15-0080A](#) [765-16-0080B](#) [789.700-44](#) [789.700-54](#) [80-1010](#) [80-9](#) [827381-1](#)
[829992-1](#) [902-77-02113](#) [PL00U-301-10D10](#) [PM103MOOLOO](#) [PM212MOOLOO](#) [PM309FOOLOO](#) [PM324FOOLCH](#) [PMHPAF11S03](#)
[PMHPAF14S01](#) [PMHPAM14P05](#) [PMHPAS06](#) [PMHPBF14S01](#) [PP45PC12S](#)