


# 7-1393810-1 Product Details



7-1393810-1



Active

## Communications / Signal PC Board Relays



[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

### Product Highlights:

- V23154/Cradle Relay N Series
- DC Actuating System
- Input Voltage = 24 VDC
- Contact Arrangement = 6 Form A, 6PST-NO, 6 N/O
- Contact Current Rating = 2 Amps.

[View all Features](#) | [Find Similar Products](#)

[Previous 1 ... \[11\] 12 13 14 15 ... 20 Next](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Compare Products](#)
- [Contact Us About This Product](#)

## Documentation & Additional Information

### Product Drawings:

- None Available

### Catalog Pages/Data Sheets:

- None Available

### Product Specifications:

- None Available

### Application Specifications:

- None Available

### Instruction Sheets:

- None Available

### CAD Files:

- None Available

### Additional Information:

- [Product Line Information](#)

### Related Products:

- [Tooling](#)

## Product Features (Please use the Product Drawing for all design activity)

### Product Type Features:

- Termination Type = Through Hole

### Electrical Characteristics:

- Actuating System = DC
- Input Voltage (VDC) = 24
- Contact Current Rating (Amps.) = 2
- [Coil Resistance \(?\)](#) = 890
- Coil Power, Nominal (mW) = 650
- Dielectric Between Coil and Contacts (V rms) = 500

### Body Related Features:

- [Series](#) = V23154/Cradle Relay N
- Polarized = No

### Contact Related Features:

- Mounting Options = PC Board
- Enclosure = Dust Protected
- [FCC Part 68 Isolation](#) = No
- Approved Standards = None
- Contact Material = Silver, Gold Overlay
- Approx. Dimensions (L x W x H) (mm [in]) = 30.00 x 19.00 x 30.00 [1.181 x .748 x 1.181]
- Compatible Socket = Without
- Contact Type = Single
- Pin Configuration = Industry Standard

### Configuration Related Features:

- [Contact Arrangement](#) = 6 Form A, 6PST-NO, 6 N/O
- [Coil Magnetic System](#) = Non Polarized, Monostable
- Coil Suppression Diode = Without

### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240C, Wave solder capable to 260C, Wave solder capable to 265C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

### Other:

- Brand = Axicom

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Low Signal Relays - PCB category](#):*

*Click to view products by [TE Connectivity manufacturer](#):*

Other Similar products are found below :

[LZN4-US-DC12](#) [LZNQ4-US-DC24](#) [LZNQ4-US-DC48](#) [6-1617347-5](#) [6-1617353-3](#) [6-1617529-6](#) [M39016/20-054M](#) [67RPCX-3](#) [D3493L](#) [7-1393813-3](#) [741B8](#) [MF-11AM-24](#) [MF1201N12](#) [MF-17A-24](#) [FBR244D024/02CS](#) [80.010.4522.1](#) [FL-4036](#) [FLH-11D-6](#) [831A7](#) [MMS124](#) [FTR-B4GA006Z](#) [FW1210S02](#) [FW1521S01](#) [9-1393813-6](#) [9-1617582-5](#) [G6AK-2-H-DC5](#) [G6E-184P-ST-US-DC48](#) [G6G234CDC24](#) [A07A939BZ1-0388](#) [PZ-2A2420](#) [HB1-DC6V](#) [HB1-DC9V](#) [R10-14A10-240](#) [R10-14D10-12](#) [R10-5A10-120F](#) [R10-E1L8-S200](#) [R10-E2468-1](#) [R10-E4Z2-V700](#) [R10-T1L2N-115V](#) [R40-E1Z4-V50](#) [R40-E3Z4-V200](#) [R50-E2Y2-24](#) [HFW11130K01](#) [HFW1201W200](#) [RA30511121](#) [RA-5W-K](#) [RB06H2C12](#) [REL-MR- 60DC/21AU](#) [RG2ET-L-12V](#) [RG2ET-L2-9V](#)