

Holsworthy | Holsworthy Holco

TE Internal #: 7-1879645-2

Holsworthy Holco, Through-Hole Resistors, Precision Resistor, 7.2 x


2.5 mm, 2 Termination, Bandoliered, .5 %, Thin Film, Resistance

Class Up to $1k\Omega$

View on TE.com >



Passive Components > Resistors > Through-Hole Resistors



Resistor Type: Precision Resistor

Passive Component Dimensions: 7.2 x 2.5 mm

Number of Terminations: 2

Packaging Method: Bandoliered

Passive Component Tolerance: .5 %

Features

Product Type Features

Troduct Type realures	
Product Type	Fixed Resistor
Resistor Type	Precision Resistor
Element Type	Thin Film
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Voltage Rating	350 V
Passive Component Tolerance	.5 %
Resistance Class	Up to $1k\Omega$
Resistance Value	301 Ω
Power Rating	.25 W
Body Features	
Passive Component Lead Type	Axial-Leaded

Termination Features

Number of Terminations	2
Passive Component Termination Material Type	Tinned Copper Leads

Dimensions

Passive Component Dimensions 7.2 x 2.5 mm	
---	--



Usage Conditions		
Operating Temperature Range	-55 – 155 °C	
Temperature Coefficient	±50 ppm/°C	
Packaging Features		
Packaging Method	Bandoliered	

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUL 2021 (219) Candidate List Declared Against: JUN 2020 (209) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts
















Also in the Series | Holsworthy Holco



Customers Also Bought





















Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_7-1879645-2_BA.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_7-1879645-2_BA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_7-1879645-2_BA.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

1309350_PASSIVE_COMPONENT

English

Axial Leaded Precision Resistors - Type HOLCO Series

English

8-1773459-4_POWER_FILTERING_AND_RESISTIVE_SOLUTIONS_FOR_ELEVATORS_AND_ESCALATORS

English

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Metal Film Resistors - Through Hole category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

MF2S-6K8JI GP55S-1002-FTW GP55S-1004-FTW GP55S-4753-FTW QW210 RCFH-0.5-5TA RCFH-100-5TA RCFH-10-5TA RCFH-110-5TA RCFH-11M-5TA RCFH-12K-5TA RCFH-130K-5TA RCFH-13-5TA RCFH-13K-5TA RCFH-13M-5TA RCFH-150K-5TA RCFH-15-5TA RCFH-160-5TA RCFH-160K-5TA RCFH-16-5TA RCFH-180K-5TA RCFH-18K-5TA RCFH-1M-5TA RCFH-200-5TA RCFH-200K-5TA RCFH-20K-5TA RCFH-220K-5TA RCFH-220K-5TA RCFH-22K-5TA RCFH-22M-5TA RCFH-240K-5TA RCFH-24K-5TA RCFH-2-5TA RCFH-27-5TA RCFH-27K-5TA RCFH-27K-5TA RCFH-330-5TA RCFH-33-5TA RCFH-33M-5TA RCFH-360-5TA RCFH-360K-5TA RCFH-360K-5TA RCFH-3-36M-5TA RCFH-39-5TA RCFH-39K-5TA RCFH-3.9M-5TA RCFH-430-5TA RCFH-47K-5TA RCFH-510K-5TA RCFH-51-5TA