



- 1 HOUSING: FLAME RETARDANT, GLASS FILLED, POLYESTER, COLOR: BLACK. CONTACT: PHOSPHOR BRONZE
- 2 CONTACT: DUPLEX PLATED 0.76µm[.000030] MIN GOLD IN CONTACT AREA, 3.81-7.62µm[.000150-.000300] BRIGHT TIN-LEAD ON LEADS ALL OVER 1.27µm[.000050] MIN NICKEL
- 3 THESE DIMENSIONS PERTAIN TO CAVITY CENTERLINES ONLY - NOT TO CONTACT LOCATIONS
- 4 PART NUMBER AND DATE CODE ARE MARKED IN APPROXIMATE LOCATION SHOWN, EITHER SIDE.
- 5 TOLERANCE IS NON-CUMULATIVE.
- 6 2 POSITION DATE CODE IS MARKED OPPOSITE SIDE OF TE CONNECTIVITY LOGO.
- 7 POINT-OF-MEASUREMENT DIMENSION FOR PLATING THICKNESS (INSIDE CONTACT BEAM).
- 8 POINT-OF-CONTACT DIMENSION.
- 9 NO PART NUMBER MARKING REQUIRED FOR THIS PART.
- 10 TE LOGO AND CSA LOGO ARE MOLDED INTO HOUSING.
- 11 CONTACT: DUPLEX PLATED 0.76µm[.000030] MIN GOLD IN CONTACT AREA, 3.81-7.62µm[.000150-.000300] MATTE TIN ON LEADS ALL OVER 1.27µm[.000050] MIN NICKEL
- 12 ROHS 2002/95/EC COMPLIANT.

6	9	OBSOLETE		2.54 [.100]	5.08 [.200]	2	12	8-535541-9
		99.06 [3.900]	101.60 [4.000]	40	12	8-535541-8		
		96.52 [3.800]	99.06 [3.900]	39	12	8-535541-7		
		93.98 [3.700]	96.52 [3.800]	38	12	8-535541-6		
		91.44 [3.600]	93.98 [3.700]	37	12	8-535541-5		
		88.90 [3.500]	91.44 [3.600]	36	12	8-535541-4		
		86.36 [3.400]	88.90 [3.500]	35	12	8-535541-3		
		83.82 [3.300]	86.36 [3.400]	34	12	8-535541-2		
		81.28 [3.200]	83.82 [3.300]	33	12	8-535541-1		
		78.74 [3.100]	81.28 [3.200]	32	12	8-535541-0		
		76.20 [3.000]	78.74 [3.100]	31	12	7-535541-9		
		73.66 [2.900]	76.20 [3.000]	30	12	7-535541-8		
		71.12 [2.800]	73.66 [2.900]	29	12	7-535541-7		
		68.58 [2.700]	71.12 [2.800]	28	12	7-535541-6		
		66.04 [2.600]	68.58 [2.700]	27	12	7-535541-5		
		63.50 [2.500]	66.04 [2.600]	26	12	7-535541-4		
		60.96 [2.400]	63.50 [2.500]	25	12	7-535541-3		
		58.42 [2.300]	60.96 [2.400]	24	12	7-535541-2		
		55.88 [2.200]	58.42 [2.300]	23	12	7-535541-1		
		53.34 [2.100]	55.88 [2.200]	22	12	7-535541-0		
		50.80 [2.000]	53.34 [2.100]	21	12	6-535541-9		
		48.26 [1.900]	50.80 [2.000]	20	12	6-535541-8		
		45.72 [1.800]	48.26 [1.900]	19	12	6-535541-7		
		43.18 [1.700]	45.72 [1.800]	18	12	6-535541-6		
		40.64 [1.600]	43.18 [1.700]	17	12	6-535541-5		
		38.10 [1.500]	40.64 [1.600]	16	12	6-535541-4		
		35.56 [1.400]	38.10 [1.500]	15	12	6-535541-3		
		33.02 [1.300]	35.56 [1.400]	14	12	6-535541-2		
		30.48 [1.200]	33.02 [1.300]	13	12	6-535541-1		
		27.94 [1.100]	30.48 [1.200]	12	12	6-535541-0		
		25.40 [1.000]	27.94 [1.100]	11	12	5-535541-9		
		22.86 [.900]	25.40 [1.000]	10	12	5-535541-8		
		20.32 [.800]	22.86 [.900]	9	12	5-535541-7		
		17.78 [.700]	20.32 [.800]	8	12	5-535541-6		
		15.24 [.600]	17.78 [.700]	7	12	5-535541-5		
		12.70 [.500]	15.24 [.600]	6	12	5-535541-4		
		10.16 [.400]	12.70 [.500]	5	12	5-535541-3		
		7.62 [.300]	10.16 [.400]	4	12	5-535541-2		
		5.08 [.200]	7.62 [.300]	3	12	5-535541-1		
		FINISH	B	A	NO OF POSN	PART NUMBER		

9	2.54 [.100]	5.08 [.200]	2	12	3-535541-9
	99.06 [3.900]	101.60 [4.000]	40	12	3-535541-8
	96.52 [3.800]	99.06 [3.900]	39	12	3-535541-7
	93.98 [3.700]	96.52 [3.800]	38	12	3-535541-6
	91.44 [3.600]	93.98 [3.700]	37	12	3-535541-5
	88.90 [3.500]	91.44 [3.600]	36	12	3-535541-4
	86.36 [3.400]	88.90 [3.500]	35	12	3-535541-3
	83.82 [3.300]	86.36 [3.400]	34	12	3-535541-2
	81.28 [3.200]	83.82 [3.300]	33	12	3-535541-1
	78.74 [3.100]	81.28 [3.200]	32	12	3-535541-0
	76.20 [3.000]	78.74 [3.100]	31	12	2-535541-9
	73.66 [2.900]	76.20 [3.000]	30	12	2-535541-8
	71.12 [2.800]	73.66 [2.900]	29	12	2-535541-7
	68.58 [2.700]	71.12 [2.800]	28	12	2-535541-6
	66.04 [2.600]	68.58 [2.700]	27	12	2-535541-5
	63.50 [2.500]	66.04 [2.600]	26	12	2-535541-4
	60.96 [2.400]	63.50 [2.500]	25	12	2-535541-3
	58.42 [2.300]	60.96 [2.400]	24	12	2-535541-2
	55.88 [2.200]	58.42 [2.300]	23	12	2-535541-1
	53.34 [2.100]	55.88 [2.200]	22	12	2-535541-0
	50.80 [2.000]	53.34 [2.100]	21	12	1-535541-9
	48.26 [1.900]	50.80 [2.000]	20	12	1-535541-8
	45.72 [1.800]	48.26 [1.900]	19	12	1-535541-7
	43.18 [1.700]	45.72 [1.800]	18	12	1-535541-6
	40.64 [1.600]	43.18 [1.700]	17	12	1-535541-5
	38.10 [1.500]	40.64 [1.600]	16	12	1-535541-4
	35.56 [1.400]	38.10 [1.500]	15	12	1-535541-3
	33.02 [1.300]	35.56 [1.400]	14	12	1-535541-2
	30.48 [1.200]	33.02 [1.300]	13	12	1-535541-1
	27.94 [1.100]	30.48 [1.200]	12	12	1-535541-0
	25.40 [1.000]	27.94 [1.100]	11	12	535541-9
	22.86 [.900]	25.40 [1.000]	10	12	535541-8
	20.32 [.800]	22.86 [.900]	9	12	535541-7
	17.78 [.700]	20.32 [.800]	8	12	535541-6
	15.24 [.600]	17.78 [.700]	7	12	535541-5
	12.70 [.500]	15.24 [.600]	6	12	535541-4
	10.16 [.400]	12.70 [.500]	5	12	535541-3
	7.62 [.300]	10.16 [.400]	4	12	535541-2
	5.08 [.200]	7.62 [.300]	3	12	535541-1
	FINISH	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN M. BINNER 05NOV02	APVD J. JOLSON 05NOV02	NAME J. JOLSON 05NOV02
0 PL ± -	1 PL ± -	2 PL ± 0.25[.010]	3 PL ± 0.13[.005]	4 PL ± -
MATERIAL FINISH		WEIGHT -	SIZE A1	CAGE CODE DRAWING NO 00779
CUSTOMER DRAWING		SCALE 4:1	SHEET 1 of 1	REV N6

RECP.TASSY, MOD IV, SINGLE ROW, .100CL, VERTICAL BOARD MOUNT, CLOSED, TOP ENTRY, SHORT PNT. OF CONTACT

STE TE Connectivity

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)
[609-3404](#) [61062-3](#) [61082-181009](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-](#)
[010LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68645-018](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#)
[FCN-360C032-B](#) [FCN-367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#)